



Relational Calculus

Chapter 4, Part B



Relational Calculus

- ❖ Comes in two flavors: Tuple relational calculus (TRC) and Domain relational calculus (DRC).
- ❖ Calculus has *variables*, *constants*, *comparison ops*, *logical connectives* and *quantifiers*.
 - TRC: Variables range over (i.e., get bound to) *tuples*.
 - DRC: Variables range over *domain elements* (= field values).
 - Both TRC and DRC are simple subsets of first-order logic.
- ❖ Expressions in the calculus are called *formulas*. An answer tuple is essentially an assignment of constants to variables that make the formula evaluate to *true*.




Domain Relational Calculus

❖ *Query* has the form:

$$\{ \langle x_1, x_2, \dots, x_n \rangle \mid p(\langle x_1, x_2, \dots, x_n \rangle) \}$$

❖ *Answer* includes all tuples $\langle x_1, x_2, \dots, x_n \rangle$ that make the *formula* $p(\langle x_1, x_2, \dots, x_n \rangle)$ be *true*.

❖ *Formula* is recursively defined, starting with simple *atomic formulas* (getting tuples from relations or making comparisons of values), and building bigger and better formulas using the *logical connectives*.




DRC Formulas

❖ *Atomic formula:*

- $\langle x_1, x_2, \dots, x_n \rangle \in Rname$, or $X \text{ op } Y$, or $X \text{ op } \text{constant}$
- *op* is one of $<, >, =, \leq, \geq, \neq$

❖ *Formula:*

- an atomic formula, or
 - $\neg p, p \wedge q, p \vee q$, where p and q are formulas, or
 - $\exists X (p(X))$, where variable X is *free* in $p(X)$, or
 - $\forall X (p(X))$, where variable X is *free* in $p(X)$
- ❖ The use of quantifiers $\exists X$ and $\forall X$ is said to *bind* X .
- A variable that is not bound is free.




Free and Bound Variables

- ❖ The use of quantifiers $\exists X$ and $\forall X$ in a formula is said to bind X .
 - A variable that is not bound is free.
- ❖ Let us revisit the definition of a query:

$$\left\{ \langle x_1, x_2, \dots, x_n \rangle \mid p(\langle x_1, x_2, \dots, x_n \rangle) \right\}$$


- ❖ There is an important restriction: the variables x_1, \dots, x_n that appear to the left of `|` must be the *only* free variables in the formula $p(\dots)$.

Find all sailors with a rating above 7



$$\{ \langle I, N, T, A \rangle \mid \langle I, N, T, A \rangle \in \text{Sailors} \wedge T > 7 \}$$


- ❖ The condition $\langle I, N, T, A \rangle \in \text{Sailors}$ ensures that the domain variables I , N , T and A are bound to fields of the same Sailors tuple.
- ❖ The term $\langle I, N, T, A \rangle$ to the left of `|` (which should be read as *such that*) says that every tuple $\langle I, N, T, A \rangle$ that satisfies $T > 7$ is in the answer.
- ❖ Modify this query to answer:
 - Find sailors who are older than 18 or have a rating under 9, and are called 'Joe'.



Find sailors rated > 7 who've reserved boat #103

$$\left\{ \langle I, N, T, A \rangle \mid \langle I, N, T, A \rangle \in \text{Sailors} \wedge T > 7 \wedge \right. \\ \left. \exists Ir, Br, D \left(\langle Ir, Br, D \rangle \in \text{Reserves} \wedge Ir = I \wedge Br = 103 \right) \right\}$$

- ❖ We have used $\exists Ir, Br, D (\dots)$ as a shorthand for $\exists Ir (\exists Br (\exists D (\dots)))$
- ❖ Note the use of \exists to find a tuple in Reserves that 'joins with' the Sailors tuple under consideration.




Find sailors rated > 7 who've reserved a red boat

$$\left\{ \left\langle I, N, T, A \right\rangle \mid \left\langle I, N, T, A \right\rangle \in \text{Sailors} \wedge T > 7 \wedge \right. \\ \left. \exists Ir, Br, D \left(\left\langle Ir, Br, D \right\rangle \in \text{Reserves} \wedge Ir = I \wedge \right. \right. \\ \left. \left. \exists B, BN, C \left(\left\langle B, BN, C \right\rangle \in \text{Boats} \wedge B = Br \wedge C = 'red' \right) \right) \right\}$$


- ❖ Observe how the parentheses control the scope of each quantifier's binding.
- ❖ This may look cumbersome, but with a good user interface, it is very intuitive. (MS Access, QBE)

Find sailors who've reserved all boats



$$\left\{ \langle I, N, T, A \rangle \mid \langle I, N, T, A \rangle \in \text{Sailors} \wedge \right. \\ \left. \forall B, BN, C \left(\neg \left(\langle B, BN, C \rangle \in \text{Boats} \right) \vee \right. \right. \\ \left. \left. \left(\exists Ir, Br, D \left(\langle Ir, Br, D \rangle \in \text{Reserves} \wedge I = Ir \wedge Br = B \right) \right) \right) \right\}$$

- ❖ Find all sailors I such that for each 3-tuple $\langle B, BN, C \rangle$ either it is not a tuple in Boats or there is a tuple in Reserves showing that sailor I has reserved it.




Find sailors who've reserved all boats (again!)

$$\left\{ \langle I, N, T, A \rangle \mid \langle I, N, T, A \rangle \in \text{Sailors} \wedge \right. \\ \left. \forall \langle B, BN, C \rangle \in \text{Boats} \right. \\ \left. \left(\exists \langle Ir, Br, D \rangle \in \text{Reserves} (I = Ir \wedge Br = B) \right) \right\}$$


- ❖ Simpler notation, same query. (Much clearer!)
- ❖ To find sailors who've reserved all red boats:

$$\dots \left\{ C \neq 'red' \vee \exists \langle Ir, Br, D \rangle \in \text{Reserves} (I = Ir \wedge Br = B) \right\}$$



Unsafe Queries, Expressive Power

- ❖ It is possible to write syntactically correct calculus queries that have an infinite number of answers! Such queries are called unsafe.
 - e.g., $\{S \mid \neg (S \in Sailors)\}$
- ❖ It is known that every query that can be expressed in relational algebra can be expressed as a safe query in DRC / TRC; the converse is also true.
- ❖ Relational Completeness: Query language (e.g., SQL) can express every query that is expressible in relational algebra/calculus.



Summary

- ❖ Relational calculus is non-operational, and users define queries in terms of what they want, not in terms of how to compute it. (Declarativeness.)
- ❖ Algebra and safe calculus have same expressive power, leading to the notion of relational completeness.