

Implementing Array Lists

What is an array?

- ▶ Contiguous area of memory to store data
- ▶ Fixed length
- ▶ Each item can be directly accessed by its index: $0..length-1$
- ▶ Less overhead than other data structures

How to define an array?

- ▶ double[] collection = new double[SIZE];
- ▶ Students[] lecture = new Student[SIZE];
- ▶ String[] dictionary = {"apple", "banana", "cherry", "grape", "orange", "plum"};
- ▶ int[] bag = {5, 8, 32, 17, 22};

Using arrays

- ▶ Access elements
 - `double thirdNum = collection[2];`
- ▶ Write elements
 - `collection[0] = 5.0;`
- ▶ Determine length
 - `int lengthOfArray = collection.length;`

Command Line Arguments

- ▶ You've seen arrays before...

```
public static void main(String[ ] args)
```

- ▶ Running a main class (e.g., "Foo")...

```
java Foo one two three
```

- ▶ Will have the following elements passed as arguments in the String array args:
 - ["one", "two", "three"]

Using arrays in a for-loop

- ▶ Writing the contents of the array:

```
for(int i = 0; i < collection.length; i++)  
{  
    System.out.println(collection[i]);  
}
```

or

```
for(Double n : collection)  
{  
    System.out.println(n);  
}
```

ArrayList implementation

```
public class MyArrayList
{
    public final int DEFAULT_SIZE = 10;
    private int size;
    private Character[] array;

    public MyArrayList()
    {
        array = new Character[DEFAULT_SIZE];
        size = 0;
    }

    ...
}
```

getSize()

```
public int getSize()  
{  
    return size;  
}
```

set()

```
public void set(int index, Character c)
{
    array[index] = c;
}
```

toString()

```
public String toString()
{
    StringBuilder sb = new StringBuilder();
    sb.append("[");
    toString(0, sb);
    sb.append("]");
    return sb.toString();
}

private void toString(int index, StringBuilder sb)
{
    if (index < getSize() - 1)
    {
        sb.append(array[index] + ", ");
        toString(index + 1, sb);
    }
    else if (index < getSize())
    {
        sb.append(array[index]);
    }
}
```

add() – version 1

```
public void add(int index, Character c)
{
    if (index < 0 || index > getSize())
    {
        throw new IndexOutOfBoundsException();
    }

    // Assumes available space in array.
    if (getSize() == 0 || getSize() == index)
    {
        array[index] = c;
    }
    else
    {
        shiftTowardsEnd(index, getSize() - 1);
        array[index] = c;
    }
    size++;
}
```

add() - version 1

```
// Shift elements by one towards the end of the array
// Assumes available space in array.
private void shiftTowardsEnd(int index, int current)
{
    if (current >= index)
    {
        array[current + 1] = array[current];
        shiftTowardsEnd(index, current - 1);
    }
}
```

remove()

```
public Character remove(int index)
{
    Character result = array[index];
    shiftTowardsStart(index + 1);
    size--;
    return result;
}

// Shift elements by one towards the start of the array
private void shiftTowardsStart(int current)
{
    array[current - 1] = array[current];
    if (current == getSize() - 1)
    {
        array[current] = null;
    }
    else
    {
        shiftTowardsStart(current + 1);
    }
}
```

add() – version 2

```
public void add(int index, Character c)
{
    // Check for valid index...

    Character[] newArray = new Character[2 * array.length];
    copyArray(array, newArray, 0);
    array = newArray;

    // Same as before...
}

private void copyArray(Character[] from, Character[] to, int index)
{
    if (index < getSize())
    {
        to[index] = from[index];
        copyArray(from, to, index + 1);
    }
}
```

Big-O running time

- ▶ getSize():
- ▶ set():
- ▶ toString():
- ▶ add():
- ▶ remove():

Big-O running time

- ▶ `getSize()`: $O(1)$
- ▶ `set()`: $O(1)$
- ▶ `toString()`: $O(n)$
- ▶ `add()`: $O(n)$
- ▶ `remove()`: $O(n)$

Using Generics

- ▶ Allows data structures in Java to hold elements of any data type
 - E.g.: examples: List<E>, Map<E>, Set<E>, etc.
- ▶ Specific type is indicated during declaration
- ▶ MyArrayList
 - public class MyArrayList<E>
 - Replace “Character” with “E”
 - private E[] array
 - array = (E[]) new Object[DEFAULT_SIZE];
 - etc.