

Consider the following Java code:

```
1 boolean isSorted(int[] a) {
2     return isSortedHelper(a, 0, a.length - 1);
3 }
4 boolean isSortedHelper(int[] a, int from, int to) {
5     if (from > to) {
6         return true;
7     }
8     else if (from == to) {
9         return true;
10    }
11    else {
12        return a[from] <= a[from + 1]
13            && isSortedHelper(a, from + 1, to);
14    }
15 }
```

Prove, via mathematical induction, that the method `isSorted` method above correctly returns `true` if the array `a` is sorted in a non-descending order; and `false` otherwise.

Solution:

We first prove that the recursive helper method `isSortedHelper` (Line 4 – Line 15) is correct (i.e., is the subarray $\{a[\text{from}], a[\text{from} + 1], \dots, a[\text{to}]\}$ sorted).

1. Base Cases

- (a) **Concept:** In an empty array, there is no witness (i.e., adjacent numbers that are not sorted) \therefore result is `true`.
- (b) **Link to Code:** **Lines 5 – 7 (or just Line 6)** of the above code does this.
- (c) **Concept:** In an array of size 1, the only one element is automatically sorted.
- (d) **Link to Code:** **Lines 8 – 10 (or just Line 9)** of the above code does this.

2. Inductive Cases

- (a) **Inductive Hypothesis (I.H.):** The recursive call `isSortedHelper(a, from + 1, to)` returns `true` if $a[\text{from} + 1], a[\text{from} + 2], \dots, a[\text{to}]$ are sorted in a non-descending order; `false` otherwise.
- (b) **Concept:** `isSortedHelper(a, from, to)` should return `true` if:
 - 1) $a[\text{from}] \leq a[\text{from} + 1]$; **and**
 - 2) the subarray $\{a[\text{from} + 1], \dots, a[\text{to}]\}$ is sorted.
- (c) **Link to I.H.:** By I.H., condition **2)** is satisfied.
- (d) **Link to Code:** **Line 12** in the above code does condition **1)**.
 \therefore **Lines 12 – Line 13** perform a correct combination.

3. Given that the recursive helper method `isSortedHelper` (Line 4 – Line 4) is correct, we now argue that the method `isSorted` (Line 1 – Line 3) is correct.

- (a) **Concept:** `isSorted(a)` is correct by invoking `isSortedHelper(a, 0, a.length - 1)`, examining the entire array.
- (b) **Link to Code:** **Line 2** of the above code does this.