

TEST 2 REVIEW
FRIDAY NOVEMBER 22

```
class Collector {
```

```
    List cs;
```

```
    void add(C obj) { ... }
```


```
}
```

Collector C = new Coll. C;
 C.add(D) new B();

① valid down cast from B to D

ClassCastException
 the type of D cast into is an ancestor of the DL.

② ClassCastException
 is DL B is not descen. of D.



B obj = new C();

A oa = (A) obj;

B ob = (A) obj;

~~D od = (D) obj;~~
 down

X E oe = (E) obj;

- Inheritance

↳ try eclipse demo

↳ practice test

↳ class Collector {

 ↳ void add(C oc) { ... }

∴ B ^{cannot fulfill} C. Collector c = _____
 X c.add(new B());

No
RECURSION

- hashCode
- equals


/ call by value / collection

(C)

agg.




lc2. getLineAt(0). getStart(). getX()

lc2. getLineAt(0). getStart(). setX(100)



Comp. - lc2. getLineAt(0). getStart(). getX(c)


lc2. getLineAt(0). getStart(). setX(100)



Implementing a Hash Table via Hashing

$k_1 \text{ equals } (k_2) \Rightarrow hc(k_1) = hc(k_2)$

- Converting k to $hc(k)$
- Indexing into $A[hc(k)]$




For illustration, assume $A.length$ is 11 and $hc(k) = k \% 11$

$hc(k) = k \% 11$	(SEARCH) KEY	VALUE
	1	D
	25	C
	3	F
	14	Z
	6	A
	39	C
	7	Q

bucket array

search (3)

$hc(3) = 3$



collision: distinct keys map to same hashCode

```
class A {  
    B b;  
    C c;  
}
```


```
void c() {  
    b = c.a.b  
} B A B
```

```
class B {  
    A a;  
    C c;  
}
```

```
class C {  
    A a;  
    B b;  
}
```

obj instance of C

↳ TRUE if ① the dynamic type of obj can fulfill the expectations on C.




SmartPhone p =
new IOS();

p instance of SmartPhone (T)

p instance of IOS (T) (2)

p instance of IPillPro (F)

the DT of obj is a descendant of C.



$$(2+3) + (3 \times 4) + (3 > 4)$$

Haskell
↳ functional programming.

Implement Map keys & values

Naive Solution



$O(n)$

