



## Abstract Classes and Interfaces

EECS2030 B: Advanced  
Object Oriented Programming  
Fall 2019

CHEN-WEI WANG



## Abstract Class (2)

```
public abstract class Polygon {  
    double[] sides;  
    Polygon(double[] sides) { this.sides = sides; }  
    void grow() {  
        for(int i = 0; i < sides.length; i++) { sides[i]++; }  
    }  
    double getPerimeter() {  
        double perimeter = 0;  
        for(int i = 0; i < sides.length; i++) {  
            perimeter += sides[i];  
        }  
        return perimeter;  
    }  
    abstract double getArea();  
}
```

- Method `getArea` not implemented and shown **signature** only.
- ∴ `Polygon` cannot be used as a **dynamic type**
- Writing `new Polygon(...)` is forbidden!

3 of 20

## Abstract Class (1)



**Problem:** A polygon may be either a triangle or a rectangle.  
Given a polygon, we may either

- **Grow** its shape by incrementing the size of each of its sides;
  - Compute and return its **perimeter**; or
  - Compute and return its **area**.
- For a rectangle with *length* and *width*, its area is  $length \times width$ .
  - For a triangle with sides *a*, *b*, and *c*, its area, according to Heron's formula, is

$$\sqrt{s(s-a)(s-b)(s-c)}$$

where

$$s = \frac{a+b+c}{2}$$

- How would you solve this problem in Java, while **minimizing code duplicates**?

2 of 20



## Abstract Class (3)

```
public class Rectangle extends Polygon {  
    Rectangle(double length, double width) {  
        super(new double[4]);  
        sides[0] = length; sides[1] = width;  
        sides[2] = length; sides[3] = width;  
    }  
    double getArea() { return sides[0] * sides[1]; }  
}
```

- Method `getPerimeter` is inherited from the super-class `Polygon`.
- Method `getArea` is implemented in the sub-class `Rectangle`.
- ∴ `Rectangle` can be used as a **dynamic type**
- Writing `Polygon p = new Rectangle(3, 4)` allowed!

4 of 20

## Abstract Class (4)



```
public class Triangle extends Polygon {
    Triangle(double side1, double side2, double side3) {
        super(new double[3]);
        sides[0] = side1; sides[1] = side2; sides[2] = side3;
    }
    double getArea() {
        /* Heron's formula */
        double s = getPerimeter() * 0.5;
        double area = Math.sqrt(
            s * (s - sides[0]) * (s - sides[1]) * (s - sides[2]));
        return area;
    }
}
```

- Method `getPerimeter` is inherited from `Polygon`.
- Method `getArea` is implemented in the sub-class `Triangle`.
- ∴ `Triangle` can be used as a **dynamic type**
- Writing `Polygon p = new Triangle(3, 4, 5)` allowed!

5 of 20

## Abstract Class (5)




```
1 public class PolygonCollector {
2     Polygon[] polygons;
3     int numberOfPolygons;
4     PolygonCollector() { polygons = new Polygon[10]; }
5     void addPolygon(Polygon p) {
6         polygons[numberOfPolygons] = p; numberOfPolygons++;
7     }
8     void growAll() {
9         for(int i = 0; i < numberOfPolygons; i++) {
10             polygons[i].grow();
11         }
12     }
13 }
```

- **Polymorphism:** Line 5 may accept as argument any object whose **static type** is `Polygon` or any of its sub-classes.
- **Dynamic Binding:** Line 10 calls the version of `grow` inherited to the **dynamic type** of `polygons[i]`.

6 of 20

## Abstract Class (6)



```
1 public class PolygonConstructor {
2     Polygon getPolygon(double[] sides) {
3         Polygon p = null;
4         if(sides.length == 3) {
5             p = new Triangle(sides[0], sides[1], sides[2]);
6         }
7         else if(sides.length == 4) {
8             p = new Rectangle(sides[0], sides[1]);
9         }
10        return p;
11    }
12    void grow(Polygon p) { p.grow(); }
13 }
```

- **Polymorphism:**

- Line 2 may accept as return value any object whose **static type** is `Polygon` or any of its sub-classes.
- Line 5 returns an object whose **dynamic type** is `Triangle`; Line 8 returns an object whose **dynamic type** is `Rectangle`.

7 of 20

## Abstract Class (7.1)



```
1 public class PolygonTester {
2     public static void main(String[] args) {
3         Polygon p;
4         p = new Rectangle(3, 4); /* polymorphism */
5         System.out.println(p.getPerimeter()); /* 14.0 */
6         System.out.println(p.getArea()); /* 12.0 */
7         p = new Triangle(3, 4, 5); /* polymorphism */
8         System.out.println(p.getPerimeter()); /* 12.0 */
9         System.out.println(p.getArea()); /* 6.0 */
10
11     PolygonCollector col = new PolygonCollector();
12     col.addPolygon(new Rectangle(3, 4)); /* polymorphism */
13     col.addPolygon(new Triangle(3, 4, 5)); /* polymorphism */
14     System.out.println(col.polygons[0].getPerimeter()); /* 14.0 */
15     System.out.println(col.polygons[1].getPerimeter()); /* 12.0 */
16     col.growAll();
17     System.out.println(col.polygons[0].getPerimeter()); /* 18.0 */
18     System.out.println(col.polygons[1].getPerimeter()); /* 15.0 */
19 }
```

8 of 20

## Abstract Class (7.2)



```

1  PolygonConstructor con = new PolygonConstructor();
2  double[] recSides = {3, 4, 3, 4}; p = con.getPolygon(recSides);
3  System.out.println(p instanceof Polygon); ✓
4  System.out.println(p instanceof Rectangle); ✓
5  System.out.println(p instanceof Triangle); ✗
6  System.out.println(p.getPerimeter()); /* 14.0 */
7  System.out.println(p.getArea()); /* 12.0 */
8  con.grow(p);
9  System.out.println(p.getPerimeter()); /* 18.0 */
10 System.out.println(p.getArea()); /* 20.0 */
11 double[] triSides = {3, 4, 5}; p = con.getPolygon(triSides);
12 System.out.println(p instanceof Polygon); ✓
13 System.out.println(p instanceof Rectangle); ✗
14 System.out.println(p instanceof Triangle); ✓
15 System.out.println(p.getPerimeter()); /* 12.0 */
16 System.out.println(p.getArea()); /* 6.0 */
17 con.grow(p);
18 System.out.println(p.getPerimeter()); /* 15.0 */
19 System.out.println(p.getArea()); /* 9.921 */
20 }
```

9 of 20

## Abstract Class (8)




- An **abstract class**:
  - Typically has **at least one** method with no implementation body
  - May define common implementations inherited to **sub-classes**.
- Recommended to use an **abstract class** as the **static type** of:
  - A **variable**  
e.g., `Polygon p`
  - A **method parameter**  
e.g., `void grow(Polygon p)`
  - A **method return value**  
e.g., `Polygon getPolygon(double[] sides)`
- It is forbidden to use an **abstract class** as a **dynamic type**  
e.g., `Polygon p = new Polygon(...)` is not allowed!
- Instead, create objects whose **dynamic types** are descendant classes of the **abstract class** ⇒ Exploit **dynamic binding**!  
e.g., `Polygon p = con.getPolygon(recSides)`  
This is as if we did `Polygon p = new Rectangle(...)`

10 of 20

## Interface (1.1)



- We may implement `Point` using two representation systems:



- The **Cartesian system** stores the **absolute** positions of **x** and **y**.
- The **Polar system** stores the **relative** position: the angle (in radian) **phi** and distance **r** from the origin (0,0).


- As far as users of a `Point` object `p` is concerned, being able to call `p.getX()` and `p.getY()` is what matters.
- How `p.getX()` and `p.getY()` are internally computed, depending on the **dynamic type** of `p`, do not matter to users.

11 of 20

## Interface (1.2)



Recall:  $\sin 30^\circ = \frac{1}{2}$  and  $\cos 30^\circ = \frac{1}{2} \cdot \sqrt{3}$



We consider the same point represented differently as:

- $r = 2a, \psi = 30^\circ$  [polar system]
- $x = 2a \cdot \cos 30^\circ = a \cdot \sqrt{3}, y = 2a \cdot \sin 30^\circ = a$  [cartesian system]

12 of 20

## Interface (2)



```
interface Point {  
    double getX();  
    double getY();  
}
```

- An interface `Point` defines how users may access a point: either get its `x` coordinate or its `y` coordinate.
- Methods `getX` and `getY` similar to `getArea` in `Polygon`, have no implementations, but *signatures* only.
- ∴ `Point` cannot be used as a **dynamic type**
- Writing `new Point(...)` is forbidden!

13 of 20

## Interface (3)



```
public class CartesianPoint implements Point {  
    double x;  
    double y;  
    CartesianPoint(double x, double y) {  
        this.x = x;  
        this.y = y;  
    }  
    public double getX() { return x; }  
    public double getY() { return y; }  
}
```

- `CartesianPoint` is a possible implementation of `Point`.
- Attributes `x` and `y` declared according to the *Cartesian system*
- All method from the interface `Point` are implemented in the sub-class `CartesianPoint`.
- ∴ `CartesianPoint` can be used as a **dynamic type**
- `Point p = new CartesianPoint(3, 4)` allowed!

14 of 20

## Interface (4)



```
public class PolarPoint implements Point {  
    double phi;  
    double r;  
    public PolarPoint(double r, double phi) {  
        this.r = r;  
        this.phi = phi;  
    }  
    public double getX() { return Math.cos(phi) * r; }  
    public double getY() { return Math.sin(phi) * r; }  
}
```

- `PolarPoint` is a possible implementation of `Point`.
- Attributes `phi` and `r` declared according to the *Polar system*
- All method from the interface `Point` are implemented in the sub-class `PolarPoint`.
- ∴ `PolarPoint` can be used as a **dynamic type**
- `Point p = new PolarPoint(3, π/6)` allowed! [ $360^\circ = 2\pi$ ]

15 of 20

## Interface (5)



```
1 public class PointTester {  
2     public static void main(String[] args) {  
3         double A = 5;  
4         double X = A * Math.sqrt(3);  
5         double Y = A;  
6         Point p;  
7         p = new CartesianPoint(X, Y); /* polymorphism */  
8         print("(" + p.getX() + ", " + p.getY() + ")"); /* dyn. bin. */  
9         p = new PolarPoint(2 * A, Math.toRadians(30)); /* polymorphism */  
10        print("(" + p.getX() + ", " + p.getY() + ")"); /* dyn. bin. */  
11    }  
12 }
```

- Lines 7 and 9 illustrate *polymorphism*, how?
- Lines 8 and 10 illustrate *dynamic binding*, how?

16 of 20

## Interface (6)



- An **interface**:
  - Has **all** its methods with no implementation bodies.
  - Leaves complete freedom to its **implementors**.
- Recommended to use an **interface** as the **static type** of:
  - A **variable**  
e.g., Point p
  - A **method parameter**  
e.g., void moveUp(Point p)
  - A **method return value**  
e.g., Point getPoint(double v1, double v2, boolean isCartesian)
- It is forbidden to use an **interface** as a **dynamic type**  
e.g., Point p = new Point(...) is not allowed!
- Instead, create objects whose **dynamic types** are descendant classes of the **interface** ⇒ Exploit **dynamic binding** !

17 of 20

## Abstract Classes vs. Interfaces: When to Use Which?



- Use **interfaces** when:
  - There is a **common set of functionalities** that can be implemented via **a variety of strategies**.  
e.g., Interface Point declares signatures of getX() and getY().
  - Each descendant class represents a different implementation strategy for the same set of functionalities.
  - CartesianPoint and PolarPoint represent different strategies for supporting getX() and getY().
- Use **abstract classes** when:
  - **Some (not all) implementations can be shared** by descendants, and **some (not all) implementations cannot be shared**.  
e.g., Abstract class Polygon:
    - Defines implementation of getPerimeter, to be shared by Rectangle and Triangle.
    - Declares signature of getArea, to be implemented by Rectangle and Triangle.

18 of 20

## Index (1)

- Abstract Class (1)**
- Abstract Class (2)**
- Abstract Class (3)**
- Abstract Class (4)**
- Abstract Class (5)**
- Abstract Class (6)**
- Abstract Class (7.1)**
- Abstract Class (7.2)**
- Abstract Class (8)**
- Interface (1.1)**
- Interface (1.2)**
- Interface (2)**
- Interface (3)**
- Interface (4)**

19 of 20

## Index (2)

- Interface (5)**

- Interface (6)**

**Abstract Classes vs. Interfaces:**  
**When to Use Which?**

20 of 20