

Generics



EECS3311 M: Software Design
Winter 2019

CHEN-WEI WANG

Motivating Example: Observations (1)



- In the `BOOK` class:
 - In the attribute declaration

```
records: ARRAY [ANY]
```

 - ANY** is the most general type of records.
 - Each book instance may store any object whose *static type* is a **descendant class** of **ANY**.
 - Accordingly, from the return type of the `get` feature, we only know that the returned record has the static type **ANY**, but not certain about its *dynamic type* (e.g., `DATE`, `STRING`, etc.).
 - \therefore a record retrieved from the book, e.g., `b.get("Yuna")`, may only be called upon features defined in its *static type* (i.e., **ANY**).
- In the tester code of the `BOOK` class:
 - In **Line 1**, the *static types* of variables `birthday` (i.e., `DATE`) and `phone_number` (i.e., `STRING`) are **descendant classes** of **ANY**.
 - \therefore **Line 5** and **Line 7** compile.

3 of 16

Motivating Example: A Book of Any Objects



```
class BOOK
  names: ARRAY [STRING]
  records: ARRAY [ANY]
  -- Create an empty book
  make do ... end
  -- Add a name-record pair to the book
  add (name: STRING; record: ANY) do ... end
  -- Return the record associated with a given name
  get (name: STRING): ANY do ... end
end
```

Question: Which line has a type error?

```
1 birthday: DATE; phone_number: STRING
2 b: BOOK; is_wednesday: BOOLEAN
3 create {BOOK} b.make
4 phone_number := "416-677-1010"
5 b.add ("SuYeon", phone_number)
6 create {DATE} birthday.make(1975, 4, 10)
7 b.add ("Yuna", birthday)
8 is_wednesday := b.get("Yuna").get_day_of_week = 4
```

2 of 16

Motivating Example: Observations (2)



Due to **polymorphism**, in a collection, the *dynamic types* of stored objects (e.g., `phone_number` and `birthday`) need not be the same.

- Features specific to the *dynamic types* (e.g., `get_day_of_week` of class `Date`) may be new features that are not inherited from **ANY**.
- This is why **Line 8** would fail to compile, and may be fixed using an explicit **cast**:

```
check attached {DATE} b.get("Yuna") as yuna_bday then
  is_wednesday := yuna_bday.get_day_of_week = 4
end
```

- But what if the *dynamic type* of the returned object is not a `DATE`?

```
check attached {DATE} b.get("SuYeon") as suyeon_bday then
  is_wednesday := suyeon_bday.get_day_of_week = 4
end
```

\Rightarrow An **assertion violation** at *runtime*!

4 of 16

Motivating Example: Observations (2.1)



- It seems that a combination of `attached` check (similar to an `instanceof` check in Java) and type cast can work.
- Can you see any potential problem(s)?
- **Hints:**
 - Extensibility and Maintainability
 - What happens when you have a large number of records of distinct *dynamic types* stored in the book (e.g., DATE, STRING, PERSON, ACCOUNT, ARRAY_CONTAINER, DICTIONARY, etc.)? [all classes are descendants of **ANY**]

5 of 16

Motivating Example: Observations (2.2)



Imagine that the tester code (or an application) stores 100 different record objects into the book.

```
rec1: C1
... -- declarations of rec2 to rec99
rec100: C100
create {C1} rec1.make(...) ; b.add(..., rec1)
... -- additions of rec2 to rec99
create {C100} rec100.make(...) ; b.add(..., rec100)
```

where *static types* C1 to C100 are *descendant classes* of ANY.

- *Every time* you retrieve a record from the book, you need to check “exhaustively” on its *dynamic type* before calling some feature(s).

```
-- assumption: 'f1' specific to C1, 'f2' specific to C2, etc.
check attached {C1} b.get("Jim") as c1 then c1.f1 end
... -- casts for C2 to C99
check attached {C100} b.get("Jim") as c100 then c100.f100 end
```

- Writing out this list multiple times is tedious and error-prone!

6 of 16

Motivating Example: Observations (3)



We need a solution that:

- Eliminates runtime assertion violations due to wrong casts
- Saves us from explicit `attached` checks and type casts

As a sketch, this is how the solution looks like:

- When the user declares a BOOK object `b`, they must commit to the kind of record that `b` stores at runtime. e.g., `b` stores *either* DATE objects (and its *descendants*) only *or* String objects (and its *descendants*) only, but *not a mix*.
- When attempting to store a new record object `rec` into `b`, if `rec`'s *static type* is not a *descendant class* of the type of book that the user previously commits to, then:
 - It is considered as a *compilation error*
 - Rather than triggering a *runtime assertion violation*
- When attempting to retrieve a record object from `b`, there is *no longer a need* to check and cast.
 - *Static types* of all records in `b` are guaranteed to be the same.

7 of 16

Parameters



- In mathematics:
 - The same *function* is applied with different *argument values*. e.g., $2 + 3$, $1 + 1$, $10 + 101$, etc.
 - We *generalize* these instance applications into a definition. e.g., $+: (\mathbb{Z} \times \mathbb{Z}) \rightarrow \mathbb{Z}$ is a function that takes two integer *parameters* and returns an integer.
- In object-oriented programming:
 - We want to call a *feature*, with different *argument values*, to achieve a similar goal. e.g., `acc.deposit(100)`, `acc.deposit(23)`, etc.
 - We *generalize* these possible feature calls into a definition. e.g., In class ACCOUNT, a feature `deposit(amount: REAL)` takes a real-valued *parameter*.
- When you design a mathematical function or a class feature, always consider the list of *parameters*, each of which representing a set of possible *argument values*.

8 of 16

Generics: Design of a Generic Book



```
class BOOK[G]
  names: ARRAY[STRING]
  records: ARRAY[G]
  -- Create an empty book
  make do ... end
  /* Add a name-record pair to the book */
  add (name: STRING; record: G) do ... end
  /* Return the record associated with a given name */
  get (name: STRING): G do ... end
end
```

Question: Which line has a type error?

```
1 birthday: DATE; phone_number: STRING
2 b: BOOK[DATE]; is_wednesday: BOOLEAN
3 create BOOK[DATE] b.make
4 phone_number = "416-67-1010"
5 b.add ("SuYeon", phone_number)
6 create {DATE} birthday.make (1975, 4, 10)
7 b.add ("Yuna", birthday)
8 is_wednesday := b.get("Yuna").get_day_of_week == 4
```

9 of 16

Generics: Observations



- In class BOOK:
 - At the class level, we **parameterize the type of records**:

```
class BOOK[G]
```
 - Every occurrence of ANY is replaced by E.
- As far as a client of BOOK is concerned, they must **instantiate** G.
⇒ This particular instance of book must consistently store items of that instantiating type.
- As soon as E instantiated to some known type (e.g., DATE, STRING), every occurrence of E will be replaced by that type.
- For example, in the tester code of BOOK:
 - In **Line 2**, we commit that the book b will store DATE objects only.
 - Line 5** fails to compile. [∵ STRING not **descendant** of DATE]
 - Line 7** still compiles. [∵ DATE is **descendant** of itself]
 - Line 8** does **not need** any attached check and type cast, and does **not cause** any runtime assertion violation.
∵ All attempts to store non-DATE objects are caught at **compile time**.

10 of 16

Bad Example of using Generics



Has the following client made an appropriate choice?

```
book: BOOK[ANY]
```

NO!!!!!!!!!!!!!!!!!!!!!!

- It allows **all** kinds of objects to be stored.
∵ All classes are descendants of **ANY**.
- We can expect **very little** from an object retrieved from this book.
∵ The **static type** of book's items are **ANY**, root of the class hierarchy, has the **minimum** amount of features available for use.
∵ Exhaustive list of casts are unavoidable.
[**bad** for extensibility and maintainability]

11 of 16

Instantiating Generic Parameters



- Say the **supplier** provides a generic DICTIONARY class:

```
class DICTIONARY[V, K] -- V type of values; K type of keys
  add_entry (v: V; k: K) do ... end
  remove_entry (k: K) do ... end
end
```

- Clients** use DICTIONARY with different degrees of instantiations:

```
class DATABASE_TABLE[K, V]
  imp: DICTIONARY[V, K]
end
```


e.g., Declaring `DATABASE_TABLE[INTEGER, STRING]` instantiates
`DICTIONARY[STRING, INTEGER]`.

```
class STUDENT_BOOK[V]
  imp: DICTIONARY[V, STRING]
end
```

e.g., Declaring `STUDENT_BOOK[ARRAY[COURSE]]` instantiates
`DICTIONARY[ARRAY[COURSE], STRING]`.

12 of 16

Generics vs. Inheritance (1)




13 of 16

Beyond this lecture ...

- Study the “Generic Parameters and the Iterator Pattern” Tutorial Videos.

15 of 16

Generics vs. Inheritance (2)



14 of 16

Index (1)

- Motivating Example: A Book of Any Objects
- Motivating Example: Observations (1)
- Motivating Example: Observations (2)
- Motivating Example: Observations (2.1)
- Motivating Example: Observations (2.2)
- Motivating Example: Observations (3) Parameters
- Generics: Design of a Generic Book
- Generics: Observations
- Bad Example of using Generics
- Instantiating Generic Parameters
- Generics vs. Inheritance (1)
- Generics vs. Inheritance (2)
- Beyond this lecture ...

16 of 16