

EECS2030 (Sec. G) Fall 2025

Advanced Object-Oriented Programming

Lecture Notes

Instructor: Jackie Wang

Lecture 1 - Sep 4

Syllabus & Introduction

Professional Engineers: Code of Ethics
Software Development Process

Course Learning Outcomes (CLOs)

CLO1

Implement an Application Programming Interface (API)

headers

CLO2

Test the implementation.

JUnit
(Eclipse)

refactoring

CLO3

Document the implementation.

CLO4

Implement aggregations and compositions.

1. programming.
2. polymorphism
3. dynamic binding

CLO5

Implement inheritance.

CLO6

Use recursion.

- primitive arrays
2101 - TOH.

CLO7

Implement linked lists.

2101


CLO8

(Informally) prove that recursive algorithms are correct and terminate.

CLO9

(Informally) analyse the running time of (recursive) algorithms.

Software Development: **Compile Time** vs. **Run Time**



editing Java code
↳ save
↳ syntax error (missing ";", "class")
type errors
↳ manipulating values
inconsistently
p.g. ① int i = "2020";
② int i = 23;
int j = 23;
unchecked!

Lecture 2 - Sep 8

OOP Review

Separation of Concerns: Model vs. Tests
OO: Observe-Model-Execute Process
Java Data Types: Primitive

Announcements/Reminders


- First Class (Syllabus) recording & notes posted
- Today's class: [notes template](#) posted
- Priorities:
 - + **LabOP1** (tutorial videos + PDFs)
 - + Due: This Tuesday (Sep 8)
- **LabOP2** to be released this Tuesday (Sep 8)
- Lab this Wednesday (Sep 10): Demo on [helper methods?](#)
- Lab next Wednesday (Sep 17):
 - + [≈ 40 min] Mock-up **Programming Test 0**
 - + [≈ 40 min] Q&As (TAs, Jackie)

Separation of Concerns

Slide 6

logic of implementations.

model




- Classes & Methods
- Methods
 - * constructors
 - * accessors: **return** statements
 - * mutators: **no return** statements
 - * containing **no** print statements

use

*model $\approx$ supplier
junit $\approx$ client*

use


junit_tests



specification (what)

- Expected vs. Actual Values
- Methods
 - * calling methods from model
 - * assertions
 - * containing **no** print statements

console_apps





- main method (entry point of execution)
 - * reading inputs from keyboard
 - * calling methods from model
 - * producing outputs to console (print)
 - * containing **no** return statements

discouraged.

Observe-Model-Execute Process

Slide 7




Entities: Jim, Jonathan.

Attributes: weight, height.

Changes: grow taller

Inquiries: getW, getH, getBUI

Template: Person



Entities:

Attributes:

Changes:

Inquiries:

Template:

1. Assume: Everything compiles
2. Instantiate template;
3. create objects on obj.
4. test & debug.

OO

templates

instances

changes

inquiries

(Java, C#)
OOP

classes

objects

mutators/setters

accessors/getters not void.

String getN()
double getW()

void set(...)

- Entities of the same kind share the same set of attributes.

Jonathan, Jim → Person

↳ weight, height

- Values of attributes among entities (of the same kind) may be different.

Jim. weight
vs.
Jonathan. weight


```
class Person {
```

```
    double weight;
```

```
    double height;
```

```
    Person (double w) { ... }
```

```
    Person (double h) { ... }
```

```
}
```

↓
Compilation Error !! the list of parameter types is not distinct

```
Person jim = new Person  
    (72.6);
```

↓
ambiguous:
which version
to call?

```
class Person {
```

```
    double weight;
```

```
    double height;
```

```
    Person (double w) { ... }
```

```
    Person (double h) { ... }
```

```
}
```

double,
double

double

Jim

Person	
w.	0
h.	173.2

✓

① Person Jim = new Person (173²);

②

Person Jonathan = new Person (84.5, 185.7);

Jonathan

Person	
w	84.5
h.	185.7

Object Oriented Programming (OOP)

Slide 8

- Templates (compile-time Java classes)
 - + attributes (common around instances)
 - + methods
 - * constructors
 - * accessors/getters
 - * mutators/setters
- + Eclipse: **Refactoring**
- Instances/Entities (runtime objects)
 - + instance-specific attribute values
 - + calling constructor to create objects
 - + using the "dot notation", with the right contexts, to:
 - * get attribute values
 - * call accessors or mutators

private attr methods
internal workings
modify the code without any public/external users realizing it.
(e.g. helper methods)
obj.m1().m2().m3()
chain of method calls.

Slides 9 ~ 47

assigned readings!

Person jim = ... ; * ref. aliasing

Person jon = ... ;
↑ different objects

① jim.getWeight() → 72

② jon.getWeight() → 85

✓ ③ jim.gainWeight(2) → +2 to jim's weight

* may ref. the same object
④ jon.gainWeight(2) → +2 to jon's weight

⑤ jim.getWeight() → 74

⑥ jon.getWeight()

① vs. ②

③ vs. ④

① vs. ⑤. (not same
" ③)

② vs ⑥
(not same
" ④)

- In Java, each variable must be declared with a type.

compile time ← static typed

PL
dynamic typed python.
PL e.g. 1, 0, 3
{... 7, 2, 3...}

e.g. int i =

↓
declared type
for i
(p.t.)

↓
at

v.t. → store any value
i can store a member of

int.

Lecture 3 - Sep 11

OOP Review

***Java Data Types: Reference
Parameters vs. Arguments
Variable Scopes, Tracing Object Creations***

Announcements/Reminders

- First Class (Syllabus) recording & notes posted
- Today's class: [notes template](#) posted
- Priorities:
 - + **LabOP2** (tutorial videos + PDFs)
 - + Due: Next Tuesday (Sep 16)
- **Lab1** to be released next Tuesday (Sep 16)
- Lab yesterday (Sep 10): Demo on [helper methods](#)
- Lab next Wednesday (Sep 17):
 - + [≈ 40 min] Mock-up **Programming Test 0**
 - + [≈ 40 min] Q&As (TAs, Jackie)

In Java, each variable must be declared with a type.

compile time. ← static-typed

PL
dynamic-typed python.
e.g. 1, 0, 3
{... 7, -1, 0, 3}
1, 2, 3, ...

e.g. `int i`

declared type for `i` (P.t.)

at v.t. `i` can store any value that's a member of `int`.

1. a class declared within your proj. (P.t.)
2. external lib. class imported (e.g. ArrayList)

e.g. `Person`

at v.t. `P` can store of some

address
Person object
memory block reserved for storing specific info. Person address

∴ cannot store string address to a new string

Person p1 = ...;

String s = "2030";


p1 = s;

NullPointerException

runtime error



obj



when context object of some method call is null.

undefined address

method call

obj

context object (C.O.)

m(...)

apply the def. of method to the targetted


look up the address that's stored in the C.O. and go there.

mem. block

if the mem. block does not exist (i.e. address of C.O. is null)
 → NPE

Execution:
 $L \rightarrow R$

break
point &
debugger



(3) $CO.m1().m2()$
may be null

→ Compiles
→ at r.f.
NPE.

Q. How many possible causes for NPE? 3

memory lookups
using

Expression

Q. What are the exact causes?

- (1)
- (2)
- (3)

A declared type of some variable x

denotes the set of values that

is allowed to be stored in x .

Arithmetic
allowed

numbers

1, 2, -1, -2, 0, 23.6, ...

address.

Person@

0x123
base-8
base-16
number

means
to uniquely
identify a
memory location
(no address
authentication)

Parameters

vs.

Arguments

```
class Point {  
    Point(double x, double y) {...}  
  
    double getDistanceFrom(Point other) {...}  
  
    void move(char direction, double units) {...}  
}
```

Template Definition

Method Usages

```
class PointTester {  
    static void main(String[] args) {  
        Point p1 = new Point(2.5, -3.6);  
        Point p2 = new Point(-4.8, 5.9);  
        double dist1 = p1.getDistanceFrom(p2);  
        double dist2 = p2.getDistanceFrom(p1);  
        p1.move('R', 7.6);  
    }  
}
```

Arguments

Scope of Variables in a Class

- Class-level variables may be accessed/modified between methods.
[Assume for now: non-**static**]
- Method-level parameters may be accessed within the declared method only.
- Method-level (local) variables may be accessed/modified within the declared method.

```
class MyClass {  
    int i;  
    int j;  
    void m1(int p1) {  
        int m;  
    }  
    void m2(int p2) {  
        int n;  
    }  
}
```

attributes (class-level variables)
fields


parameters,
local variables
(method-level)

```

class MyClass {
    int i = j; ✓
    int j = p1; X
    void m1 (int p1) {
        int m = p1; ✓
    }
    void m2 (int p2) {
        int n;
    }
}

```

$p2 = n$ ✓
 ↓ call by value.



Constructors not using this Keyword

```
public class Person {  
    /*  
    * Attributes.  
    * Person instances have the same attribute names.  
    * Person instances have specific attribute values.  
    */
```

model

```
double weight;  
double height;
```

```
/*  
* Constructors  
*/  
public Person() {  
}
```

```
public Person(double newWeight, double newHeight) {  
    weight = newWeight;  
    height = newHeight;  
}
```

@Test

```
public void test_1() {  
    Person jim = new Person(72, 1.81);  
    Person jonathan = new Person(65, 1.67);  
    assertTrue(jim != jonathan);  
    assertFalse(jim == jonathan);  
    assertNotSame(jim, jonathan);  
    assertNotEquals(jim, jonathan);  
}
```


JUnit

```
public static void main(String[] args) {  
    Person jim = new Person(72, 1.81);  
    Person jonathan = new Person(65, 1.67);  
    System.out.println(jim);  
    System.out.println(jonathan);  
}
```

console

- Default Constructor?
- Parameters vs. Arguments
- Reference Variables

memory
(sequence of bytes)



0x123
jim

0x123

0x789

jonathan
0x789

(e.g. `assertTrue` vs `assertFalse`)

JUnit assertions : pass vs fail

(e.g. `j1 == j2` vs `j1 != j2`)

boolean expressions : True vs. false

`assertTrue` (boolean exp)
↓

- true → pass
- false → fail

`assertFalse` ()
↓

- true → fail
- false → pass

Use of ^{non-word} Accessors vs. ^{word} Mutators

Slide 48

```
class Person {  
    void setWeight(double weight) { ... }  
    double getBMI() { ... }  
}
```

- Calls to **mutator methods** *cannot* be used as values.

- e.g., `System.out.println(jim.setWeight(78.5));` ✗
- e.g., `double w = jim.setWeight(78.5);` ✗
- e.g., `jim.setWeight(78.5);` ✓

- Calls to **accessor methods** *should* be used as values.

- e.g., `jim.getBMI();`
- e.g., `System.out.println(jim.getBMI());` ✓
- e.g., `double w = jim.getBMI();` ✓

✗ *compiles but useless*

Lecture 4 - Sep 16

OOP Review

***Tracing OOP: New Obj. & Method Calls
Variable Shadowing, Use of this
Reference Aliasing***

Announcements/Reminders

- Today's class: [notes template](#) posted
- Priorities:
 - + **LabOP2** (tutorial videos + PDFs)
 - + Due: This Tuesday (Sep 16)
- **Lab1** released today (Sep 16)
- Lab last Wednesday (Sep 10): Demo on [helper methods](#)
- **ProgTest0** (next Wednesday, Sep 24), **Guide** released
- Lab this Wednesday (Sep 17):
 - + Please go to your enrolled session.
 - + [≈ 40 min] Mock-up **Programming Test 0**
 - + [≈ 40 min] Q&As (TAs, Jackie)

Constructors not using this Keyword

Use "this" keyword
to denote the Context obj

Question

- What if names of parameter & attribute are the same?
- implicit "this"

```
public class Person {  
    /*  
     * Attributes.  
     * Person instances have the same attribute names.  
     * Person instances have specific attribute values.  
     */  
    double weight;  
    double height;  
  
    /*  
     * Constructors  
     */  
    public Person() {  
           
    }  
  
    public Person(double newWeight, double newHeight) {  
        this.weight = newWeight; weight  
        this.height = newHeight; height  
    }  
}
```

leave attr's
default values

weight

height

ref. to
the parameter
"weight"

variable
shadowing

Tracing OO Code: Visualizing Objects

To visualize an object:

- Draw a rectangle box to represent **contents** of that object:
 - **Title** indicates the *name of class* from which the object is instantiated.
 - **Left column** enumerates *names of attributes* of the instantiated class.
 - **Right column** fills in *values* of the corresponding attributes.
- Draw **arrow(s)** for *variable(s)* that store the object's **address**.

(selected)
list of attributes

stores the add. of
jim
reference variable
(storing Person add. only)

Person	
age	50
nationality	"British"
weight	80
height	1.8

object in memory.

instance-specific
att. values

type of object

Effects of Creating New Objects

```
public class Person {  
    /*  
    * Attributes.  
    * Person instances have the same attribute names.  
    * Person instances have specific attribute values.  
    */  
    double weight;  
    double height;  
  
    /*  
    * Constructors  
    */  
    public Person() {  
  
    }  
  
    public Person(double weight, double height) {  
        this.weight = weight;  
        this.height = height;  
    }  
}
```

model

- Variable Shadowing
- Visualizing Objects
- Context Object
- this
- dot notation

overloading

72 65 1.81 1.67
X X X X
72 65 1.67
X X X X
1.81
Jonathan
this

Person	
w	65
h	1.67

@Test

```
public void test_1() {  
    * Person jim = new Person(72, 1.81);  
    Person jonathan = new Person(65, 1.67);  
    assertTrue(jim != jonathan);  
    assertFalse(jim == jonathan);  
    assertNotSame(jim, jonathan);  
    assertNotEquals(jim, jonathan);  
}
```

JUnit

* Person jim = new Person(72, 1.81);
① ③ ②

① declares a ref. var. "jim" that stores add./ref of some Person obj.

Jim

this

Person	
w.	72
h.	1.81

② starts add. of new obj. to the ref. var.

Accessors/Getters vs. Mutators/Setters

```
public class Person {
    /*
     * Attributes.
     * Person instances have the same attribute names.
     * Person instances have specific attribute values.
     */
    double weight;
    double height;

    /* Accessors/Getters */
    public double getBMI() {
        double bmi = this.weight / (this.height * this.height);
        return bmi;
    }

    /* Mutators/Setters */
    public void gainWeightBy(double amount) {
        this.weight = this.weight + amount;
    }
}
```

Handwritten notes: Blue arrows point to `getBMI()` and `gainWeightBy()`. Orange and blue scribbles are next to `this.weight` and `this.height` in the `BMI` calculation. Purple and blue scribbles are next to `amount` and `this.weight` in the `gainWeightBy` method.

Jim

Person	
w.	72
h.	1.81

72

Jonathan

Person	
w.	65
h.	1.67

65

```
@Test
public void test_3() {
    Person jim = new Person(72, 1.81);
    Person jonathan = new Person(65, 1.67);

    assertEquals(21.977, jim.getBMI(), 0.01);
    assertEquals(23.307, jonathan.getBMI(), 0.01);

    jim.gainWeightBy(3);
    jonathan.gainWeightBy(3);

    assertEquals(22.893, jim.getBMI(), 0.01);
    assertEquals(24.382, jonathan.getBMI(), 0.01);
}
```

Handwritten notes: Blue circles around `72`, `1.81`, `65`, `1.67`, `21.977`, `23.307`, `22.893`, and `24.382`. Orange circles around `Person` and `Person` in the constructor calls. Purple circles around `3` in the `gainWeightBy` calls. A red box highlights the final two `assertEquals` calls. A red 'X' is next to the second `assertEquals` call.


Handwritten notes: `assertEquals(x, y, 0.01)` with `double` above `x` and `y`. Below it, `assertEquals(|x - y| ≤ 0.01)` with `ε (tolerance)` next to `0.01`.

Slide 50

```
int i = 3;  
int j = i;  
int k = 3;
```


→ copy what's stored in τ , and store that value in τ_j .

```
System.out.println(i == Tj);  
System.out.println(k == i && k == j);
```



①

```
Point p1 = new Point(2, 3);  
Point p2 = p1; System.out.println(p1 == p2);  
Point p3 = new Point(2, 3);  
System.out.println(p3 == p1 || p3 == p2);  
System.out.println(p3.x == p1.x && p3.y == p1.y);  
System.out.println(p3.x == p2.x && p3.y == p2.y);
```



**** After exec. this
var. assignment, p1 and
p2 point to same
obj.**

Copying Primitive Values


Slide 51

```
int i1 = 1;
int i2 = 2;
int i3 = 3;
```


```
int[] numbers1 = {i1, i2, i3};
int[] numbers2 = new int[numbers1.length];
for (int i = 0; i < numbers1.length; i++) {
    numbers2[i] = numbers1[i];
}
```

```
numbers1[0] = 4;
System.out.println(numbers1[0]);
System.out.println(numbers2[0]);
```

ref. var. stops the starting point of an array where each element is an int.



$ns2[0] = ns1[0]$
 $ns2[1] = ns1[1]$
 $ns2[2] = ns1[2]$



3 < 3
False exit

Lecture 5 - Sep 18

OOP Review

Exercise: Reference Aliasing & Arrays
Manual Management of Account IDs
Use of Static vs. Non-Static Variables

Announcements/Reminders

- Today's class: notes template posted
- Priorities:
 - + Review Lab0
 - + Complete Lab1
 - + Due: Next Tuesday (Sep 30)
- ProgTest0 (next Wednesday, Sep 24), Guide released
- Mock-up Programming Test 0 to be released


Copying Reference Values: Aliasing

Slide 52

```


Person alan = new Person("Alan");
Person mark = new Person("Mark");
Person tom = new Person("Tom");
Person jim = new Person("Jim");
Person[] persons1 = {alan, mark, tom};
Person[] persons2 = new Person[persons1.length];
for(int i = 0; i < persons1.length; i++) {
    persons2[i] = persons1[i];
}
persons1[0].setAge(70);
System.out.println(jim.getAge());
System.out.println(alan.getAge());
System.out.println(persons2[0].getAge());
persons1[0] = jim;
persons1[0].setAge(75);
System.out.println(jim.getAge());
System.out.println(alan.getAge());
System.out.println(persons2[0].getAge());
    
```

** copy the add. stored in alan into index 0 of array ps1.
 * Person[] ps1 = new Person[3];
 ps1[0] = alan;
 ps1[1] = mark; ps1[2] = tom;



 0 ps2[0] = ps1[0];
 1 ps2[1] = ps1[1];
 2 ps2[2] = ps1[2];

$a[\bar{t}]$



① $a \neq \text{null}$

$a.\text{length} == 10$

② $0 \leq \bar{t} \leq a.\text{length} - 1$

Copying Arrays

Person[] ps1;

Person[] ps2;

ps1 = new ...


ps2 = new ...

ps2 = ps1;

ps1 = null;


	①	②	③	④
ps1 == null	T	F	F	T
ps2 == null	T	F	F	F
ps1 == ps2	T	F	T	F

②
Creating alias for the array ref.



Arrays and Aliasing

All alias paths to "Alan"?



Q. All alias paths to "Alan"?

alan

persons1[0]

persons2[0]

Managing Account IDs: Manual

Slide 75

```
public class Account {  
    private int id;  
    private String owner;  
    public int getID() { return this.id; }  
    public Account(int id, String owner) {  
        this.id = id;  
        this.owner = owner;  
    }  
}
```

explicit parameter, presumably should not clash with existing IDs.

Goal:

auto.

generate & manage IDs

```
class AccountTester {  
    Account acc1 = new Account(1, "Jim");  
    Account acc2 = new Account(2, "Jeremy");  
    System.out.println(acc1.getID() != acc2.getID());  
}
```

2. when IDs are duplicated, not a compilation error (logical error)

1. burden on the user to specify unique IDs.

Declaring Global Variables among Objects


- * Each Counter object has its own copy (instance-specific value)
- ** All Counter objects share a single/unique copy (global var.)

```
public class Counter {  
    private int l;  
    static int g = 0;  
    public Counter() {  
        this.l = 0;  
    }  
    public int getLocal() {  
        return this.l;  
    }  
    public void incrementLocal() {  
        this.l++;  
    }  
    public void incrementGlobal() {  
        g++;  
    }  
}
```

Handwritten notes:
- `static int g = 0;`: static variable (attribute)
- `this.l = 0;`: non-static var. int. as soon as it's decl. in constructor.
- `g++`: this.g ++ (compiles with a warning)

```
public class CounterTester {  
    public static void main(String[] args) {  
        Counter c1 = new Counter();  
        Counter c2 = new Counter();  
  
        System.out.println("c1's local: " + c1.getLocal());  
        System.out.println("c2's local: " + c2.getLocal());  
        System.out.println("Global accessed via c1: " + c1.g);  
        System.out.println("Global accessed via c2: " + c2.g);  
        System.out.println("Global accessed via Counter: " + Counter.g);  
    }  
}
```

- ① `c1.incrementLocal();`
- ② `c2.incrementLocal();`
- ③ `c1.incrementGlobal();`
- ④ `c2.incrementGlobal();`
- ⑤ `Counter.g = Counter.g + 1; // Counter.global ++;`



Accessing static variables: ClassName.nameOfStaticVar.

Lecture 6 - Sep 23

OOP Review

Use and Misuse of Static Variables

Use of this: Marriage Example

Reference-Typed Return Values

Anonymous Objects

Announcements/Reminders

- Today's class: [notes template](#) posted
- Priorities:
 - + Review **Lab0**
 - + Complete **Lab1**
 - + Due: Next Tuesday (Sep 30)
- **ProgTest0** (this Wednesday, Sep 24):
 - + **Guide** & **Mockup Test** released
 - + **Required**: Go to your enrolled session.
 - + A physical photo ID is required.

Alt String id_str = "Id" + id;

Managing Account IDs: Automatic

Slides 76 - 77

id_str
"Id1"
"Id2"
?

```
class Account {  
    private static int globalCounter = 1;  
    private int id; String owner;  
    public Account(String owner) {  
        this.id = globalCounter;  
        globalCounter ++;  
        this.owner = owner; } }
```

list of parameters
not including id
anymore (not burden
of user)

```
class AccountTester {  
    Account acc1 = new Account("Jim");  
    Account acc2 = new Account("Jeremy");  
    System.out.println(acc1.getID() != acc2.getID()); }
```

Account	
gc*	1

acc1
c.o.

Account	
id	1
owner	"Jim"





acc2
c.o.

Account	
id	2
owner	"Jeremy"

~~1~~
2

Misuse of Static Variables

⑥



```
public class Client {  
    private Account[] accounts;  
    private static int numberOfAccounts = 0;  
    public void addAccount(Account acc) {  
        accounts[this.numberOfAccounts] = acc;  
        this.numberOfAccounts++;  
    }  
}
```

```
public class ClientTester {  
    Client bill = new Client("Bill");  
    Client steve = new Client("Steve");  
    Account acc1 = new Account();  
    Account acc2 = new Account();  
    bill.addAccount(acc1);  
    /* ... */  
    steve.addAccount(acc2);  
    /* ... */  
}
```

tan.addAccount(acc3); ~> [0] [1] [2] [3] [4] ...

skipped & wasted.

Use of Static Variables: Common Error

Slides 80 - 82

```
1 public class Bank {  
2     private string branchName;  
3     public String getBrachName() { return this.branchName; }  
4     private static int nextAccountNumber = 0;  
5     public static String getInfo() {  
6         nextAccountNumber++;  
7         return this.branchName + nextAccountNumber;  
8     }  
9 }
```

Compilation Error: branchName non-static var used in getInfo static context

Expected Usage: Bank.getInfo not an object!
not a context object → Bank.branchName non-static

Fix 1

```
1 public class Bank {  
2     private String branchName;  
3     public String getBrachName() { return this.branchName; }  
4     private static int nextAccountNumber = 0;  
5     public static String getInfo() {  
6         nextAccountNumber++;  
7         return this.branchName + nextAccountNumber;  
8     }  
9 }
```

↓ remove the usage of non-static var.

↳ return value of global counter.

Fix 2

```
1 public class Bank {  
2     private static String branchName;  
3     public String getBrachName() { return this.branchName; }  
4     private static int nextAccountNumber = 0;  
5     public static String getInfo() {  
6         nextAccountNumber++;  
7         return this.branchName + nextAccountNumber;  
8     }  
9 }
```

→ not a good design :-

branch name should be instance-specific.

Example: Reference to **this**


Slide 59 - 61

recursive type

```
public class Person {  
    private String name;  
    private Person spouse;  
    public Person(String name) {  
        this.name = name;  
    }  
    public void marry(Person other) {  
        // * marriage is legal *  
        ① this.spouse = other;  
        ② other.spouse = this;  
    }  
}
```

*
this.spouse == null
other.spouse == null

this
① jim.spouse = elsa;
other
② elsa.spouse = jim;
this



```
Person jim = new Person("Jim");  
Person elsa = new Person("Elsa");  
jim.marry(elsa);
```

C.O.

other

Math

(conjunction,
and) $\wedge$

(disjunction,
or) $\vee$

(negation) $\neg$

Programming

$\&\&$
 $\|\|$

short-circuit
evaluation.

!

Exercise

$\neg \text{legal} \equiv \neg (\text{legal})$

De Morgan

$$\neg (P \wedge Q) \equiv \neg P \vee \neg Q$$
$$\neg (P \vee Q) \equiv \neg P \wedge \neg Q$$

this.spouse == null
other.spouse == null

```
public void marry (Person other) {
```

```
    if ( * proposed marriage is illegal ) { /* error */ }
```



```
    else {
```

①

②.

```
    }
```

```
}
```



Jim.marry(elsa):

Jim.marry(mary):

not single;
should be some error.



Reference-Typed Return Values

Slide 53

```
public class Point {  
    /* A mutator modifying the context Point object */  
    public void moveUp(double i) {  
        this.y = this.y + i;  
    }  
  
    /* An accessor returning a new Point object */  
    public Point movedUpBy(double i) {  
        Point np = new Point(this.x, this.y);  
        np.moveUp(i);  
        return np;  
    }  
}
```

```
public class PointTester {  
    public static void main(String[] args) {  
        Point p1 = new Point(2.5, -3.6);  
        p1.moveUp(7.8);  
        Point p2 = p1.movedUpBy(6.4);  
        System.out.println(p1 == p2);  
    }  
}
```



Anonymous Objects

Slide 56 - 58

```
1 double square(double x) {  
2     double sqr = x * x;  
3     return sqr; }
```

```
1 double square(double x) {  
2     return x * x; }
```

```
1 Person getP(String n) {  
2     Person p = new Person(n);  
3     return p; }
```

```
1 Person getP(String n) {  
2     return new Person(n); }
```

```
class Member {  
    private Order[] orders;  
    private int noo;  
    /* constructor omitted */  
    public void addOrder(Order o) {  
        this.orders[this.noo] = o;  
        this.noo++;  
    }
```

```
    public void addOrder(String n, double p, double q) {
```

```
    }  
}
```

Exercise

Lecture 7 - Sep 25

OOP Review

Caller vs. Callee

Tracing Chain of Method Calls via a Stack

Catch-or-Specify Requirement

To Handle or Not to Handle: V1

Announcements/Reminders

- Today's class: notes template posted
- Priorities:
 - + Review Lab0
 - + Complete Lab1; Due: Next Tuesday (Sep 30)

method that calls another method → caller * Each method call defines a caller-callee relation.
Caller vs. **Callee** method that's called by another method → caller.

- **caller** is the **client** using the service provided by another method.
- **callee** is the **supplier** providing the service to another method.

```
class C1 {  
    void m1() {  
        C2 o = new C2();  
        o.m2(); /* static type of o is C2 */  
    }  
}
```

Exercise: Make C2.m2 a caller.
caller: C2.m2
callee: C1.m1

type of C.O. → C2
C.O. → C1.m1
caller-callee relation.

does not mean that m2 is static!

Q: Can a method be a **caller** and a **callee** simultaneously?

(Alt 1) Make C1.m1 a callee.


```
class C3 {  
    void m() { C1 o = new C1(); o.m1(); }  
}
```

caller


caller
class C {
 void m() {
 ...
 this.m();
 }
}

↳
C.m is
also the caller.

Visualizing a Call Chain using a Stack



What to Do When an Exception is Thrown: Call Stack



Example: To Handle or Not To Handle?

```
class A {  
    ma(int i) {  
        if(i < 0) { /* Error */ }  
        else { /* Do something. */ }  
    }  
}
```

```
class B {  
    mb(int i) {  
        A oa = new A();  
        oa.ma(i); /* Error occurs if i < 0 */  
    }  
}
```

```
class Tester {  
    public static void main(String[] args) {  
        Scanner input = new Scanner(System.in);  
        int i = input.nextInt();  
        B ob = new B();  
        ob.mb(i); /* Where can the error be handled? */  
    }  
}
```

```
class NegValException extends Exception {  
    NegValException(String s) { super(s); }  
}
```

context	caller	callee
A	/	/
B	B.mb	A.ma
Tester	Tester. main	B.mb

Version 1:

Handle it in B.mb

Version 2:

Pass it from B.mb and handle it in Tester.main

Version 3:

Pass it from B.mb, then from Tester.main, then throw it to the console.

call
stack

A.ma
B.mb
Tester.main

Lecture 8 - Sep 30

Exceptions

***To Handle or Not to Handle: Versions 2, 3
Generalizing Exception Handling***

Announcements/Reminders

- Today's class: [notes template](#) posted
- Priorities:
 - + Complete **Lab1**; **Due**: This Tuesday (Sep 30)
 - + **Lab2** to be released
- **ProgTest1**
 - + guide released
 - + PracticeTest1 released
 - + In-Person Review Session at 2 PM, Friday, Oct 3 (CLH C)

Version 1: B.mb Catches

```
class A {
    A() {}

    void ma(int i) throws NegValException {
        ⑥ if (i < 0) {
            ⑦ println("abnormal exec of A.ma");
            ⑧ throw new NegValException("Neg Val: " + i);
        }
        ⑦ else {
            println("normal exec of A.ma");
        }
    }
}
```

normal exec of A.ma
B.mb: calling A.ma
did not cause NVE.

Tester.main: after
calling B.mb.

abnormal exec. of A.ma
B.mb: calling A.ma
caused NVE.

Tester.main: After calling B.mb.

```
class B {
    B() {}


    void mb(int i) {
        ④ A oa = new A();
        ⑤ try {
            ⑥ oa.ma(i);
            ⑦ println("From B.mb: Calling A.ma did not cause NVE.");
        }
        catch (NegValException nve) {
            ⑧ println("From B.mb: Calling A.ma caused NVE.");
        }
    }
}
```

```
class Tester {
    main(...) {
        ① int i = 5;
        ② B ob = new B();
        ③ ob.mb(i);
        ④ println("From Tester.main: After calling B.mb.");
    }
}
```

A.ma
B.mb
Tester.main

NVE caught, not
throws an exception
catches an exception

Since B.mb
catches NVE,
subsequent callers
no longer
subject to
try-or-
catch req.



Q1. In B.mb, is calling oa.ma
subject to **catch-or-specify** req?

YES 'i' res caller A.ma
specifies it.

Q2. In Tester.main, is calling B.mb
subject to **catch-or-specify** req?

No 'i' res caller
B.mb catches that.

Version 2: B.mb Specifies,


```
class A {  
    A() {}  
  
    void ma(int i) throws NegValException {  
        if(i < 0) {  
            println("abnormal exec of A.ma");  
            throw new NegValException("Neg Val: " + i);  
        }  
        else {  
            println("normal exec of A.ma");  
        }  
    }  
}
```

```
class B {  
    B() {}  
  
    void mb(int i) throws NegValException {  
        A oa = new A();  
        oa.ma(i);  
        println("From B.mb: Calling A.ma did not cause NVE.");  
    }  
}
```

```
class Tester {  
    main(...) {  
        int i; 4-5  
        B ob = new b();  
        try {  
            ob.mb(i);  
            println("Tester.main: Calling B.mb did not cause NVE.");  
        }  
        catch(NegValException nve) {  
            println("Tester.main: Calling B.mb caused NVE.");  
        }  
    }  
}
```

could be specify option
(version 3)

Tester.main Catches



Q1. In B.mb, is calling oa.ma subject to **catch-or-specify** req?

Yes ∵ A.ma specifies it.

Q2. In Tester.main, is calling B.mb subject to **catch-or-specify** req?

Yes ∵ B.mb specifies it


Version 3: B.mb Specifies,

```
class A {  
    A() {}  
  
    void ma(int i) throws NegValException {  
        if(i < 0) {  
            println("abnormal exec of A.ma");  
            throw new NegValException("Neg Val: " + i);  
        }  
        else {  
            println("normal exec of A.ma");  
        }  
    }  
}
```

Tester.main Specifies

```
class B {  
    B() {}  
  
    void mb(int i) throws NegValException {  
        A oa = new A();  
        oa.ma(i);  
        println("From B.mb: Calling A.ma did not cause NVE.");  
    }  
}
```

```
class Tester {  
    main(...) throws NegValException {  
        int i;  
        B ob = new b();  
        ob.mb(i);  
        println("Tester.main: Calling B.mb did not cause NVE.");  
    }  
}
```



Q1. In B.mb, is calling oa.ma subject to **catch-or-specify** req?

Yes. A.ma specifies it

Q2. In Tester.main, is calling B.mb subject to **catch-or-specify** req?

Yes. B.mb specifies it.

Catch-or-Specify Requirement: Call Stack

Q1. Origin of Exception:

Ci.m1

Q2. Methods subject to CoS Req:

3. Methods free from CoS Req: $\frac{1}{2}$ methods specify 1 method (arch)

Q3. Methods free from CoS Req:


n-l methods

Q4. Extreme Case 1 (exception handled earliest):

`l2.mz` catches the exception.

Q5. Extreme Case 2 (exception never handled):

$C_{1..m} \sim C_{n..m} \underline{\underline{\text{all specify}}}$.



Lecture 9 - Oct 2

Exceptions

Execution Flows: Normal vs. Abnormal
Examples: Circle, Bank, parseInt

Announcements/Reminders

- Today's class: [notes template](#) posted
- Priorities:
 - + **Lab1** solution video released
 - + **Lab2** released
- **ProgTest1**
 - + guide released
 - + PracticeTest1 released
 - + In-Person Review Session at 2 PM, Friday, Oct 3 (CLH C)

Catch-or-Specify Requirement: Execution Flows (1)

Scenario: Current caller chooses to catch/handle the exception.

Normal Flow of Execution

```
①.. /* before, outside try-catch block */  
try {  
  ② o.m(...) /* may throw SomeException */  
  ③ ... /* rest of try-block */  
}  
catch (SomeException se) {  
  ... /* rest of catch-block */  
}  
④.. /* after, outside try-catch block */
```

When the exception does not occur

by passed
∵ no exception occurred

Abnormal Flow of Execution

```
①.. /* before, outside try-catch block */  
try {  
  ② o.m(...) /* may throw SomeException */  
  X ... /* rest of try-block */  
}  
catch (SomeException se) {  
  ③ .. /* rest of catch-block */  
}  
④.. /* after, outside try-catch block */
```

When the exception occurs

rest of try block bypassed
∵ exception occurred.

Catch-or-Specify Requirement: Execution Flows (2)

Scenario: Caller chooses to specify/propagate the exception.

Normal Flow of Execution

```
class C1 {  
    void m1 throws SomeException {  
        ①... /* some code */  
        ②... /* some code */  
        ③ C2 o = new C2();  
        ④ o.m();  
        ⑤ ... /* some code */  
        ⑥ ... /* some code */  
    }  
}
```

exception not occurred

When the exception does not occur

Abnormal Flow of Execution

```
class C1 {  
    void m1 throws SomeException {  
        ①... /* some code */  
        ②... /* some code */  
        ③ C2 o = new C2();  
        ④ o.m();  
        ... /* some code */  
        ... /* some code */  
    }  
}
```

exception thrown

specify → *C2.m*

specify → *C1.m1 calls*

;

When the exception occurs

exception disrupted the flow and thrown to the caller of C1.m1

Error Handling via Exceptions: Circles (Version 2)

```
public class InvalidRadiusException extends Exception {  
    public InvalidRadiusException(String s) {  
        super(s);  
    }  
}
```

Test Case:

User enters **-5**

Then user enters **10**

```
class Circle {  
    double radius;  
    Circle() { /* radius defaults to 0 */ }  
    void setRadius(double r) throws InvalidRadiusException {  
        if (r < 0) {  
            ① throw new InvalidRadiusException("Negative radius.");  
        }  
        ② else { radius = r; }  
        double getArea() { return radius * radius * 3.14; }  
    }  
}
```

Handwritten notes:
- **①** *terminates setR met. abnormally*
- **②** *terminates setR normally*
- **10** *10*
- **10** *10*

Handwritten notes:
- **TRIV**
- **TRIV**
- **TRIV**

Handwritten notes:
- **-5**
- **10**
- **Y**

Handwritten notes:
- **Exercise 1** 23
- **Exercise 2** -4,
- **-3** 10


```
public class CircleCalculator2 {  
    public static void main(String[] args) {  
        ① Scanner input = new Scanner(System.in);  
        ② boolean inputRadiusIsValid = false;  
        ③ while (!inputRadiusIsValid) {  
            ④ System.out.println("Enter a radius:");  
            ⑤ double r = input.nextDouble();  
            ⑥ Circle c = new Circle();  
            ⑦ try { c.setRadius(r); }  
            ⑧ catch (InvalidRadiusException e) {  
                ⑨ print("Try again!");  
            }  
            ⑩ inputRadiusIsValid = true;  
            ⑪ System.out.print("Circle with radius " + r);  
            ⑫ System.out.println(" has area: " + c.getArea());  
        }  
    }  
}
```

Handwritten notes:
- **③** *while (!inputRadiusIsValid)*
- **④** *System.out.println("Enter a radius:");*
- **⑤** *double r = input.nextDouble();*
- **⑥** *Circle c = new Circle();*
- **⑦** *try { c.setRadius(r); }*
- **⑧** *catch (InvalidRadiusException e) {*
- **⑨** *print("Try again!");*
- **⑩** *inputRadiusIsValid = true;*
- **⑪** *System.out.print("Circle with radius " + r);*
- **⑫** *System.out.println(" has area: " + c.getArea());*
- **⑬** *IRE thrown*
- **⑭** *IRE not thrown*

Handwritten notes:
- **Console**
- **Enter a radius:**
- **-5**
- **Try Again**
- **Enter a radius:**
- **10** Area is ...

Handwritten notes:
- **C.setR**
- **CC2.main**

while ($\neg C$) {



}

repeated as long as
B is true.
repeated as long as
C is false.

Error Handling via Exceptions: Circles (Version 1)

```
public class InvalidRadiusException extends Exception {  
    public InvalidRadiusException(String s) {  
        super(s);  
    }  
}
```

Test Case 1:

User enters 10

Test Case 2:

User enters -5

```
class Circle {  
    double radius;  
    Circle() { /* radius defaults to 0 */ }  
    void setRadius(double r) throws InvalidRadiusException {  
        if (r < 0) {  
            throw new InvalidRadiusException("Negative radius.");  
        }  
        else { radius = r; }  
    }  
    double getArea() { return radius * radius * 3.14; }  
}
```

caller

callee

Caller?

Callee?

call stack

```
class CircleCalculator1 {  
    public static void main(String[] args) {  
        Circle c = new Circle();  
        try {  
            c.setRadius(-10);  
            double area = c.getArea();  
            System.out.println("Area: " + area);  
        }  
        catch (InvalidRadiusException e) {  
            System.out.println(e);  
        }  
    }  
}
```



Error Handling via Exceptions: Banks

```
public class InvalidTransactionException extends Exception {  
    public InvalidTransactionException(String s) {  
        super(s);  
    }  
}
```

```
class Account {  
    int id; double balance;  
    Account() { /* balance defaults to 0 */ }  
    void withdraw(double a) throws InvalidTransactionException {  
        if (a < 0 || balance - a < 0) {  
            throw new InvalidTransactionException("Invalid withdraw.");  
        } else { balance -= a; }  
    }  
}
```

```
class Bank {  
    Account[] accounts; int numberOfAccounts;  
    Account(int id) { ... }  
    void withdraw(int id, double a)  
        throws InvalidTransactionException {  
        for(int i = 0; i < numberOfAccounts; i++) {  
            if(accounts[i].id == id) {  
                accounts[i].withdraw(a);  
            }  
        } /* end for */  
    }  
}
```

```
class BankApplication {  
    public static void main(String[] args) {  
        Bank b = new Bank();  
        Account accl = new Account(23);  
        b.addAccount(accl);  
        Scanner input = new Scanner(System.in);  
        double a = input.nextDouble();  
        try {  
            b.withdraw(23, a);  
            System.out.println(accl.balance);  
        } catch (InvalidTransactionException e) {  
            System.out.println(e);  
        }  
    }  
}
```



Account

`accounts[i].withdraw(...)`
Account[i]

Account.withdraw
Bank.withdraw
BA.main

Test Case:

User enters **-5000000**

More Example: Multiple Catch Blocks

Assumption

Customized exceptions are
unrelated to each other

↳ their
catch blocks
can be
arranged in
any order

```
① double r = 1.; -5;  
② double a = 1.; 100;  
try{  
③ Bank b = new Bank();  
④ b.addAccount(new Account(34));  
⑤ b.deposit(34, 100); may throw  
⑥ b.withdraw(34, 100); may throw ITE → not thrown  
⑦ Circle c = new Circle();  
⑧ c.setRadius(r); may throw NRE → thrown  
System.out.println(r.getArea());  
}
```

```
catch (NegativeRadiusException e) {
```

```
① System.out.println(r + " is not a valid radius value.");  
② e.printStackTrace();  
}
```

```
catch (InvalidTransactionException e) {
```

```
System.out.println(r + " is not a valid transaction value.");  
e.printStackTrace();  
}
```

Test Case 1:

a: -5000000

r: 23

Test Case 2:

a: 100

r: -5

More Example: Parsing Strings as Integers

~~False~~ True
~I

```
1 Scanner input = new Scanner(System.in);
2 boolean validInteger = false;
3 while (!validInteger) {
4     System.out.println("Enter an integer:");
5     String userInput = input.nextLine();
6     try {
7         int 23userInteger = Integer.parseInt(userInput);
8         validInteger = true;
9     }
10    catch (NumberFormatException e) {
11        System.out.println(userInput + " is not a valid integer.");
12        /* validInteger remains false */
13    }
14 }
```

Test Case:

User Enters: twenty-three

User Then Enters: 23

✓ → NFE thrown Enter an integer
twenty-three
"twenty-three" Not valid
Enter an integer.
23

Review: Specify-or-Catch Principle

Approach 1 – Specify: Indicate in the method signature that a specific exception might be thrown.

Example 1: Method that throws the exception

```
class C1 {  
    void m1(int x) throws ValueTooSmallException {  
        if(x < 0) {  
            throw new ValueTooSmallException("val " + x);  
        }  
    }  
}
```

Example 2: Method that calls another which throws the exception

```
class C2 {  
    C1 c1;  
    void m2(int x) throws ValueTooSmallException {  
        c1.m1(x);  
    }  
}
```

Review: **Specify**-or-**Catch** Principle

Approach 2 – Catch: Handle the thrown exception(s) in a try-catch block.

```
class C3 {  
    public static void main(String[] args) {  
        Scanner input = new Scanner(System.in);  
        int x = input.nextInt();  
        C2 c2 = new C2();  
        try {  
            c2.m2(x);  
        }  
        catch (ValueTooSmallException e) { ... }  
    }  
}
```


A Class for Bounded Counters

```
public class Counter {  
    public final static int MAX_VALUE = 3;  
    public final static int MIN_VALUE = 0;  
    private int value;  
    public Counter() {  
        this.value = Counter.MIN_VALUE;  
    }  
    public int getValue() {  
        return value;  
    }  
    ... /* more later!
```


mit.
↓
0 1 2 3

```
/* class Counter */  
public void increment() throws ValueTooLargeException {  
    if(value == Counter.MAX_VALUE) {  
        throw new ValueTooLargeException("counter value is " + value);  
    }  
    else { value ++; }  
}  
  
public void decrement() throws ValueTooSmallException {  
    if(value == Counter.MIN_VALUE) {  
        throw new ValueTooSmallException("counter value is " + value);  
    }  
    else { value --; }  
}  
}
```

Coming Up with Test Cases: A Single, Bounded Variable

Boundries:

Counter.**MIN_VALUE** <= c.**value** <= Counter.**MAX_VALUE**



Lecture 10 - Oct 7

TDD with JUnit

Regression Testing

Example Test 1: VTLE Not Expected

Example Test 2: VTSE Expected

Announcements/Reminders

- Today's class: notes template posted
- Priorities:
 - + **Lab1** solution video released
 - + **Lab2** released
- **ProgTest1**
 - + guide released
 - + PracticeTest1 released
 - + Last Friday's **Review session** materials posted


* VICE or VISE not expected.

Coming Up with **Test Cases**: A Single, Bounded Variable

** VICE expected for inc, VISE expected for dec

Boundries:

Counter.**MIN_VALUE** <= c.value <= Counter.**MAX_VALUE**



JUnit Test Method vs. Method Under Test

@Test

public void test() {

MyClass o = new MyClass();

assertEquals(23, o.getValue());

}

(JUnit) test method
(caller)

value produced
by the implementation

method under test
(callee)

expected
value

expected
value

JUnit test method
(+test)

pass

expectation met.


fail


arguments

Method under test
(getValue)

return
value

Test-Driven Development (TDD): Regression Testing





Self Studies

Creating & Running JUnit Test Cases: Slides 12 to 21

Common Assertions in JUnit: Slide 22

Examples on JUnit: Slides 23 - 25

A Default Test Case that **Fails**

slide 16

The result of running a test is considered:

- **Failure** if either
 - an **assertion failure** (e.g., caused by `fail`, `assertTrue`, `assertEquals`) occurs
 - an **unexpected exception** (e.g., `NullPointerException`, `ArrayIndexOutOfBoundsException`) thrown
- **Success** if neither **assertion failures** nor (unexpected) **exceptions** occur.

fail the first
right away
unconditionally

↓ `fail()` `fail("...")`


slide 19

doing nothing
↳ test passes
trivially!

```
TestCounter.java
1 package tests;
2 import static org.junit.Assert.*;
3 import org.junit.Test;
4 public class TestCounter {
5     @Test
6     public void test() {
7         // fail("Not yet implemented");
8     }
9 }
10
```

Q: What is the easiest way to making this test **pass**?

Design of a Test



JUnit: An Exception Not Expected

```
1 @Test
2 public void testIncAfterCreation() {
3     Counter c = new Counter();
4     assertEquals(Counter.MIN_VALUE, c.getValue());
5     try {
6         c.increment();
7         assertEquals(1, c.getValue());
8     }
9     catch (ValueTooLargeException e) {
10        /* Exception is not expected to be thrown. */
11        fail("ValueTooLargeException is not expected.");
12    }
13 }
```

→ may or may not throw VTLE
→ VTLE not thrown (correct)
— pass.

```
1 @Test
2 public void testIncAfterCreation() {
3     Counter c = new Counter();
4     assertEquals(Counter.MIN_VALUE, c.getValue());
5     try {
6         c.increment();
7         assertEquals(1, c.getValue());
8     }
9     catch (ValueTooLargeException e) {
10        /* Exception is not expected to be thrown. */
11        fail("ValueTooLargeException is not expected.");
12    }
13 }
```

→ VTLE thrown (incorrect)
— fail.

What if increment is
implemented correctly?

test pass

may or may not be imp.

Expected Behaviour: Correctly

Calling c.increment()
when c.value is 0 should not
trigger a ValueTooLargeException

expectation of test.

What if increment is
implemented incorrectly?

e.g., It throws VTLE when
c.value < Counter.MAX_VALUE

Running JUnit Test 1 on Correct Implementation

Expectation
VTLException not
thrown.

```
public void increment() throws ValueTooLargeException {  
    ④ if (value == 0 Counter.MAX_VALUE) {  
        X throw new ValueTooLargeException("counter value is " + value);  
    }  
    else { ⑤ value++; }  
    }  
    0 → ①.
```

test passed
∴ imp.
does not throw
VTLException as
expected.

```
1  @Test  
2  public void testIncAfterCreation() {  
3      ① Counter c = new Counter(); | c.v == 0  
4      ② assertEquals(Counter.MIN_VALUE, c.getValue());  
5      try {  
6          ③ c.increment(); → VTLException not thrown  
7          ④ assertEquals(1, c.getValue());  
8      }  
9      catch (ValueTooLargeException e) {  
10         X /* Exception is not expected to be thrown. */  
11         fail("ValueTooLargeException is not expected.");  
12     }  
13 }  
    pass
```

Running JUnit Test 1 on Incorrect Implementation

```
public void increment() throws ValueTooLargeException {  
    ④ if (value < Counter.MAX_VALUE) {  
        ⑤ throw new ValueTooLargeException("counter value is " + value);  
    }  
    X else { value++; }  
}
```

unexpected.

Expectation

VTL E not
thrown

test failed
- 1 imp.
has thrown the
VTL E unexpectedly.

```
1  @Test  
2  public void testIncAfterCreation() {  
3      ① Counter c = new Counter(); | c.v == 0  
4      ② assertEquals(Counter.MIN_VALUE, c.getValue());  
5      try {  
6          ③ c.increment();  
7          X assertEquals(1, c.getValue());  
8      }  
9      → catch (ValueTooLargeException e) {  
10         /* Exception is not expected to be thrown. */  
11         ⑥ fail("ValueTooLargeException is not expected.");  
12     }  
13 }
```

fail

JUnit: An Exception Expected

```
1 @Test
2 public void testDecFromMinValue() {
3     Counter c = new Counter();
4     assertEquals(Counter.MIN_VALUE, c.getValue());
5     try {
6         c.decrement();
7         fail("ValueTooSmallException is expected.");
8     }
9     catch (ValueTooSmallException e) {
10         /* Exception is expected to be thrown. */
11     }
12 }
```

→ VTSE thrown (correct)
X fail
✓
PASS.

```
1 @Test
2 public void testDecFromMinValue() {
3     Counter c = new Counter();
4     assertEquals(Counter.MIN_VALUE, c.getValue());
5     try {
6         c.decrement();
7         fail("ValueTooSmallException is expected.");
8     }
9     catch (ValueTooSmallException e) {
10         /* Exception is expected to be thrown. */
11     }
12 }
```

→ VTSE not thrown (incorrect)
X fail
fail.

What if decrement is implemented correctly?

VTSE thrown → PASS

Expected Behaviour:

Calling c.decrement()
when c.value is 0 should
trigger a ValueTooSmallException.

expectation:
VTSE should be thrown.

What if decrement is implemented incorrectly?

e.g., It only throws VTSE when
c.value < Counter.MIN_VALUE

→ VTSE not thrown → fail

Running JUnit Test 2 on Correct Implementation

Expectation
VTSF thrown.

```
public void decrement() throws ValueTooSmallException {  
    ④ if (value == Counter.MIN_VALUE) {  
        ⑤ throw new ValueTooSmallException("counter value is " + value);  
    }  
    else { value --; }  
}
```

Correct behaviour!

test passed
∴ imp.
has thrown
VTSF as
expected.

```
1  @Test  
2  public void testDecFromMinValue() {  
3      ① Counter c = new Counter(); | C.V == 0  
4      ② assertEquals(Counter.MIN_VALUE, c.getValue());  
5      try {  
6          ③ c.decrement(); → VTSF thrown  
7          X fail("ValueTooSmallException is expected.");  
8      }  
9      ④ catch (ValueTooSmallException e) {  
10         ⑤ /* Exception is expected to be thrown. */  
11     }  
12 }
```

↓ pass

Running JUnit Test 2 on Incorrect Implementation

```
public void decrement() throws ValueTooSmallException {  
    ④ if (value < Counter.MIN_VALUE) {  
        X throw new ValueTooSmallException("counter value is " + value);  
    }  
    else { ⑤ value --; }  
    0 → -1  
}
```

Expectation
VTSSE thrown

test fail
∴ imp.
did not throw
VTSSE as
expected.

```
1  @Test  
2  public void testDecFromMinValue() {  
3      ① Counter c = new Counter(); | c.v = 0  
4      ② assertEquals(Counter.MIN_VALUE, c.getValue());  
5      try {  
6          ③ c.decrement(); → VTSSE not thrown!  
7          ⑥ fail("ValueTooSmallException is expected.");  
8      }  
9      X catch (ValueTooSmallException e) { fail  
10         /* Exception is expected to be thrown. */  
11     }  
12 }
```

JUnit: Exception Sometimes Expected, Somtimes Not

Expected Behaviour:

Calling c.increment()

3 times to reach c's max **should not** trigger any ValueTooLargeException.

Calling c.increment()

when c is already at its max **should** trigger a ValueTooLargeException

```
1 @Test
2 public void testIncFromMaxValue() {
3     Counter c = new Counter(); | 1. V == 0
4     try {
5         c.increment(); | 2
6         c.increment(); | 3
7         c.increment();
8     }
9     catch (ValueTooLargeException e) {
10        fail("ValueTooLargeException was thrown unexpectedly.");
11    }
12    assertEquals(Counter.MAX_VALUE, c.getValue());
13    try {
14        c.increment(); | 4?
15    }
16    catch (ValueTooLargeException e) {
17        fail("ValueTooLargeException was NOT thrown as expected.");
18    }
19    }
20 }
```

→ P1: NTLEx not expected

→ P2: NTLEx expected

Lecture 11 - Oct 9

TDD with JUnit

Example Test 3:

***Some Exceptions Expected, Some Not
Console Tester vs. JUnit Test
Using a for-Loop for
Call by Value: Principle, Circle Examples***

Announcements/Reminders

- Today's class: [notes template](#) posted
- Office Hour during Reading Week to be announced

Running JUnit Test 3 on Correct Implementation

```
① public void increment() throws ValueTooLargeException {  
    ③ if (value == Counter.MAX_VALUE) {  
        ④ X throw new ValueTooLargeException("counter value is " + value);  
    }  
    else { value ++; }  
}
```

0 → 1
1 → 2
2 → 3

→ correct beh.

test passed
-! imp.
sat expectations
of P1 & P2.

```
1 @Test  
2 public void testIncFromMaxValue() {  
3     ① Counter c = new Counter(); | C.V == 0  
4     try { | C.V == 1 | ④ | C.V == 2 | ⑤ | C.V == 3  
5         ② c.increment(); | c.increment(); | c.increment();  
6     }  
7     catch (ValueTooLargeException e) {  
8         fail("ValueTooLargeException was thrown unexpectedly.");  
9     }  
10    ⑥ assertEquals(Counter.MAX_VALUE, c.getValue()); | ③  
11    try {  
12        ⑦ c.increment(); ~ NLE thrown  
13        X fail("ValueTooLargeException was NOT thrown as expected.");  
14    }  
15    catch (ValueTooLargeException e) {  
16        ⑩ /* Do nothing: ValueTooLargeException thrown as expected. */  
17    }  
18 }
```

pass

Running JUnit Test 3 on Incorrect Implementation

```
public void increment() throws ValueTooLargeException {  
    ③ if (value < Counter.MAX_VALUE) {  
        ④ throw new ValueTooLargeException("counter value is " + value);  
    }  
    else { value++; }  
}
```

→ maxVal chk.

```
1 @Test  
2 public void testIncFromMaxValue() {  
3     ① Counter c = new Counter(); | C.V == 0  
4     try {  
5         ② c.increment(); c.increment(); c.increment();  
6     }  
7     catch (ValueTooLargeException e) {  
8         ⑤ fail("ValueTooLargeException was thrown unexpectedly.");  
9     }  
10    assertEquals(Counter.MAX_VALUE, c.getValue());  
11    try {  
12        c.increment();  
13        fail("ValueTooLargeException was NOT thrown as expected.");  
14    }  
15    catch (ValueTooLargeException e) {  
16        /* Do nothing: ValueTooLargeException thrown as expected. */  
17    }  
18 }
```

→ VLE thrown

→ fail

test failed
- imp.
failed to sat
exp. of pl

Running JUnit Test 3 on Incorrect Implementation

```
public void increment() throws ValueTooLargeException {  
    if (value < Counter.MAX_VALUE) {  
        throw new ValueTooLargeException("counter value is " + value);  
    }  
    else { value++; }  
}
```

0 → 1
1 → 2
2 → 3
3 → 4

test failed
even though sat P/s
exp, failed to sat P/s exp.

```
1 @Test  
2 public void testIncFromMaxValue() {  
3     Counter c = new Counter();  
4     try {  
5         c.increment(); c.increment(); c.increment();  
6     }  
7     catch (ValueTooLargeException e) {  
8         fail("ValueTooLargeException was thrown unexpectedly.");  
9     }  
10    assertEquals(Counter.MAX_VALUE, c.getValue());  
11    try {  
12        c.increment();   
13        fail("ValueTooLargeException was NOT thrown as expected.");  
14    }  
15    catch (ValueTooLargeException e) {  
16        /* Do nothing: ValueTooLargeException thrown as expected. */  
17    }  
18 }
```

Handwritten notes on the test code:
- Line 3: $C.V = 0$
- Line 4: $C.V = 1$
- Line 5: $C.V = 2$
- Line 8: $C.V = 3$
- Line 12: $\rightarrow$ VLE not thrown
- Line 15: $\rightarrow$ fail.

Exercise: Console Tester vs. JUnit Test

WTI
Example question
nested
try-catch?

Q. Can this **console tester** work like the **JUnit test** testIncFromMaxValue does?

```
1 public class CounterTester {
2     public static void main(String[] args) {
3         Counter c = new Counter();
4         println("Current val: " + c.getValue());
5         try {
6             c.increment(); c.increment(); c.increment();
7             println("Current val: " + c.getValue());
8         }
9         catch (ValueTooLargeException e) {
10            println("Error: ValueTooLargeException thrown unexpectedly.");
11        }
12        try {
13            c.increment();
14            println("Error: ValueTooLargeException NOT thrown.");
15        } /* end of inner try */
16        catch (ValueTooLargeException e) {
17            println("Success: ValueTooLargeException thrown.");
18        }
19    } /* end of main method */
20 } /* end of CounterTester class */
```

Witness 0 0 →
if (value < max) {
 throw VTLException(...)

Console
Error.
Success

Hint: What if one of the first 3 c.increment() mistakenly throws a ValueTooLargeException?

Exercise: Combining catch Blocks?

Q: Can we rewrite `testIncFromMaxValue` to:

```
1  @Test
2  public void testIncFromMaxValue() {
3      Counter c = new Counter();
4      try {
5          c.increment();
6          c.increment();
7          c.increment();
8          assertEquals(Counter.MAX_VALUE, c.getValue());
9          c.increment();
10         fail("ValueTooLargeException was NOT thrown as expected.");
11     }
12     catch (ValueTooLargeException e) {}
13 }
```

Handwritten annotations on the code:

- Line 5: **P1** (orange)
- Line 9: **P2** (pink)
- Line 12: A pink box around the empty catch block with an arrow pointing to it and the text "VTLSE caught."

Hint: Say **Line 12** is executed,

is it clear if that **ValueTooLargeException** was thrown as expected?

Handwritten notes explaining the ambiguity:

- from P1 → not expected → **fail** (red)
- from P2 → expected → **pass** (green)
- A blue box labeled "ambiguous" encloses the "fail" and "pass" outcomes.

Testing Many Values in a Single Test

what if


MIN : 0

MAX : 1000

Loops can make it effective on generating test cases:

```
1 @Test
2 public void testIncDecFromMiddleValues() {
3     Counter c = new Counter();
4     try {
5         for(int i = Counter.MIN_VALUE; i < Counter.MAX_VALUE; i++) {
6             int currentValue = c.getValue();
7             c.increment();
8             assertEquals(currentValue + 1, c.getValue());
9         }
10        for(int i = Counter.MAX_VALUE; i > Counter.MIN_VALUE; i--) {
11            int currentValue = c.getValue();
12            c.decrement();
13            assertEquals(currentValue - 1, c.getValue());
14        }
15    }
16    catch (ValueTooLargeException e) {
17        fail("ValueTooLargeException is thrown unexpectedly");
18    }
19    catch (ValueTooSmallException e) {
20        fail("ValueTooSmallException is thrown unexpectedly");
21    }
22 }
```

i: 0 1 2



Method Call: Callee vs. Caller

```
class A {  
    ...  
    void m(T param) {  
        /* use of param */  
    }  
}
```

declaration of the caller's method parameter

```
class B {  
    ...  
    void n(...){  
        A co = new A();  
        co.m(arg);  
    }  
}
```

caller: B.n

callee: A.m

value used to call the callee's method

call
by
value.

Before the 1st line of method `m` is executed, there's an implicit variable assignment EXEC:

`param = arg`




Call by Value: Primitive Argument

```
class Circle {  
    int radius;  
    void setRadius(int r) {  
        this.radius = r;  
    }  
}
```

```
class CircleUser {  
    ...  
    ① Circle c = new Circle();  
    ② int arg = 10;  
    ③ c.setRadius(arg);  
}
```

call by
value:

r = arg




Call by Value: Reference Argument

```
class Circle {  
    int radius;  
    Circle() {}  
    Circle(int r) {  
        this.radius = r;  
    }  
    void setRadius(Circle c) {  
        this.radius = c.radius;  
    }  
}
```

Call by value: c = arg

```
class CircleUser {  
    ...  
    ① Circle c = new Circle();  
    ② Circle arg = new Circle(10);  
    ③ c.setRadius(arg);  
}
```

c.0.



Lecture 12 - Oct 21

Object Equality.

Call by Value: Prim. vs. Ref. Types
Equality: == vs. equals
Default Version of equals in Object Class

Announcements/Reminders

- Today's class: [notes template](#) posted
- **ProgTest0, ProgTest1** grading process:
 - + TAs are due to return results to me Tuesday afternoon.
 - + I will take one day or two to finalize the results.
- **WrittenTest1** next Wednesday (October 29)
 - + Some **practice questions** on eClass
 - + **Lecture 12** and **Lecture 13** this week are covered.
 - + Zoom **Review Session**: 4 PM on Saturday, October 25
- **Lab3** to be released

Call by Value: Re-Assigning Primitive Parameter



```
public class Util {  
    void reassignInt(int j) {  
        j = j + 1; }  
    void reassignRef(Point q) {  
        Point np = new Point(6, 8);  
        q = np; }  
    void changeViaRef(Point q) {  
        q.moveHorizontally(3);  
        q.moveVertically(4); } }
```

⑤ $j = \bar{j}$

c.b.v.

```
1 @Test  
2 public void testCallByVal() {  
3     ① Util u = new Util();  
4     ② int i = 10;  
5     ③ assertTrue(i == 10);  
6     ④ u.reassignInt(i);  
7     ⑦ assertTrue(i == 10);  
8 }
```

Copy of arg. $\bar{i}$
is modified.



Call by Value: Re-Assigning Reference Parameter


* param. (q) is re-assigned to np.

xx avg (p)

stays the same.

```
public class Util {
    void reassignInt(int j) {
        j = j + 1;
    }
    void reassignRef(Point q) {
        Point np = new Point(6, 8);
        q = np;
    }
    void changeViaRef(Point q) {
        q.moveHorizontally(3);
        q.moveVertically(4);
    }
}
```

```
1 @Test
2 public void testCallByRef_1() {
3     ① Util u = new Util();
4     ② Point p = new Point(3, 4);
5     ③ Point refOfPBefore = p;
6     ④ u.reassignRef(p);
7     ⑤ assertTrue(p == refOfPBefore);
8     ⑥ assertTrue(p.getX() == 3);
9     ⑦ assertTrue(p.getY() == 4);
10 }
```




```
public class Point {
    private int x;
    private int y;
    public Point(int x, int y) {
        this.x = x;
        this.y = y;
    }
    public int getX() { return this.x; }
    public int getY() { return this.y; }
    public void moveVertically(int y) { this.y += y; }
    public void moveHorizontally(int x) { this.x += x; }
}
```

Call by Value: Calling Mutator on Reference Parameter

```
public class Util {  
    void reassignInt(int j) {  
        j = j + 1; }  
    void reassignRef(Point q) {  
        Point np = new Point(6, 8);  
        q = np; }  
    void changeViaRef(Point q) {  
        q.moveHorizontally(3);  
        q.moveVertically(4); }  
}
```

```
1 @Test  
2 public void testCallByRef_2() {  
3     Util u = new Util();  
4     Point p = new Point(3, 4);  
5     Point refOfPBefore = p;  
6     u.changeViaRef(p);  
7     assertTrue(p == refOfPBefore);  
8     assertTrue(p.getX() == 6);  
9     assertTrue(p.getY() == 8);  
10 }
```



```
public class Point {  
    private int x;  
    private int y;  
    public Point(int x, int y) {  
        this.x = x;  
        this.y = y;  
    }  
    public int getX() { return this.x; }  
    public int getY() { return this.y; }  
    public void moveVertically(int y) { this.y += y; }  
    public void moveHorizontally(int x) { this.x += x; }  
}
```

Equality $\begin{cases} == \\ equals \end{cases}$

Primitive

1. $==$ (value)
2. $equals$ X

`int i = 23;`

`int j = 46;`

`i == j`
 false

1. $==$ (address/ref)
2. $equals$
 $\hookrightarrow$ default version?
 $\hookrightarrow$ customized version?

Reference

`Point p1 = new Point(...);`

`Point p2 = new Point(...);`

invalid C.O.
`i.equals(j)` X

$\hookrightarrow$ compilation error

`Integer i = new Integer(23);`
`Integer j = new Integer(23);`
`i.equals(j)`
 $\neq$
 false $\because$ diff. refs.

`i` $\rightarrow$

i
v. 23

 temp

`j` $\rightarrow$

j
v. 23

1. $==$ (address/ref)
2. $equals$
 $\hookrightarrow$ default version?
 $\hookrightarrow$ customized version?

`p1.equals(p2)`
 $\hookrightarrow$ compares result depends on how the Point class defines equals.

Object Equality: First Example

```
class PointV1 {  
    private int x;  
    private int y;  
    public PointV1(int x, int y) {  
        this.x = x;  
        this.y = y;  
    }  
}
```

Q1:

Does PointTester compile, given that **equals** is not declared in PointV1?

YES.

Q2:

Where does **equals** come from?

```
class PointTester {  
    ... main(...) {  
        PointV1 p1 = new PointV1(3, 4);  
        PointV1 p2 = new PointV1(3, 4);  
        System.out.println(p1.equals(p2));  
    }  
}
```

bori down into p1 == p2


↳ Object

```
public boolean equals(Object obj) {  
    return (this == obj);  
}
```

p1 p2

1. not explicitly defined in PointV1
2. default version from Object is called.*

The equals Method: To **Override** or **Not**?



The equals Method: Default Version

```
public class Object {  
    ...  
    public boolean equals(Object obj) {  
        return this == obj;  
    }  
}
```




extends

default version
inherited to
all classes.

```
public class PointV1 {  
    private int x;  
    private int y;  
    public PointV1 (int x, int y) {  
        this.x = x;  
        this.y = y;  
    }  
}
```

Since PointV1 does not explicitly override/define equals → default version inherited from Object is used.

```
1 String s = "(2, 3)";  
2 PointV1 p1 = new PointV1(2, 3);  
3 PointV1 p2 = new PointV1(2, 3);  
4 PointV1 p3 = new PointV1(4, 6);  
5 System.out.println(p1 == p2); /* [ ] */  
6 System.out.println(p2 == p3); /* [ ] */  
7 System.out.println(p1.equals(p1)); /* [ ] */  
8 System.out.println(p1.equals(null)); /* [ ] */  
9 System.out.println(p1.equals(s)); /* [ ] */  
10 System.out.println(p1.equals(p2)); /* [ ] */  
11 System.out.println(p2.equals(p3)); /* [ ] */
```



Lecture 13 - Oct 23

Object Equality.

Call by Value: Array Indexing

Deciding the Version of equals Method

Short-Circuit Evaluation

Announcements/Reminders




- Today's class: [notes template](#) posted
- **WrittenTest1** next Wednesday (October 29)
 - + Some **practice questions** on eClass
 - + Past review session materials released
 - + **Lecture 12** and **Lecture 13** this week are covered.
 - + Zoom **Review Session**: 4 PM on Saturday, October 25
 - * We can focus on revisiting parts of the covered topics.
- **Lab3** released

Call by Value: Array Indexing

```
class Student {  
    String[] courses; int noc;  
    void register(String course) {  
    }  
}
```

```
RygSystem sys = new RygSystem();  
Student s1 = new Student("alan");  
Student s2 = new Student("mark");  
sys.add(s1); sys.add(s2);  
sys.register(s1, "EECS1020");  
sys.register(s2, "MATH1025");  
sys.registerAll("EECS2030");
```

```
class RegSystem {  
    Student[] ss; int nos;  
    void register(Student s, String course) {  
        (s.register(course);  
    }  
    void registerAll(String course) {  
        for(int i = 0; i < nos; i++) {  
            this.register(this.ss[i], course);  
        }  
    }  
}
```



C.b.v. happens for every iteration.

Method Call: When Multiple Versions are Available

C.O. is all that matters to determining the version of equals method being called


x.equals(y)

which version?

1. default version (from object class)
2. overridden version (if exists).

Principle:

- + Trace the **dynamic type** of object "pointed to" by **reference variable x** at the point of executing this line of method call.
- + Is the **equals** method overridden in this **dynamic type**?
 - * Yes -> Invoke the overridden version.
 - * No -> Invoke the default version (inherited from **Object**).




$x = \text{new PointV}();$

$x.\text{equals}(\dots)$

default
version
called.

x


~~$\rightarrow$~~



$x = \text{new PointVZ}();$

$x.\text{equals}(\dots)$

overridden version
called






The equals Method: Default Version

```
public class Object {  
    ...  
    public boolean equals(Object obj) {  
        return this == obj;  
    }  
}
```

extends

```
public class PointV1 {  
    private int x;  
    private int y;  
    public PointV1 (int x, int y) {  
        this.x = x;  
        this.y = y;  
    }  
}
```

```
1 String s = "(2, 3)";  
2 PointV1 p1 = new PointV1(2, 3);  
3 PointV1 p2 = new PointV1(2, 3);  
4 PointV1 p3 = new PointV1(4, 6);  
5 System.out.println(p1 == p2);  
6 System.out.println(p2 == p3);  
7 System.out.println(p1.equals(p1));  
8 System.out.println(p1.equals(null));  
9 System.out.println(p1.equals(s));  
10 System.out.println(p1.equals(p2));  
11 System.out.println(p2.equals(p3));
```




1. all O.O.s have the same D.T. PointV1
2. PointV1 has not overridden equals method
3. ∴ default version from Object invoked.

27: p1 == p1 → ①

28: p1 == null → ②

29: "p1 == s" → ③

s → String
"(2, 3)"



$p1 = \text{new } \overset{\text{PointV}}{\text{...}} \Rightarrow$
 $s = \text{"..."} \Rightarrow$



deduced types different
 ↳ forbidden to compare their addresses directly.

① p1.equals(s) → (F)

↳ "p1 == s"
 ↳ Compiles ∴

boolean equals (Object obj)

any type of argument is acceptable.



② $p1 == s \rightarrow$ Compilation Error

Call by Value: Invoking the Overridden equals


```
public class Object {  
    ...  
    public boolean equals(Object obj) {  
        return this == obj;  
    }  
}
```

extends

```
public class PointV2 {  
    private int x;  
    private int y;  
    public PointV2(int x, int y) { ... }  
    public boolean equals(Object obj) {  
        if (this == obj) { return true; }  
        if (obj == null) { return false; }  
        if (this.getClass() != obj.getClass()) { return false }  
        PointV2 other = (PointV2) obj;  
        return this.x == other.x  
            && this.y == other.y;  
    }  
}
```

C.B.V. obj = p3

```
1 PointV2 p1 = new PointV2(3, 4);  
2 PointV2 p2 = new PointV2(3, 4);  
3 PointV2 p3 = new PointV2(4, 5);  
4 System.out.println(p1 == p1); /* true */  
5 System.out.println(p1.equals(p1)); /* true */  
6 System.out.println(p1 == p2); /* false */  
7 System.out.println(p1.equals(p2)); /* true */  
8 System.out.println(p2 == p3); /* false */  
9 System.out.println(p2.equals(p3)); /* false */
```



Short-Circuit Evaluation: && ^{and, conjunction}

Left Operand op1	Right Operand op2	op1 && op2
2.1 true	true	true
true	false	false
false	true	false
false	false	false

the only way for && to be T, is when both operands are true.

Test Inputs:

x = 0, y = 10
x = 5, y = 10

```
System.out.println("Enter x:");
int x = input.nextInt();
System.out.println("Enter y:");
int y = input.nextInt();
if (x != 0 && y / x > 2) {
    System.out.println("y / x is greater than 2");
}
else { /* !(x != 0 && y / x > 2) == (x == 0 || y / x <= 2) */
    if (x == 0) {
        System.out.println("Error: Division by Zero");
    }
    else {
        System.out.println("y / x is not greater than 2");
    }
}
```

Annotations:
 - **Division by Zero** (circled F)
 - **if x == 0** (skipped)
 - **0 != 0** (F)
 - **10/0 > 2** (skipped)
 - **5 != 0** (T)
 - **10/5 > 2** (T)

1. Evaluate L to R

2.1. If op1 eval. to T
 ↳ eval op2 to decide the final result of &&

2.2. If op1 eval. to F
 ↳ skip eval. of op2 (F)
 the final result of && is

Short-Circuit Evaluation: $\parallel$ ^{or, disjunction}

Left Operand op1	Right Operand op2	op1 op2
false	false	false
true	false	true
false	true	true
true	true	true

2.1. (circled in blue)

2.2. (circled in pink)

```
System.out.println("Enter x:");
int x = input.nextInt();
System.out.println("Enter y:");
int y = input.nextInt();
if(x == 0 || y / x > 2) {
    if(x == 0) {
        System.out.println("Error: Division by Zero");
    }
    else {
        System.out.println("y / x is greater than 2");
    }
}
else { /* !(x == 0 || y / x > 2) == (x != 0 && y / x <= 2) */
    System.out.println("y / x is not greater than 2");
}
```

Test Inputs:

x = 0, y = 10

x = 5, y = 10

the only way to make $\parallel$ F is both operands are false.

op1 || op2

1. Evaluate L to R

2.1. If op1 eval. to F
↳ eval op2 to decide the final result of $\parallel$

2.2. if op1 eval. to T
↳ skip eval. of op2 the final result of $\parallel$ is T

Math

$P \wedge Q$
 $P \vee Q$

Commutativity

$$P \wedge Q \equiv Q \wedge P$$

Java


$P \&\&Q$

$P \parallel Q$

$\rightarrow$


$P \&\&Q$
 $Q \&\&P$

not identical
 $\hookrightarrow$ short-circuit evaluation



guarding condition (without passing it's skip 2nd operand)

&&



some expression to protect.

y/x ...

||

...

y/x ...

logical negation of each other.

error condition (if it's true, skip 2nd operand).

A: array of values

a.length == 10
0..9

is this always
guaranteed?
No.

①

10
0..9

i > 0

&&

a[i]

= v

&&

i < a.length - 1

g1

i == length
of array
(10)

10

a[10]

→ IOOBE!

Correct:

g2

g1 && g2 && ...
a[i]

Example: use 11

Short-Circuit Evaluation: Common Errors

Test Inputs:

$x = 0, y = 10$

Short-Circuit Evaluation is not exploited: crash when $x == 0$

```
if (y / x > 2 && x != 0) {  
    /* do something */  
}  
else {  
    /* print error */ }
```

Short-Circuit Evaluation is not exploited: crash when $x == 0$

```
if (y / x <= 2 || x == 0) {  
    /* print error */  
}  
else {  
    /* do something */ }
```

Lecture 14 - Oct 28

Object Equality.

Overridden equals: Phases 1, 2, 3
Static vs. Dynamic Types, Type Casting

Announcements/Reminders

- Today's class: notes template posted
- **ProgTest0** and **ProgTest1 marks** and feedback released
- **WrittenTest1** this Wednesday (October 29)
 - + Some **practice questions** on eClass
 - + Past review session materials released
 - + **Lecture 12** and **Lecture 13** this week are covered.
- **Lab3** released

The equals Method: Overridden Version

Phase 1


```
public class Object {  
    ...  
    public boolean equals(Object obj) {  
        return this == obj;  
    }  
}
```

C.O. P1 equals (P2) *arg.* → T
→ F

extends

```
public class PointV2 {  
    private int x;  
    private int y;  
    public PointV2(int x, int y) { ... }  
    public boolean equals(Object obj) {  
        if (this == obj) { return true; }  
        if (obj == null) { return false; }  
        if (this.getClass() != obj.getClass()) { return false }  
        PointV2 other = (PointV2) obj;  
        return this.x == other.x  
            && this.y == other.y;  
    }  
}
```

if C.O. and obj param. are the same object → they're equal



obj = P2 (arg.)

PointV2	
x	
y	

The equals Method: Overridden Version

Example 1: Trace L7

```
public class Object {  
    ...  
    public boolean equals(Object obj) {  
        return this == obj;  
    }  
}
```

extends


```
public class PointV2 {  
    private int x;  
    private int y;  
    public PointV2 (int x, int y) { ... }  
    public boolean equals(Object obj) {  
        if (this == obj) { return true; }  
        if (obj == null) { return false; }  
        if (this.getClass() != obj.getClass()) { return false; }  
        PointV2 other = (PointV2) obj;  
        return this.x == other.x  
            && this.y == other.y;  
    }  
}
```

obj = p1
∵ p1 and p1 are the same object.

DT.

```
1 String s = "(2, 3)";  
2 PointV2 p1 = new PointV2(2, 3);  
3 PointV2 p2 = new PointV2(2, 3);  
4 PointV2 p3 = new PointV2(4, 6);  
5 System.out.println(p1 == p2); /* [ ] */  
6 System.out.println(p2 == p3); /* [ ] */  
7 System.out.println(p1.equals(p1)); /* [ ] */  
8 System.out.println(p1.equals(null)); /* [ ] */  
9 System.out.println(p1.equals(s)); /* [ ] */  
10 System.out.println(p1.equals(p2)); /* [ ] */  
11 System.out.println(p2.equals(p3)); /* [ ] */
```

L.O.
avg



The equals Method: Overridden Version

Phase 2

```
public class Object {  
    ...  
    public boolean equals(Object obj) {  
        return this == obj;  
    }  
}
```

P1.equals(P2)
this == null → NPE.

* alt. phase 2

```
if (obj == null) {  
    if (this == null) {  
        return true;  
    } else { /* this != null */  
        return false;  
    }  
}
```

unreadable
if this were null,
then a NPE


would
have
already
occurred.

extends

```
public class PointV2 {  
    private int x;  
    private int y;  
    public PointV2(int x, int y) { ... }  
    public boolean equals(Object obj) {  
        if (this == obj) { return true; }  
        * if (obj == null) { return false; }  
        if (this.getClass() != obj.getClass()) { return false }  
        PointV2 other = (PointV2) obj;  
        return this.x == other.x  
            && this.y == other.y;  
    }  
}
```

PointV2	
x	
y	

reaching this line
means this != obj



The equals Method: Overridden Version




Example 1: Trace L8

```
public class Object {  
    ...  
    public boolean equals(Object obj) {  
        return this == obj;  
    }  
}
```

extends

```
public class PointV2 {  
    private int x;  
    private int y;  
    public PointV2 (int x, int y) { }  
    public boolean equals(Object obj) {  
        if (this == obj) { return true; }  
        if (obj == null) { return false; }  
        if (this.getClass() != obj.getClass()) { return false; }  
        PointV2 other = (PointV2) obj;  
        return this.x == other.x  
            && this.y == other.y;  
    }  
}
```

```
1 String s = "(2, 3)";  
2 PointV2 p1 = new PointV2(2, 3);  
3 PointV2 p2 = new PointV2(2, 3);  
4 PointV2 p3 = new PointV2(4, 6);  
5 System.out.println(p1 == p2); /*   
6 System.out.println(p2 == p3); /*   
7 System.out.println(p1.equals(p1)); /*   
8 System.out.println(p1.equals(null)); /*   
9 System.out.println(p1.equals(s)); /*   
10 System.out.println(p1.equals(p2)); /*   
11 System.out.println(p2.equals(p3)); /*
```



Handwritten notes:

- for p1, obj is not null
- obj is null

may be changed runtime type: determines the version of method called.

Static Type, Dynamic Type, Type Casting

var	ST	exp.
o1	C1	m1, equals
o2	C2	m2, equals
o3	Object	equals

Static Type: a ref variable's declared type

Dynamic Type: type of address currently stored in a ref variable

Type Casting: creating an expression of certain static type

```


class C1 {
    ...
    public void m1() {...}
}

class C2 {
    ...
    public void m2() {...}
}
    
```

```

C1 o1 = new C1();
C2 o2 = new C2();
o1.m1();
o1.m2(); X
o2.m1(); X
o2.m2();
Object o3;
o3 = o1;
o3.m1(); X
o3.m2(); X
((C1) o3).m1(); ✓
((C1) o3).m2(); X
o3 = o2;
((C2) o3).m1(); X
((C2) o3).m2(); ✓
    
```

Create a new copy of address with a different S.T.



not compile
 - ST of o3 is Object whose expectation does not match m1.


o3 is C1
 ST: C1
 alias with ST C1
 alias with ST C2

fixed
 declared type
 determines the range of methods & attributes that can be invoked on that ref. var.

ST: C1
 ST: C2

m2 is not an exp. of o1's
 ST (C1) C1 o1

Object o3
 C1 o2



Expectation of
a type/class:
range of meth./atts
callable on that
type

Given a line of method call:

obj. [✓]m(...)

(1) Does it Compile?

↳ look at the S.T. of C.O. obj.

(2) If it compiles, which version of m is called?

↳ look at the P.T of C.O. obj.

parent of every class

Object
Object

obj =

new

SomeClass();

can be any class

obj =

obj2;

↓
declared type
can be any class.

force the to happen fast.

$(C_1) \text{ } 03.ml$
 x not comp./p

Object 03 = ...


Object 03 = not going to change
 when 03's pointing to.

$(C_1) 03$

"casting 03 to C_1 "
 "creating an alias of 03 with ST. C_1 "

Object 03

exp: equals



03's ST: object

$(C_1) 03.ml$

03's ST: object

exp: ml, equals.

$(C_1) 03$
 alias with C_1

The equals Method: Overridden Version

Phase 3

```
public class Object {  
    ...  
    public boolean equals(Object obj) {  
        return this == obj;  
    }  
}
```


extends

```
public class PointV2 {  
    private int x;  
    private int y;  
    public PointV2(int x, int y) { ... }  
    public boolean equals(Object obj) {  
        if (this == obj) { return true; }  
        if (obj == null) { return false; }  
        if (this.getClass() != obj.getClass()) { return false; }  
        PointV2 other = (PointV2) obj;  
        return this.x == other.x  
            && this.y == other.y;  
    }  
}
```

*this != obj
obj != null*

return the D.T. of the context objects

objects with different D.T.s are not equal to each other.



PointV2	
x	
y	

The equals Method: Overridden Version

Example 1: Trace L9


```
public class Object {  
    ...  
    public boolean equals(Object obj) {  
        return this == obj;  
    }  
}
```

extends

```
public class PointV2 {  
    private int x;  
    private int y;  
    public PointV2 (int x, int y) { ... }  
    public boolean equals(Object obj) {  
        if(this == obj) { return true; }  
        if(obj == null) { return false; }  
        if(this.getClass() != obj.getClass()) { return false }  
        PointV2 other = (PointV2) obj;  
        return this.x == other.x  
            && this.y == other.y;  
    }  
}
```

```
1 String s = "(2, 3)";  
2 PointV2 p1 = new PointV2(2, 3);  
3 PointV2 p2 = new PointV2(2, 3);  
4 PointV2 p3 = new PointV2(4, 6);  
5 System.out.println(p1 == p2); /* ████████ */  
6 System.out.println(p2 == p3); /* ████████ */  
7 System.out.println(p1.equals(p1)); /* ████████ */  
8 System.out.println(p1.equals(null)); /* ████████ */  
9 System.out.println(p1.equals(s)); /* ████████ */  
10 System.out.println(p1.equals(p2)); /* ████████ */  
11 System.out.println(p2.equals(p3)); /* ████████ */
```

rn.
false.



Lecture 15 - Oct 30

Object Equality

Overridden equals: Phase 4
Short-Circuit, Logical Implication
JUnit: assertEquals vs assertEquals

Announcements/Reminders

- Today's class: [notes template](#) posted
- **ProgTest0** and **ProgTest1 marks** and feedback released
- **Lab3** released

The equals Method: Overridden Version

Phase 4

```
public class Object {  
    ...  
    public boolean equals(Object obj) {  
        return this == obj;  
    }  
}
```

* PointV2 other =
(PointV2) obj;



extends

d.t. of C.O. this

```
public class PointV2 {  
    private int x;  
    private int y;  
    public PointV2(int x, int y) { ... }  
    public boolean equals(Object obj) {  
        if (this == obj) { return true; }  
        if (obj == null) { return false; }  
        if (this.getClass() != obj.getClass()) { return false; }  
        * PointV2 other = (PointV2) obj;  
        return this.x == other.x  
            && this.y == other.y;  
    }  
}
```

this != obj
obj != null
this.getClass() !=
obj.getClass()

Compile '1' ST of other is PointV2.



alt. cast exp of ST. PointV2
$$\text{this.x} == \frac{\text{obj.x}}{x} \because \text{ST of obj is object.}$$

$$\&\& \text{this.y} == \frac{\text{obj.y}}{y}$$

PointV2	
x	
y	

The equals Method: Overridden Version

Example 1: Trace L10


D.T.

```
public class Object {  
    ...  
    public boolean equals(Object obj) {  
        return this == obj;  
    }  
}
```

extends

```
public class PointV2 {  
    private int x;  
    private int y;  
    public PointV2 (int x, int y) { ... }  
    public boolean equals(Object obj) {  
        if(this == obj) { return true; }  
        if(obj == null) { return false; }  
        if(this.getClass() != obj.getClass()) { return false }  
        PointV2 other = (PointV2) obj;  
        return this.x == other.x  
            && this.y == other.y;  
    }  
}
```

```
1 String s = "(2, 3)";  
2 PointV2 p1 = new PointV2(2, 3);  
3 PointV2 p2 = new PointV2(2, 3);  
4 PointV2 p3 = new PointV2(4, 6);  
5 System.out.println(p1 == p2); /*   
6 System.out.println(p2 == p3); /*   
7 System.out.println(p1.equals(p1)); /*   
8 System.out.println(p1.equals(null)); /*   
9 System.out.println(p1.equals(s)); /*   
10 System.out.println(p1.equals(p2)); /*   
11 System.out.println(p2.equals(p3)); /*
```



Object

obj

PointV2 other

(PointV2) obj

return false
Exception

The equals Method: Overridden Version


Example 1: Trace L11

```
public class Object {  
    ...  
    public boolean equals(Object obj) {  
        return this == obj;  
    }  
}
```

extends

```
public class PointV2 {  
    private int x;  
    private int y;  
    public PointV2 (int x, int y) { ... }  
    public boolean equals(Object obj) {  
        if(this == obj) { return true; }  
        if(obj == null) { return false; }  
        if(this.getClass() != obj.getClass()) { return false }  
        PointV2 other = (PointV2) obj;  
        return this.x == other.x  
            && this.y == other.y;  
    }  
}
```

```
1 String s = "(2, 3)";  
2 PointV2 p1 = new PointV2(2, 3);  
3 PointV2 p2 = new PointV2(2, 3);  
4 PointV2 p3 = new PointV2(4, 6);  
5 System.out.println(p1 == p2); /* [ ] */  
6 System.out.println(p2 == p3); /* [ ] */  
7 System.out.println(p1.equals(p1)); /* [ ] */  
8 System.out.println(p1.equals(null)); /* [ ] */  
9 System.out.println(p1.equals(s)); /* [ ] */  
10 System.out.println(p1.equals(p2)); /* [ ] */  
11 System.out.println(p2.equals(p3)); /* [ ] */
```



The equals Method:

To Override or Not?

```
public class Object {  
    ...  
    public boolean equals(Object obj) {  
        return this == obj;  
    }  
}
```

extends

extends


```
public class PointV1 {  
    private int x;  
    private int y;  
    public PointV1(int x, int y) {  
        this.x = x;  
        this.y = y;  
    }  
}
```

```
public class PointV2 {  
    private int x; double y;  
    public PointV2(double x, double y) { ... }  
    boolean equals(Object obj) {  
        if(this == obj) { return true; }  
        if(obj == null) { return false; }  
        if(this.getClass() != obj.getClass()) { return false }  
        PointV2 other = (PointV2) obj;  
        return this.x == other.x  
            && this.y == other.y;  
    }  
}
```

default
version from
Object
is called
↳
p1 == p2
overridden
version from
PointV2
is called

```
1 String s = "(2, 3)";  
2 PointV1 p1 = new PointV1(2, 3);  
3 PointV1 p2 = new PointV1(2, 3);  
4 PointV1 p3 = new PointV1(4, 6);  
5 System.out.println(p1 == p2); /* false */  
6 System.out.println(p2 == p3); /* false */  
7 System.out.println(p1.equals(p1)); /* true */  
8 System.out.println(p1.equals(null)); /* false */  
9 System.out.println(p1.equals(s)); /* false */  
10 System.out.println(p1.equals(p2)); /* false */  
11 System.out.println(p2.equals(p3)); /* false */
```

```
1 String s = "(2, 3)";  
2 PointV2 p1 = new PointV2(2, 3);  
3 PointV2 p2 = new PointV2(2, 3);  
4 PointV2 p3 = new PointV2(4, 6);  
5 System.out.println(p1 == p2); /* false */  
6 System.out.println(p2 == p3); /* false */  
7 System.out.println(p1.equals(p1)); /* true */  
8 System.out.println(p1.equals(null)); /* false */  
9 System.out.println(p1.equals(s)); /* false */  
10 System.out.println(p1.equals(p2)); /* true */  
11 System.out.println(p2.equals(p3)); /* false */
```



```

public class PointV2 {
    private int x;
    private int y;
    public PointV2 (int x, int y) { ... }
    public boolean equals(Object obj) {
        if (this == obj) { return true; }
        if (obj == null) { return false; }
        if (this.getClass() != obj.getClass()) { return false; }
        PointV2 other = (PointV2) obj;
        return this.x == other.x
            && this.y == other.y;
    }
}

```

..... → risk of NPE

a ☐ ~~if (① && ②) { return false; }~~

b ☐ ~~if (② && ①) { rn. false; }~~

c ☒ if (① || ②) { rn. false; }

d ☐ if (② || ①) { rn. false; }

↘ if true, skip eval. ②
 ↓ if obj is null NPE would've occurred before evaluating ①.

The equals Method: Overridden Version

Example 2

```
public class Object {  
    ...  
    public boolean equals(Object obj) {  
        return this == obj;  
    }  
}
```

extends

obj1
obj2

```
public class PointV2 {  
    private int x;  
    private int y;  
    public PointV2(int x, int y) { ... }  
    public boolean equals(Object obj) {  
        if(this == obj) { return true; }  
        if(obj == null) { return false; }  
        if(this.getClass() != obj.getClass()) { return false }  
        PointV2 other = (PointV2) obj;  
        return this.x == other.x  
            && this.y == other.y;  
    }  
}
```

```
1 PointV2 p1 = new PointV2(3, 4);  
2 PointV2 p2 = new PointV2(3, 4);  
3 PointV2 p3 = new PointV2(4, 5);  
4 System.out.println(p1 == p1); /* [ ] */  
5 System.out.println(p1.equals(p1)); /* [ ] */  
6 System.out.println(p1 == p2); /* [ ] */  
7 System.out.println(p1.equals(p2)); /* [ ] */  
8 System.out.println(p2 == p3); /* [ ] */  
9 System.out.println(p2.equals(p3)); /* [ ] */
```

p1

PointV2	
x	
y	

p2

PointV2	
x	
y	

p3

PointV2	
x	
y	

obj1 == obj2

(A) Two objects are **reference**-equal.

(B) Two objects are **contents**-equal.

obj1.equals(obj2)

- If (A) is true, then (B) is true.

- If (B) is true, then (A) is true.

not valid.

A → B

B → A

Logical Implication

$P \rightarrow Q$
 $P \Rightarrow Q$

false when:
 P is true
 Q is false.

it rains $\rightarrow$ outdoor ground wet

it rains (T)
outdoor ground wet (F) $\rightarrow$ implication is false.

assertSame vs. assertEquals

pass if: $exp1 == exp2$
fail if: $exp1 != exp2$

assertSame(exp1, exp2) ^{Any objects}

- Passes if exp1 and exp2 are references to the same object

≈ **assertTrue**(exp1 == exp2)

≈ **assertFalse**(exp1 != exp2)


```
Point v1 p1 = new Point v1(3, 4);
```

```
Point v1 p2 = new Point v1(3, 4);
```

```
Point v1 p3 = p1;
```

```
assertSame(p1, p3);
```

```
assertSame(p2, p3);
```




assertEquals(exp1, exp2)

- ≈ `exp1 == exp2` if exp1 and exp2 are **primitive** type

```
int i = 10;
```

```
int j = 20;
```

```
assertEquals(i, j);
```



ref types, any type
assertEquals(exp1, exp2)

↳ assertEquals(exp1.equals(exp2))

① assertEquals(exp1, exp2)

↳ assertEquals(exp1, exp2)

version in

exp1's D.T.

② assertEquals(exp2, exp1)

↳ assertEquals(exp2, exp1)

version in
exp2's D.T.

assertEquals: Reference Comparison or Not

* $\text{assertT}(\text{p1.equals(p2)})$
** $\text{assertT}(\text{p2.equals(p3)})$

assertEquals(exp1, exp2)


◦ $\approx \text{exp1.equals(exp2)}$ if exp1 and exp2 are **reference** type

Case 1: If equals is **not** explicitly overridden in exp1's declared type
 $\approx \text{assertSame}(\text{exp1}, \text{exp2})$

PointV1 p1 = new PointV1(3, 4);
PointV1 p2 = new PointV1(3, 4);
PointV2 p3 = new PointV2(3, 4);


assertEquals(p1, p2);

assertEquals(p2, p3);



$p1 == p2$

" $p2 == p3$ "



Case 2: If equals is explicitly **overridden** in exp1's declared type
 $\approx \text{exp1.equals(exp2)}$

*** phase 3

PointV1 p1 = new PointV1(3, 4);
PointV1 p2 = new PointV1(3, 4);
PointV2 p3 = new PointV2(3, 4);

assertEquals(p1, p2);

assertEquals(p2, p3);

assertEquals(p3, p2);

p1.eg. (p2)
p2.eg. (p3)

* p3.eg. (p2)

↳ overridden ver.

↳ rn. false 'c' diff. r.t. **

both
rn.
false
but
for
diff.
reason



Exercise: PersonCollectors are **equal** if their arrays of persons are **equal**

```
class PersonCollector {  
    private Person[] persons;  
    private int nop; /* number of persons */  
    public PersonCollector() { ... }  
    public void addPerson(Person p) { ... }  
    public int getNop() { return this.nop; }  
    public Person[] getPersons() { ... }  
}
```

```
1 public boolean equals(Object obj) {  
2     if(this == obj) { return true; }  
3     if(obj == null || this.getClass() != obj.getClass()) { return false; }  
4     PersonCollector other = (PersonCollector) obj;  
5     boolean equal = false;  
6     if(this.nop == other.nop) {  
7         equal = true;  
8         for(int i = 0; equal && i < this.nop; i++) {  
9             equal = this.persons[i].equals(other.persons[i]);  
10        }  
11    }  
12    return equal;  
13 }
```

Q: At Line 9 of **PersonCollector**'s **equals** method which version of the **equals** method is called?

```
1 public class Person {  
2     private String firstName; private String lastName;  
3     private double weight; private double height;  
4     public boolean equals(Object obj) {  
5         if(this == obj) { return true; }  
6         if(obj == null || this.getClass() != obj.getClass()) { return false; }  
7         Person other = (Person) obj;  
8         return  
9             this.weight == other.weight  
10            && this.height == other.height  
11            && this.firstName.equals(other.firstName)  
12            && this.lastName.equals(other.lastName);  
13     }  
14 }
```



Lecture 16 - Nov 4

Inheritance

Design Principles: Cohesion, SCP

SMS: Design Attempt 1

SMS: Design Attempt 2

Implementing Inheritance in Java

Announcements/Reminders

- Today's class: [notes template](#) posted
- **WrittenTest1** marks and feedback released
- **ProgTest2** this Wednesday (November 5)
 - + **Guide** released
 - + **PracticeTest2** released
 - + **Lab3** solution released
- [Tracing Exercises](#): assertEquals and Person, PersonCollector

Inheritance: Motivating Problem

Nouns -> classes, attributes, accessors

Verbs -> mutators

Problem: A student management system stores data about students. There are two kinds of university students: resident students and non-resident students. Both kinds of students have a name and a list of registered courses. Both kinds of students are restricted to register for no more than 10 courses. When calculating the tuition for a student, a base amount is first determined from the list of courses they are currently registered (each course has an associated fee). For a non-resident student, there is a discount rate applied to the base amount to waive the fee for on-campus accommodation. For a resident student, there is a premium rate applied to the base amount to account for the fee for on-campus accommodation and meals.

Design Principles

1. Cohesion

Unix principle
↳ each command should do one thing, and do it well
↳ col pud

↳ Attributes and methods in a single class should serve the same purpose.
be under a unifying theme

2. Single Change Principle

violation:
duplicates.

↳ A change to the software should impact a minimum number of places

not necessarily 1, but no more than necessary.

methods, classes.

First Design Attempt

how to simulate OO in a non-OO language (P.g. C).

```
public class Student {
    private Course[] courses;
    private int noc;
```

```
    private int kind;
    private double premiumRate;
    private double discountRate;
```

```
    public Student(int kind){
        this.kind = kind;
    }
    ...
}
```

RS. getTuition()
NRS. getTuition()

Student (RS) = new Student(1);
Student (NRS) = new Student(2);

RS →

S.		
K.	1	
P.	1.5	
D.		X

NRS →

S.		
K.	2	
P.		X
D.	0.5	

```
public double getTuition(){
    double tuition = 0;
    for(int i = 0; i < this.noc; i++){
        tuition += this.courses[i].fee;
    }
    if (this.kind == 1) {
        return tuition * this.premiumRate;
    }
    else if (this.kind == 2) {
        return tuition * this.discountRate;
    }
}
```

→ loop amount

```
public void register(Course c){
    int MAX = -1;
    if (this.kind == 1) { MAX = 6; }
    else if (this.kind == 2) { MAX = 4; }
    if (this.noc == MAX) { /* Error */ }
    else {
        this.courses[this.noc] = c;
        this.noc ++;
    }
}
```

First Design Attempt

```
public class Student {  
    private Course[] courses;  
    private int noc;  
  
    private int kind;  
    private double premiumRate;  
    private double discountRate;  
  
    public Student (int kind){  
        this.kind = kind;  
    }  
    ...  
}
```

mutually exclusive?

*↳ should be put
in separate
classes*

Good design?

Judge by Cohesion

```
public double getTuition(){  
    double tuition = 0;  
    for(int i = 0; i < this.noc; i++){  
        tuition += this.courses[i].fee;  
    }  
    if (this.kind == 1) {  
        return tuition * this.premiumRate;  
    }  
    else if (this.kind == 2) {  
        return tuition * this.discountRate;  
    }  
}
```

```
public void register(Course c){  
    int MAX = -1;  
    if (this.kind == 1) { MAX = 6; }  
    else if (this.kind == 2) { MAX = 4; }  
    if (this.noc == MAX) { /* Error */ }  
    else {  
        this.courses[this.noc] = c;  
        this.noc ++;  
    }  
}
```

First Design Attempt

```
public class Student {  
    private Course[] courses;  
    private int noc;  
  
    private int kind;  
    private double premiumRate;  
    private double discountRate;  
  
    public Student (int kind){  
        this.kind = kind;  
    }  
    ...  
}
```

```
public double getTuition(){  
    double tuition = 0;  
    for(int i = 0; i < this.noc; i++){  
        tuition += this.courses[i].fee;  
    }  
    if (this.kind == 1) {  
        return tuition * this.premiumRate;  
    }  
    else if (this.kind == 2) {  
        return tuition * this.discountRate;  
    }  
    else if (kind == 3) { ... }
```

```
public void register(Course c){  
    int MAX = -1;  
    if (this.kind == 1) { MAX = 6; }  
    else if (this.kind == 2) { MAX = 4; }  
    if (this.noc == MAX) { /* Error */ }  
    else {  
        this.courses[this.noc] = c;  
        this.noc ++;  
    }  
}
```

Good design?

Judge by **Single Choice Principle**

- **Repeated** if-conditions
- A new kind is **introduced?**
- An existing kind is **obsolete?**

*kind == 3
↳ informational*

*else if
(kind == 3)
{ ... }*

Testing Student Classes (without inheritance)

```
public class ResidentStudent {
    private String name;
    private Course[] courses; private int noc;
    private double premiumRate; /* assume a m
    public ResidentStudent (String name) {
        this.name = name;
        this.courses = new Course[10];
    }
    public void register(Course c) {
        this.courses[this.noc] = c;
        this.noc ++;
    }
    public double getTuition() {
        double tuition = 0;
        for(int i = 0; i < this.noc; i ++ ) {
            tuition += this.courses[i].fee;
        }
        return tuition * this.premiumRate;
    }
}
```


```
public class NonResidentStudent {
    private String name;
    private Course[] courses; private int noc;
    private double discountRate; /* assume a
    public NonResidentStudent (String name) {
        this.name = name;
        this.courses = new Course[10];
    }
    public void register(Course c) {
        this.courses[this.noc] = c;
        this.noc ++;
    }
    public double getTuition() {
        double tuition = 0;
        for(int i = 0; i < this.noc; i ++ ) {
            tuition += this.courses[i].fee;
        }
        return tuition * this.discountRate;
    }
}
```

cohesion
(pr and dr
put in
different
classes)

SCP
violated
(lots of
duplicates)

```
public class StudentTester {
    public static void main(String[] args) {
        Course c1 = new Course("EECS2030", 500.00); /* title and fee */
        Course c2 = new Course("EECS3311", 500.00); /* title and fee */
        ResidentStudent jim = new ResidentStudent("J. Davis");
        jim.setPremiumRate(1.25);
        jim.register(c1); jim.register(c2);
        NonResidentStudent jeremy = new NonResidentStudent("J. Gibbons");
        jeremy.setDiscountRate(0.75);
        jeremy.register(c1); jeremy.register(c2);
        System.out.println("Jim pays " + jim.getTuition());
        System.out.println("Jeremy pays " + jeremy.getTuition());
    }
}
```

1000×1.25
 1000×0.75



Student Classes (without inheritance): Maintenance (1)

```
public class ResidentStudent {
    private String name;
    private Course[] courses; private int noc;
    private double premiumRate; /* assume a m
    public ResidentStudent (String name) {
        this.name = name;
        this.courses = new Course[10];
    }
    public void register(Course c) {
        this.courses[this.noc] = c;
        this.noc ++;
    }
    public double getTuition() {
        double tuition = 0;
        for(int i = 0; i < this.noc; i ++) {
            tuition += this.courses[i].fee;
        }
        return tuition * this.premiumRate;
    }
}
```

```
public class NonResidentStudent {
    private String name;
    private Course[] courses; private int noc;
    private double discountRate; /* assume a
    public NonResidentStudent (String name) {
        this.name = name;
        this.courses = new Course[10];
    }
    public void register(Course c) {
        this.courses[this.noc] = c;
        this.noc ++;
    }
    public double getTuition() {
        double tuition = 0;
        for(int i = 0; i < this.noc; i ++) {
            tuition += this.courses[i].fee;
        }
        return tuition * this.discountRate;
    }
}
```

every
dupl/corr
has to
be changed!

Maintenance e.g., a new registration constraint:

```
if(numberOfCourses >= MAX_ALLOWANCE) {
    throw new TooManyCoursesException("Too Many Courses");
}
else { ... }
```

how many methods
should be impacted?

Student Classes (without inheritance): Maintenance (2)

```
public class ResidentStudent {
    private String name;
    private Course[] courses; private int noc;
    private double premiumRate; /* assume a m
    public ResidentStudent (String name) {
        this.name = name;
        this.courses = new Course[10];
    }
    public void register(Course c) {
        this.courses[this.noc] = c;
        this.noc ++;
    }
    public double getTuition() {
        double tuition = 0;
        for(int i = 0; i < this.noc; i ++) {
            tuition += this.courses[i].fee;
        }
        return tuition * this.premiumRate;
    }
}
```

```
public class NonResidentStudent {
    private String name;
    private Course[] courses; private int noc;
    private double discountRate; /* assume a
    public NonResidentStudent (String name) {
        this.name = name;
        this.courses = new Course[10];
    }
    public void register(Course c) {
        this.courses[this.noc] = c;
        this.noc ++;
    }
    public double getTuition() {
        double tuition = 0;
        for(int i = 0; i < this.noc; i ++) {
            tuition += this.courses[i].fee;
        }
        return tuition * this.discountRate;
    }
}
```



Maintenance e.g., a new **tuition** formula:

```
/* ... can be premiumRate or discountRate */
...
return tuition * inflationRate * ...;
```

A Collection of Students (**without** inheritance)

```
public class StudentManagementSystem {  
    private ResidentStudent[] rss;  
    private NonResidentStudent[] nrss;  
    private int nors; /* number of resident students */  
    private int nonrs; /* number of non-resident students */  
    public void addRS(ResidentStudent rs) { rss[nors]=rs; nors++; }  
    public void addNRS(NonResidentStudent nrs) { nrss[nonrs]=nrs; nonrs++; }  
    public void registerAll(Course c) {  
        for(int i = 0; i < nors; i++) { rss[i].register(c); }  
        for(int i = 0; i < nonrs; i++) { nrss[i].register(c); }  
    }  
}
```

arrays = # kinds of students



Recall: Student Classes (with inheritance)

```
class Student {  
    String name;  
    Course[] registeredCourses;  
    int numberOfCourses;  
    Student (String name) { *  
        this.name = name;  
        registeredCourses = new Course[10];  
    }  
    void register(Course c) {  
        registeredCourses[numberOfCourses] = c;  
        numberOfCourses ++;  
    }  
    double getTuition() {  
        double tuition = 0;  
        for(int i = 0; i < numberOfCourses; i ++){  
            tuition += registeredCourses[i].fee;  
        }  
        return tuition; /* base amount only */  
    }  
}
```

child/sub-class extends parent/super class
RS NRS
Student.

super vs. this
parent class current class/object
base amt. calculation
child/sub class specific attributes
↳ cohesion RS sat.


```
class ResidentStudent extends Student {  
    double premiumRate; /* there's a mutator method  
    ResidentStudent (String name) { super (name); }  
    /* register method is inherited */  
    double getTuition() { RS overridden version  
        double base = super.getTuition();  
        return base * premiumRate;  
    }  
}
```

```
class NonResidentStudent extends Student {  
    double discountRate; /* there's a mutator method  
    NonResidentStudent (String name) { super (name); }  
    /* register method is inherited */  
    double getTuition() { NRS overridden version  
        double base = super.getTuition();  
        return base * discountRate;  
    }  
}
```

Common super/parent class
call non-private attributes/methods are inherited to child/sub classes
↳ sat. SCP.

* Student
reusing the parent version of the method.

When programming with inheritance (oop):



Lecture 17 - Nov 6

Inheritance

Modifiers in Java


Static Types and Expectations

Polymorphism, Dynamic Binding

Announcements/Reminders

- Today's class: notes template posted
- Lab4 ~~solution~~ released
- Tracing Exercises: assertEquals and Person, PersonCollector



(Scenario)



→ super.m()

version of closest ancestor

(Scenario 1)



m*



super.m()

version for P.

m*



super.m()



version from C

→ super.super.m() X


Visualizing Parent and Child Objects

dynamic
types

```
Student s = new Student("Stella");  
ResidentStudent rs = new ResidentStudent("Rachael");  
NonResidentStudent nrs = new NonResidentStudent("Nancy");
```



Testing Student Classes (with inheritance)




```

public class StudentTester {
    public static void main(String[] args) {
        Course c1 = new Course("EECS2030", 500.00); /* title and fee */
        Course c2 = new Course("EECS3311", 500.00); /* title and fee */
        ResidentStudent jim = new ResidentStudent("J. Davis");
        jim.setPremiumRate(1.25);
        jim.register(c1); jim.register(c2);
        NonResidentStudent jeremy = new NonResidentStudent("J. Gibbons");
        jeremy.setDiscountRate(0.75);
        jeremy.register(c1); jeremy.register(c2);
        System.out.println("Jim pays " + jim.getTuition());
        System.out.println("Jeremy pays " + jeremy.getTuition());
    }
}
  
```

Handwritten notes:

- Orange arrows pointing to `ResidentStudent` and `NonResidentStudent` in the code: **D.T.: RS** (D.T. = Discount/Tuition, RS = Resident Student)
- Orange arrows pointing to `setPremiumRate` and `setDiscountRate`: **varian from RS (pr)**
- Pink arrows pointing to `getTuition()` calls: **D.T.: NRS** (NRS = Non-Resident Student)
- Pink arrows pointing to `getTuition()` calls: **varian from NRS (dr)**



Modifiers in Java

visibility

① private

② no modifier

③ protected

④ public


attributes/
methods.

inheritance
(e.g. Lab4)

classes.


Visibility: Classes

CollectionOfStuffs




no modifier
↳ visible within the residing package

CollectionOfStuffs



Visibility: Attributes and Methods

CollectionOfStuffs



```


public class Chair {
    private int w;
    int x;
    protected int y;
    public int z;
}
  
```

1. package level
2. subclasses
(not in the same package)

	CLASS	PACKAGE	SUBCLASS (same pkg)	SUBCLASS (different pkg)	NON-SUBCLASS (across Project)
public	Green	Green	Green	Green	Green
protected	Green	Green	Green	Green	Red
no modifier	Green	Green	Green	Red	Red
private	Green	Red	Red	Red	Red

Student Classes (with inheritance): Expectations

- determined by static types

 $\exp(\text{Student})$

```
Student s = new Student("Stella");
ResidentStudent rs = new ResidentStudent("Rachael");
NonResidentStudent nrs = new NonResidentStudent("Nancy");
```

additional
exp.
for
child
classes


[illegible]

Handwritten notes on a grid background:

- 57. S S.
- 57. RS (rs.)
- 57. nrs.
- NRJ.

Intuition: Polymorphism

4. assumption is wrong
! $rs = s$ should not compile.




```
1 Student s = new Student("Stella");
2 ResidentStudent rs = new ResidentStudent("Rachael");
3 rs.setPremiumRate(1.25);
4 s ✓ rs; /* Is this valid? */
5 rs ✗ s; /* Is this valid? */
```


1. Assume $rs = s$ compiles.

2. Execute the var assignment.

3. Exp of rs ' ST (RS) includes: pr
 $rs.pr \rightarrow$ crash ! Student has no pr.




Intuition: Dynamic Binding



var s

step	ST	DT
①		null
②		RS
③	Student	RS
④		NRS



Compilation: static type


runtime: dynamic type

e.g. version
of method
called

e.g. exception

↓ `ClassNotFoundException`.


Multi-Level Inheritance Hierarchy: Students



Reflections:

- For **Design 1**, how many encodings to check for each method?
 - For **Design 2**, how many arrays to store for SMS?
 - For **Design 3**, where are common attributes/methods stored?
- kind var?*
how many classes
extends?

Multi-Level Inheritance Hierarchy: Smartphones



Reflections:

- For Design 1, how many encodings to check for each method?
- For Design 2, how many arrays to store for SMS?
- For Design 3, where are common attributes/methods stored?

Lecture 18 - Nov 11

Inheritance

***Ancestors, Descendants, Expectations
Rules of Substitutions***


WSC/OS -

Announcements/Reminders

- Today's class: notes template posted
- **Lab4** released
- Tracing Exercises: assertEquals and Person, PersonCollector

Multi-Level Inheritance Hierarchy: Smartphones

expectations
 SS
 callable
 method.




Exercise Compare the ranges of expectations of:

- + iPhone13Pro
- + HuaweiP50Pro
- + GalaxyS21Plus


RT, facetime, surfWeb, dial
 zoomage, skype, surfWeb, dial
 sideSync, skype, surfWeb, dial

Common exp
 inherited
 from
 SmartPhone

Inheritance Forms a Type Hierarchy



z indirectly extends y.



ancestors of A

(1) A accumulates all atts/mths. from its ancestors
expectation


(2) $\exp(A) \geq \exp$ of any ancestor class




descendants of A

(1) $\exp(A)$ inherited to all of A's descendants.


(2) $\exp(A) \leq \exp$ of any descendant class.

Inheritance Accumulates Code for Reuse



	ancestors	expectations	descendants
	GS21 → S. → A. → SP	 Exercise	GS21
			
	SP		all classes

Assumption: there's some inheritance hierarchy existing



Rule of substitutions (inheritance).

$\checkmark$ $\boxed{T_2 \text{ must be a descendant of } T_1}$

$\downarrow$ $\text{exp}(T_2) \geq \text{exp}(T_1)$

Rules of Substitutions

does a var. assignment compile? (static types; inheritance) * Oa's to f

Inherent (P)

- * OA's expectations must be fulfilled by the ST of ob.

$$\exp(?) \geq \exp(A)$$

↳ ? must be a descendant of A.

→ descendants of A
 $\exp \supset \exp(A)$.

(A) ancestors of A's parent

(b) neither ancestor nor descendant

```

graph TD
    A((A)) -- "ST of oa" --> B((?))
    B -- "ST of ob" --> A
    B -- "*" --> C((*))
    style A fill:#ffff00,stroke:#000,stroke-width:2px
    style B fill:#90ee90,stroke:#000,stroke-width:2px
    style C fill:#ffff00,stroke:#000,stroke-width:2px
  
```

Diagram illustrating a control flow graph (CFG) for a program snippet. The code is:

```

oa = ...;
? ob = ...;
oa * = ob;

```

The nodes are:

- Node 1 (A): `oa = ...;`
- Node 2 (?): `ob = ...;`
- Node 3 (*): `oa * = ob;`

Edges and labels:

- Edge from Node 1 to Node 2: `ST of oa` (blue arrow)
- Edge from Node 2 to Node 1: `ST of ob` (red arrow)
- Edge from Node 2 to Node 3: `*` (pink arrow)

SL: A.

04 X

06 —

0a = 0b,


what can ? (SI of ob)

be in order for


this var. assignment (substitution)

to compile?

- substitute oa by ob
- after the substitution we expect: $*oa$.



Rules of Substitutions (1)



Declarations:

IOS sp1;

iPhoneSE sp2;


iPhone13Pro sp3;

Substitutions:

sp1 = sp2;

sp1 = sp3;

Rules of Substitutions (2)



Declarations:

IOS sp1;

SmartPhone sp2;

Substitutions:

sp1 = sp2;

fail to compile
-! SP is not a descendant of IOS

Visualization: **Static** Type vs. **Dynamic** Type

Declaration:

Student s;

Substitution:



s = **new ResidentStudent**("Rachael");

Compiles 's' is a des. of the ST of (Student)


Static Type: Expectation

Dynamic Type: Accumulation of Code

(2) RS can fulfill the exp. of s' ST (Student)



Change of Dynamic Type (1.1)




Example 1:

```
Student jim = new ResidentStudent(...);  
jim = new NonResidentStudent(...);
```

Compile: RS and NRS
are descendants of
jim's ST (Student).

Change of Dynamic Type (1.2)




Example 2:

ResidentStudent jeremy = **new Student**(...);

fail to compile
∴ Student cannot fulfil
exp of jeremy's ST
(RS).


Change of **Dynamic** Type: Exercise (1)



Exercise 1:

```
Android myPhone = new HuaweiP50Pro(...);  
myPhone = new GalaxyS21(...);
```


Change of Dynamic Type: Exercise (2)



Exercise 2:

```
IOS myPhone = new HuaweiP50Pro(...);  
myPhone = new GalaxyS21(...);
```


Change of **Dynamic** Type (2.1)




Given:


① **Student** jim = **new Student**(...); *DT of jim: Student*
② **ResidentStudent** rs = **new ResidentStudent**(...);
③ **NonResidentStudent** nrs = **new NonResidentStudent**(...);

Example 1:

④ jim = rs; *DT of jim: changed to DT. of rs (Resident Student)*
println(jim.getTuition());
⑤ jim = nrs; *DT of jim: changed to DT. of nrs (NonR.S.)*
println(jim.getTuition());



Change of **Dynamic** Type (2.2)



Given:

```
Student jim = new Student(...);  
ResidentStudent rs = new ResidentStudent(...);  
NonResidentStudent nrs = new NonResidentStudent(...);
```

Example 2:

```
rs = jim,  
println(rs.getTuition()),  
nrs = jim,  
println(nrs.getTuition());
```

not compile
∵ Student (jim's ST)
not descendant of LHS

Lecture 19 - Nov 13

Inheritance

***Type Casts: Motivation, Syntax, Visual
Compilable Casts: Upward vs. Downward
Casts at Runtime: ClassCastException***

Announcements/Reminders

- Today's class: [notes template](#) posted
- **Lab4** released
- **WrittenTest2** guide and **example questions** released
- Notes on Type Casting

^{many} Polymorphism and Dynamic Binding

$$\frac{T_1}{ST} \checkmark_{cr} = \frac{\text{new } T_2()}{DT};$$

T₂ must fulfill the exp(T₁)

Polymorphism:


An object's **static type** may allow multiple possible **dynamic types**.

⇒ Each **dynamic type** has its version of method.

Dynamic Binding:


An object's **dynamic type** determines the version of method being invoked.

```
Student jim = new ResidentStudent(...);
jim.getTuition();
jim = new NonResidentStudent(...);
jim.getTuition();
```




```
SmartPhone sp1 = new iPhone13Pro(...);
SmartPhone sp2 = new GalaxyS21(...);
sp1.surfWeb();
sp1 = sp2;
sp1.surfWeb();
```

after this substitution, DT of sp1 changes to DT of sp2.




Type Cast: Motivation




```
1 Student jim = new ResidentStudent("J. Davis");  
2 ResidentStudent rs X jim;  
3 rs.setPremiumRate(1.5);
```

ST: Student → not compatible: Student (jim's ST)

rs not descendant of RS.



An **A+** Challenge: Inferring the **DT** of a Variable



```
class MyClass {  
  main (...)  
    Student s = ...;  
    ...  
    s = new ResidentStudent(...);  
  }  
}
```

last DT of s

undecidable problem
(writing a program
to infer the dynamic
behaviour of
another arbitrary
program)

Anatomy of a Type Cast

Student jim = **new ResidentStudent**("Jim");



ST: *ResidentStudent*


✓
Student jim

ResidentStudent	
pr	

jim. setPr X
rs. setPr. ✓

ResidentStudent rs
(RS) jim
ST: *ResidentStudent*

Type Cast: Named vs. Anonymous



Named Cast: Use intermediate variable to store the cast result.

```

SmartPhone aPhone = new iPhone13Pro();
IOS forHeeyeon = (iPhone13Pro) aPhone;
forHeeyeon.facetime();
    
```

Anonymous Cast: Use the cast result directly.

```

SmartPhone aPhone = new iPhone13Pro();
((iPhone13Pro) aPhone).facetime();
    
```

→ using type cast exp as the C.O.

Exercise

```

SmartPhone aPhone = new iPhone13Pro();
(IPhone13Pro) aPhone.facetime();
    
```

→ As if: (IP13P) (aPhone.facetime())
 ↳ ST: SP

static type consideration only

Compilable Casts: Upwards vs. Downwards


Expectations

	sp	myPhone	ga
dial			
surfWeb			
skype			
sideSync			
facetime			
quickTake			
zoomage			

Android myPhone = ~~new GalaxyS21Plus()~~;

SmartPhone sp = (SmartPhone) myPhone;

GalaxyS21Plus ga = (GalaxyS21Plus) myPhone;




Compilable Type Cast May **Fail** at Runtime (1)

trigger:
ClassCastException
(CCE)

① When the DT cannot fulfill the exp. of cast type.
e.g. RS

② when the DT is not a descendant of cast type.




```

1 Student jim = new NonResidentStudent("J. Davis");
2 ResidentStudent rs = (ResidentStudent) jim;
3 rs.setPremiumRate(1.5);
  
```

downward cast


exp ✓
(RS)
↓
pr.
ST
Student
[RS]

Jim
rs
(RS)
Jim




Issue: DT NRS cannot fulfill the exp (RS)

Compilable Type Cast May **Fail** at Runtime (2)



```
1 SmartPhone aPhone = new GalaxyS21Plus();
2 iPhone13Pro forHeeyeon = (iPhone13Pro) aPhone;
3 forHeeyeon.quickTake();
```


Exercise: Compilable Type Cast? **Fail** at Runtime? (1)



```
SmartPhone myPhone = new Samsung();  
/* ST of myPhone is SmartPhone; DT of myPhone is Samsung */  
GalaxyS21Plus ga = (GalaxyS21Plus) myPhone;
```

Compilable? **ClassCastException** at runtime?


Exercise: Compilable Type Cast? Fail at Runtime? (2)



```
SmartPhone myPhone = new Samsung();  
/* ST of myPhone is SmartPhone; DT of myPhone is Samsung */  
iPhone13Pro ip = (iPhone13Pro) myPhone;
```

Compilable? ClassCastException at runtime?

Compilable Cast vs. Exception-Free Cast



Android myPhone = new **Samsung**();

Compilable Casts

Exception-Free Casts

Non-Compilable Casts



ClassCastException

Exercise: Compilable Cast vs. Exception-Free Cast

```
class A { }  
class B extends A { }  
class C extends B { }  
class D extends A { }
```


```
1 B b = new C();  
2 D d = (D) b;
```

x compile
cast type D is
neither ancestor nor descendant
of b's ST(B)



Vaccine $v = \dots$

Channel $c = \underline{(\text{Channel})(\underline{(\text{Object } v)})}$



Lecture 20 - Nov 18

Inheritance

instanceof vs. Compileable Cast
instanceof vs. ClassCastException Freedom
Call by Value and Inheritance

Announcements/Reminders

- Today's class: notes template posted
- **Lab4** due soon
- **WrittenTest2** **guide** and **example questions**
 - + In-person review session: 3 PM on Tuesday @ R N203
 - + Notes on Type Casting
- Online Course Evaluation

x

instance of

Y

can fulfill, dynamically, exp. of

D.T.

an expression denoting some object
e.g., x , $A[i]$

Compiles iff
 $(Y) x$ compiles
upward or downward cast.

a class name.

usually used
never pattern for
a subsequent cast.

no CCE!!

$x \rightsquigarrow$ $x \text{ is } D.T.$

$\hookrightarrow$ evaluates to Boolean (True or False)

$\hookrightarrow$ True iff (1) D.T. of x can fulfill exp. of

(2) D.T. of x is descendant of Y

(3) Y is ancestor of D.T. of x


false otherwise

$\hookrightarrow$ if true, then it's safe to execute $(Y) x$

Assume:
both exp. compile

	DT of x fullfill $\text{exp}(y)$	$\neg$ (DT of x fullfill $\text{exp}(y)$)
x instance of Y	true	false.
$(\underline{Y}) \quad x$	type cast succeeds, creating an alias of Y	CCE!

x Compiles in
(??) obj Compiles




- L1 compiles if **B** can fulfill expectations of **A**.

- Compiles if Up or Down cast w.r.t. **A**.
- ClassCastException if **B** cannot fulfill expectations on **??**.

- Evaluates to true if B can fulfill expectations on ??.

Checking Dynamic Types at Runtime (1)




```
1 Student jim = new NonResidentStudent("J. Davis");
2 if (jim instanceof ResidentStudent) {
3     ResidentStudent rs = (ResidentStudent) jim;
4     rs.setPremiumRate(1.5);
5 }
```

1. compile? downward cast
2. CCE!
∵ DT NRS not descendant of cast type RS.

.....bypassed, preventing CCE from happening!!
can jim's DT fulfill the exp(RS)
↳ NO → false

Checking Dynamic Types at Runtime (2)


ExercisP




```
1 SmartPhone aPhone = new GalaxyS21Plus();
2 if (aPhone instanceof IPhone13Pro) {
3     IOS forHeeyeon = (IPhone13Pro) aPhone;
4     forHeeyeon.facetime();
5 }
```


$x.getClass() == Y$
DT of x

x instance of Y
DT of x




Use of the instanceof Operator



```
SmartPhone myPhone = new Samsung();
println(myPhone instanceof Android); (T)
println(myPhone instanceof Samsung); (T)
println(myPhone instanceof GalaxyS21); (F)
println(myPhone instanceof IOS); (F)
println(myPhone instanceof iPhone13Pro); (F)
```

myPhone instanceof ??
evaluates to true if
Samsung can
fulfill expectations on ??.

Safe Cast via Use of the instanceof Operator



```
1 SmartPhone myPhone = new Samsung();
2 /* ST of myPhone is SmartPhone: DT of myPhone is Samsung */
3 if(myPhone instanceof Samsung) {
4     Samsung samsung = (Samsung) myPhone;
5 }
6 if(myPhone instanceof GalaxyS21Plus) {
7     XGalaxyS21Plus galaxy = (GalaxyS21Plus) myPhone;
8 }
9 if(myPhone instanceof HuaweiMate40Pro) {
10    XHuawei hw = (HuaweiMate40Pro) myPhone;
11 }
```


no CCE

bypassed

CCE prevented!

myPhone instanceof ??
evaluates to true if
Samsung can
fulfill expectations on ??.


Static Types, Casts, Polymorphism (1)



```
class SmartPhone {
    void dial() { ... }
}
class IOS extends SmartPhone {
    void facetime() { ... }
}
class iPhone13Pro extends IOS {
    void quickTake() { ... }
}
```

```
1 SmartPhone sp = new iPhone13Pro();
2 sp.dial(); ✓
3 sp.facetime(); ✗
4 sp.quickTake(); ✗
```


Static Types, Casts, Polymorphism (2)



```
class SmartPhone {
    void dial() { ... }
}
class IOS extends SmartPhone {
    void facetime() { ... }
}
class iPhone13Pro extends IOS {
    void quickTake() { ... }
}
```

```
1 IOS ip = new iPhone13Pro();
2 ip.dial(); ✓
3 ip.facetime(); ✓
4 ip.quickTake(); ✗
```


Static Types, Casts, Polymorphism (3)



```
class SmartPhone {  
    void dial() { ... }  
}  
class IOS extends SmartPhone {  
    void facetime() { ... }  
}  
class iPhone13Pro extends IOS {  
    void quickTake() { ... }  
}
```

```
1 iPhone13Pro ip6sp = new iPhone13Pro();  
2 ip6sp.dial();  
3 ip6sp.facetime();  
4 ip6sp.quickTake();
```

Static Types, Casts, Polymorphism (4)




```
class SmartPhone {  
    void dial() { ... }  
}  
class IOS extends SmartPhone {  
    void facetime() { ... }  
}  
class iPhone13Pro extends IOS {  
    void quickTake() { ... }  
}
```


```
1 SmartPhone sp = new iPhone13Pro();  
2 ((iPhone13Pro) sp).dial();  
3 ((iPhone13Pro) sp).facetime();  
4 ((iPhone13Pro) sp).quickTake();
```

last compiler
(exp has ST: IP13Pro)

Static Types, Casts, Polymorphism (5)



Student s



```
Course eecs2030 = new Course("EECS2030", 500.0);
Student s = new ResidentStudent("Jim");
s.register(eecs2030);
if (s instanceof ResidentStudent) {
    ((ResidentStudent) s).setPremiumRate(1.75);
    System.out.println(((ResidentStudent) s).getTuition());
}
```


Call by Value

Callee

```
class C {  
    void m(T1 param) {  
        ...  
    }  
}
```

call by value: $\text{param} = \text{arg}$
 $\text{ST} = \text{T}_1$ $\text{ST} = \text{T}_2$

Caller


```
C obj = new C();  
T2 arg = ...;  
obj.m(arg);
```

* Rule of substitutions

- (1) T_2 fulfills $\text{exp}(\text{T}_1)$
- (2) T_2 descendant of T_1

Polymorphic Parameters (1)

each element of array has ST Student.



```
1 class StudentManagementSystem {
2     Student[] ss; /* ss[i] has static type Student */ int c;
3     void addRS(ResidentStudent rs) { ss[c] = rs; c++; }
4     void addNRS(NonResidentStudent nrs) { ss[c] = nrs; c++; }
5     void addStudent(Student s) { ss[c] = s; c++; } }
```

Q. Static type of ss[0], ss[1], ..., ss[ss.length - 1]?

call by value: rs = 0
ST: RS ST: ? ST: Student

Q. In method addRS, does ss[c] = rs compile? ✓

ST: RS ST: ? ST: Student ST: RS

Q. Under what circumstances can the following method call be valid/compilable?

Student s1, s2;
sms.addRS(o)

under what condition does this method call compile?

Polymorphic Parameters (2)

call to this method only compiles if the ST of avg. is descendant of ST of param (CRS)

```
1 class StudentManagementSystem {
2     Student [] ss; /* ss[i] has static type Student */ int c;
3     void addRS(ResidentStudent rs) { ss[c] = rs; c++; }
4     void addNRS(NonResidentStudent nrs) { ss[c] = nrs; c++; }
5     void addStudent(Student s) { ss[c] = s; c++; } }
```

```
Student s1 = new Student();
Student s2 = new ResidentStudent();
Student s3 = new NonResidentStudent();
ResidentStudent rs = new ResidentStudent();
NonResidentStudent nrs = new NonResidentStudent();
StudentManagementSystem sms = new StudentManagementSystem();
```

avg with ST a descendant of Student compiles

call by value: $rs = s1$


ST: RS $\rightarrow$ ST: S

$rs = rs \rightarrow$ ST: RS

C.L.V: $rs = nrs$ X

```
1 sms.addRS(s1); X
2 sms.addRS(s2); X
3 sms.addRS(s3); X
4 sms.addRS(rs); ✓
5 sms.addRS(nrs); X

sms.addStudent(s1) ✓
sms.addStudent(s2) ✓
sms.addStudent(s3) ✓
sms.addStudent(rs) ✓
sms.addStudent(nrs) ✓
```



Lecture 21 - Nov 20

Inheritance

Casting Method Arguments
Polymorphic Arrays and Return Types
Recursion: Resources

Announcements/Reminders

- Today's class: [notes template](#) posted
- **Lab4** solution released
- **ProgTest3** **guide** and **example questions** released
- Online Course Evaluation

Casting Arguments

1.b.v. RS = CR(S) S

void addRS(ResidentStudent rs)

fixed sms.addRS(**(ResidentStudent) s**) compiles?

fixed

```
1 Student s = new Student("Stella");
2 /* s' ST: Student; s' DT: Student */
3 StudentManagementSystem sms = new StudentManagementSystem();
4 sms.addRS(s);
```

1.b.v. RS = S

fixed

```
1 Student s = new NonResidentStudent("Nancy");
2 /* s' ST: Student; s' DT: NonResidentStudent */
3 StudentManagementSystem sms = new StudentManagementSystem();
4 sms.addRS(s);
```


fixed

```
1 Student s = new ResidentStudent("Rachael");
2 /* s' ST: Student; s' DT: ResidentStudent */
3 StudentManagementSystem sms = new StudentManagementSystem();
4 sms.addRS(s);
```

void addRS(ResidentStudent nrs) compiles?

```
1 NonResidentStudent nrs = new NonResidentStudent();
2 /* ST: NonResidentStudent; DT: NonResidentStudent */
3 StudentManagementSystem sms = new StudentManagementSystem();
4 sms.addRS(nrs);
```

if (nrs instanceof RS) { ... }



* cast completes ∴ downward
 * cast exp. has ST: RS
 ClassCastException?

YES!

∴ DT Student not depending

ClassCastException?

YES!!

∴ DT NRS cannot fulfill exp(RS)

ClassCastException?

No.


CCE loop

fail to compile
 - (RS) nrs
 fails to compile

neither upward
 nor downward
 cast → compile X

ST of elements: Student. DTs of elements: descendants of ST.

A Polymorphic Collection of Students



```

1 ResidentStudent rs = new ResidentStudent("Rachael");
2 rs.setPremiumRate(1.5);
3 NonResidentStudent nrs = new NonResidentStudent("Nancy");
4 nrs.setDiscountRate(0.5);
5 StudentManagementSystem sms = new StudentManagementSystem();
6 sms.addStudent(rs); /* polymorphism */
7 sms.addStudent(nrs); /* polymorphism */
8 Course eeecs2030 = new Course("EECS2030", 500.0);
9 sms.registerAll(eeecs2030);
10 for(int i = 0; i < sms.numberOfStudents; i++) {
11     /* Dynamic Binding:
12      * Right version of getTuition will be called */
13     System.out.println(sms.students[i].getTuition());
14 }
  
```

ST
0
1
RS
NRS

```

class StudentManagementSystem {
    Student[] students;
    int numofStudents;

    void addStudent(Student s) {
        students[numofStudents] = s;
        numofStudents++;
    }

    void registerAll(Course c) {
        for(int i = 0; i < numofStudents; i++) {
            students[i].register(c);
        }
    }
}
  
```


elements have same ST: Student.

any arg. with ST a descendant of Student can be passed.

ST: Student. part of exp.

ST of s[i]

0 RS
1 NRS



Polymorphic Return Types

→ ST of return value

↳ DTs of return values are descendants of Student.

```
Course eecs2030 = new Course("EECS2030", 500);
ResidentStudent rs = new ResidentStudent("Rachael");
rs.setPremiumRate(1.5); rs.register(eecs2030);
NonResidentStudent nrs = new NonResidentStudent("Nancy");
nrs.setDiscountRate(0.5); nrs.register(eecs2030);
StudentManagementSystem sms = new StudentManagementSystem();
sms.addStudent(rs); sms.addStudent(nrs);
```

```
Student s = sms.getStudent(0); /* dynamic type of s? */
```

DT: RS ST: Student

```
static return type: Student
print(s instanceof Student && s instanceof ResidentStudent); /* true */
print(s instanceof NonResidentStudent); /* false */
print(s.getTuition()); /* Version in ResidentStudent called: 750 */
```

```
ResidentStudent rs2 = sms.getStudent(0);
s = sms.getStudent(1); /* dynamic type of s? */
```

DT: NRS ST: Student


```
static return type: Student
print(s instanceof Student && s instanceof NonResidentStudent); /* true */
print(s instanceof ResidentStudent); /* false */
print(s.getTuition()); /* Version in NonResidentStudent called: 250 */
```

```
NonResidentStudent nrs2 = sms.getStudent(1);
```

```
class StudentManagementSystem {
    Student[] ss; int c;
    void addStudent(Student s) { ss[c] = s; c++; }
    Student getStudent(int i) {
        Student s = null;
        if (i < 0 || i >= c) {
            throw new IllegalArgumentException("Invalid");
        }
        else {
            s = ss[i];
        }
        return s;
    }
}
```

polymorphic array.

DT: RS
NRS



Summary: Type Checking Rules

CODE	CONDITION TO BE TYPE CORRECT
 <code>x = y</code>	Is <u>y's ST</u> a <u>descendant</u> of <u>x's ST</u> ?
<code>x.m(y)</code>	Is method <code>m</code> defined in <code>x's ST</code> ? Is <code>y's ST</code> a descendant of <code>m's parameter's ST</code> ?
<code>z = x.m(y)</code>	Is method <code>m</code> defined in <code>x's ST</code> ? Is <code>y's ST</code> a descendant of <code>m's parameter's ST</code> ? Is <code>ST</code> of <code>m's return value</code> a descendant of <code>z's ST</code> ?
<code>(C) y</code>	Is <code>C</code> an ancestor or a descendant of <code>y's ST</code> ?
<code>x = (C) y</code>	Is <code>C</code> an ancestor or a descendant of <code>y's ST</code> ? Is <code>C</code> a descendant of <code>x's ST</code> ?
<code>x.m((C) y)</code>	Is <code>C</code> an ancestor or a descendant of <code>y's ST</code> ? Is method <code>m</code> defined in <code>x's ST</code> ? Is <code>C</code> a descendant of <code>m's parameter's ST</code> ?

Overridden Methods and Dynamic Binding (1)

Object

```
boolean equals (Object obj) {  
    return this == obj;  
}
```

A

B

C


```
class A {  
    /*equals not overridden*/  
}  
class B extends A {  
    /*equals not overridden*/  
}  
class C extends B {  
    /*equals not overridden*/  
}
```

```
1 Object c1 = new C();  
2 Object c2 = new C();  
3 println(c1.equals(c2));
```

L3 calls which version of equals?

Object.

Overridden Methods and Dynamic Binding (2)




```
class A {  
    /*equals not overridden*/  
}  
class B extends A {  
    /*equals not overridden*/  
}  
class C extends B {  
    boolean equals (Object obj) {  
        /* overridden version */  
    }  
}
```

```
1 Object c1 = new C();  
2 Object c2 = new C();  
3 println(c1.equals(c2));
```

L3 calls which version of equals?

C

Overridden Methods and Dynamic Binding (3)



```
class A {  
    /*equals not overridden*/  
}  
class B extends A {  
    boolean equals (Object obj) {  
        /* overridden version */  
    }  
}  
class C extends B {  
    /*equals not overridden*/  
}
```

```
1 Object c1 = new C();  
2 Object c2 = new C();  
3 println c1.equals(c2);
```

L3 calls which version of equals?

B

Lecture 22 - Nov 25

Recursion

Recursion: Base vs. Recursive Cases
Tracing Recursion: Stack vs. Tree
Examples: fac, fib, isPalindrome

Announcements/Reminders

- Today's class: [notes template](#) posted
- **ProgTest2** results and feedback released
- **Lab5** released (deadline: Dec 2; **grace period** until Dec 9)
 - + Required background study: **abstract classes** & **interfaces**


* In Java, make recursive call(s), assume correct results returned.

Solving a Problem Recursively


Computed & returned right away.

base case(s)

Given a **small** problem:



Solve it **directly**:




Given a **big** problem:



divide

Divide it into **smaller** problems:



*

Assume solutions to **smaller** problems:



Combine solutions to **smaller** problems:




(direct recursion)
calls
itself

```
m(i) {  
    if(i == ...) { /* base case: do something directly */ }  
    else {  
        m(j) /* recursive call with strictly smaller value */  
    }  
}
```

j < i
A recursive call

Tracing **Recursion** via a **Stack**

- When a method is called, it is **activated** (and becomes **active**) and **pushed** onto the stack.
- When the body of a method makes a (helper) method call, that (helper) method is **activated** (and becomes **active**) and **pushed** onto the stack.
 - ⇒ The stack contains activation records of all **active** methods.
 - **Top** of stack denotes the current point of execution.
 - Remaining parts of stack are (temporarily) **suspended**.
- When entire body of a method is executed, stack is **popped**.
 - ⇒ The current point of execution is returned to the new **top** of stack (which was **suspended** and just became **active**).
- Execution terminates when the stack becomes **empty**.



$$4! = 4 * 3 * 2 * 1 = 24.$$

Recursive Solution: factorial

$$n! = \begin{cases} 1 & \text{if } n = 0 \\ n \cdot (n-1) \cdot (n-2) \cdot \dots \cdot 3 \cdot 2 \cdot 1 & \text{if } n \geq 1 \end{cases}$$

not a recursive def.

the function being defined (i.e., "!") is not recursive/called.

Recursive Def.

$$n! = \begin{cases} 1 \\ n * (n-1)! \end{cases}$$

$$\text{if } n = 0$$

$$\text{if } n \geq 1$$

to define $n!$, we use the def. of $(n-1)!$

base case

strictly smaller input.

recursive case

recursive call.

Recursive Solution in Java: factorial



$$n! = \begin{cases} 1 & \text{if } n = 0 \\ n \cdot (n-1)! & \text{if } n \geq 1 \end{cases}$$

```
int factorial (int n) {  
    int result;  
    if (n == 0) { /* base case */ result = 1; }  
    else { /* recursive case */  
        result = n * factorial (n - 1);  
    }  
    return result;  
}
```

Handwritten annotations for the code:

- Colorful arrows pointing to the function signature and parameters.
- Handwritten numbers 1, 2, 3, 1, 0 next to the base case.
- Handwritten numbers 2, 1, 0 next to the recursive call.
- Handwritten numbers 2, 1, 0 next to the return statement.

Example: factorial(3)



Runtime Stack

Tracing Recursive Methods

(1) Using a call stack

Pro: simulates how computer works at runtime

Con: for complicated tasks, using stacks can make it hard to gain intuition about the correctness of recu. method.


(2) Using a recursion tree

con
pro.

Common **Errors** of Recursion (1)

```
int factorial(int n) {  
→ return n * factorial(n - 1);  
}
```

missing
base case




infinite recursion.
Stack Overflow Exception.

Common Errors of Recursion (2)

```
int factorial(int n) {  
    if(n == 0) { /* base case */ return 1; }  
→ else { /* recursive case */ return n * factorial(n); }  
}
```

↙
recursive
call not
on strictly
smaller
input.





infinite
recursion.

Recursive Solution: Fibonacci Numbers

1 2 3 4 5 6 7 8 9 10 11

$F = 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89, \dots$

F_1 F_2



base cases.

Recursive Solution in Java: Fibonacci Numbers

$$F_n = \begin{cases} 1 & \text{if } n = 1 \\ 1 & \text{if } n = 2 \\ F_{n-1} + F_{n-2} & \text{if } n > 2 \end{cases}$$

```
int fib(int n) {  
    int result;  
    if(n == 1) { /* base case */ result = 1; }  
    else if(n == 2) { /* base case */ result = 1; }  
    else { /* recursive case */  
        result = fib(n - 1) + fib(n - 2);  
    }  
    return result;  
}
```

Example: fib(4)

Runtime Stack

Use of String

`isEmpty(" ")` → false $S \rightsquigarrow$

0	1	2	3
a	b	c	d

```
public class StringTester {  
    public static void main(String[] args) {  
        String s = "abcd";  
        System.out.println(s.isEmpty()); /* false */  
        /* Characters in index range [0, 0) */  
        String t0 = s.substring(0, 0); → [0, -1] size:  
        System.out.println(t0); /* "" */          (-1) - 0 + 1  
        /* Characters in index range [0, 4) */          = 0  
        String t1 = s.substring(0, 4); 0-3  
        System.out.println(t1); /* "abcd" */  
        /* Characters in index range [1, 3) */  
        String t2 = s.substring(1, 3); 1-2  
        System.out.println(t2); /* "bc" */ 2, 3  
        String t3 = s.substring(0, 2) + s.substring(2, 4);  
        System.out.println(s.equals(t3)); /* true */  
        for(int i = 0; i < s.length(); i++) {  
            System.out.print(s.charAt(i));  
        }  
        System.out.println();  
    }  
}
```

subs. (3, 2) → empty
or
IOBE ← exception

assumption: $i \leq j$

`S.substring(i, j)`

↪
return a string
including characters
from index: i to
 $j-1$

$S \rightarrow$

String
val → 1

$[1, 3] \rightarrow \underline{1, 2, 3}$ size: 3

$[1, 3) \rightarrow 1, 2$

$[0, 10] \rightarrow \text{size } 11$

substring(i, j)

$\hookrightarrow [i, j)$

$[i, j-1]$

Assumption: $a \leq b$

$[a, b]$

size: $b - a + 1$

Recursions on Strings

not a
palindrome.

already
diff →
false.

Palindrome

"racecar"

"aracecars"

"racecar"

1st & last
chars same

there's a change
the substring,
minus 1st & last
chars, is a
Palindrome.

Reversal

"abcd"

Number of Occurrences

"abca"

'a'

'b'

Lecture 23 - Nov 27

Recursion

Examples: reverseOf, occurrencesOf
Recursion on Arrays: Creating Sub-Arrays
Recursion on Arrays: Call by Value

Announcements/Reminders

- Today's class: [notes template](#) posted
- **Lab5** released (deadline: Dec 2; **grace period** until Dec 9)
 - + Required background study: **abstract classes** & **interfaces**

Recursions on Strings

not a palindrome.

already diff $\rightarrow$ false.

Palindrome

1st & last chars same

there's a change the substring, minus 1st & last char, is a Palindrome.

"racecar"

"aracecar"

"racecar"

Reversal

rev("abcd")
 $\downarrow$
"dcba"

reverse of.

Number of Occurrences

occ("abca", 'a')

'a'

'b'

1 + occ("bcb", 'a')


0 + occ("bcb", 'b')

Problem: Palindrome

```

boolean isPalindrome(String word) {
    if (word.length() == 0 || word.length() == 1) {
        /* base case */
        return true;
    }
    else {
        /* recursive case */
        char firstChar = word.charAt(0);
        char lastChar = word.charAt(word.length() - 1);
        String middle = word.substring(1, word.length() - 1);
        return
            firstChar == lastChar
            && isPalindrome(middle);
    }
}
    
```


isP(abcb a)



if (fc == lc) {
return isP(middle);
}
else { return false; }

recursive case.

1) LHS is true → eval RHS
2) LHS is false → skip RHS




Problem: Reverse of a String


base cases

```
String reverseOf (String s) {  
    if (s.isEmpty()) { /* base case 1 */  
        return "";  
    }  
    else if (s.length() == 1) { /* base case 2 */  
        return s;  
    }  
    else { /* recursive case */  
        String tail = s.substring(1, s.length());  
        String reverseOfTail = reverseOf (tail);  
        char head = s.charAt(0);  
        return reverseOfTail + head;  
    }  
}
```

what if $s.length == 1$
"c".substring(1,1)



cba



a b c d

d c b a

alternative
approach
for implementing
reverse of .

Problem: Number of Occurrences

```
int occurrencesOf (String s, char c) {
    if (s.isEmpty()) {
        /* Base Case */
        return 0;
    }
    else {
        /* Recursive Case */
        char head = s.charAt(0);
        String tail = s.substring(1, s.length());
        if (head == c) {
            return 1 + occurrencesOf (tail, c);
        }
        else {
            return 0 + occurrencesOf (tail, c);
        }
    }
}
```

base.

$occ('ab', 'b')$

$a \neq b$
0

$+ occ('b', 'b')$

$1 + 1 = 2$
 $1 + 1 = 2$

$s \rightarrow$ [head] [tail]

head


tail

$1 \text{ if } head == c + occ(tail, c)$
 $0 \text{ if } head \neq c + occ(tail, c)$

$return head == c ? 1 + occ(tail, c) : occ(tail, c)$

Recursion on an Array: Passing new Sub-Arrays

```
void m(int[] a) {  
    if(a.length == 0) { /* base case */ }  
    else if(a.length == 1) { /* base case */ }  
    else {  
        int[] sub = new int[a.length - 1];  
        for(int i = 1; i < a.length; i++) { sub[i - 1] = a[i]; }  
        m(sub) } }  
}
```




Say $a1 = \{\}$, consider $m(a1)$

↳ base case #1.

Say $a2 = \{A, B, C\}$, consider $m(a2)$

loop time & space wasted to create sub-arrays between R.C.s.



Recursion on an Array: Passing Same Array Reference

"sub-arrays"

range of indices

to inspect in array



```
void m(int[] a, int from, int to) {
    if (from > to) { /* base case */ }
    else if (from == to) { /* base case */ }
    else { m(a, from + 1, to) } }
```

3, 2
2, 2

sub-array of size 0

sub-array of size 1

recursive call

* call by value: passing the ref. of 'a' around.

Say $a1 = \{\}$, consider $m(a1, 0, a1.length - 1) \rightarrow m(a1, 0, -1)$

$a1.length == 0$

1st index


last index

$from > to$


empty range of indices to look at
↳ empty sub-array

Say $a2 = \{A, B, C\}$, consider $m(a2, 0, a2.length - 1)$

$a2.length == 3$



Say $a2 = \{A, B, C\}$, consider $m(a2, \underline{0}, \underline{a2.length - 1})$



$m(a2, \underline{0}, \underline{2})$

↳ input array of length 3

$m(a2, \underline{1}, \underline{2})$

↳ sub-array of length 2

$m(a2, \underline{2}, \underline{2})$

↳ base case (as if sub-array of length 1).

As recursive calls are made, narrow down the intervals.

Lecture 24 - Dec 2

Recursion

Recursion on Arrays: allPositive, isSorted
Course Wrap-Up
Assigned Readings: Tower of Hanoi

Announcements/Reminders

- Today's class: [notes template](#) posted
- **Lab5** released (deadline: Dec 2; **grace period** until Dec 9)
 - + Required background study: **abstract classes** & **interfaces**
- **Review session** survey active now!
- **Exam guide**, example questions to be released

Problem: Are All Numbers Positive? ^{universal property} > 0 $\hookrightarrow 0$ is not positive.

Say $a = \{\}$

$\forall x \cdot P(x) \equiv \text{True}$ $\in \emptyset$ $x > 0$ there's no witness some violation

Say $a = \{4\}$

$\textcircled{T}$ $0 \leq 3$

Say $a = \{4, 7, 3, 9\}$

$\textcircled{T}$

Say $a = \{5, 3, -2, 9\}$

$\textcircled{F}$

existential property: $\exists x \cdot P(x) \equiv \text{False}$ $\in \emptyset$ $x > 0$ there's no witness to show some satisfaction.


$\text{allP}(\underline{a}, 0, 3)$

$\underline{a[0] > 0}$ $\&\&$ $\text{allP}(\underline{a}, 1, 3)$
 $4 > 0$
 $\textcircled{T}$

Problem: Are All Numbers Positive?

```
boolean → public allPositive(int[] a) {  
    return allPositiveHelper(a, 0, a.length - 1);  
}  
  
boolean → private allPositiveHelper(int[] a, int from, int to) {  
    if (from > to) { /* base case 1: empty range */  
        return true;  
    }  
    else if (from == to) { /* base case 2: range of one element */  
        return a[from] > 0;  
    }  
    else { /* recursive case */  
        return a[from] > 0 && allPositiveHelper(a, from + 1, to);  
    }  
}
```

call to a recursive helper method!



Tracing Recursion: `allPositive`

Say `a = {}`

`allPositive(a)`

`allPH(a,0,-1)`

```
boolean allPositive(int[] a) {  
    return allPositiveHelper(a, 0, a.length - 1);  
}  
  
boolean allPositiveHelper(int[] a, int from, int to) {  
    if (from > to) { /* base case 1: empty range */  
        return true;  
    }  
    else if (from == to) { /* base case 2: range of one element */  
        return a[from] > 0;  
    }  
    else { /* recursive case */  
        return a[from] > 0 && allPositiveHelper(a, from + 1, to);  
    }  
}
```

Tracing Recursion: allPositive

Say a = {4}

allPositive(a)


allPH(a,0,0)

a[0] > 0

```
boolean allPositive(int[] a) {  
    return allPositiveHelper(a, 0, a.length - 1);  
}  
  
boolean allPositiveHelper(int[] a, int from, int to) {  
    if (from > to) { /* base case 1: empty range */  
        return true;  
    }  
    else if (from == to) { /* base case 2: range of one element */  
        return a[from] > 0;  
    }  
    else { /* recursive case */  
        return a[from] > 0 && allPositiveHelper(a, from + 1, to);  
    }  
}
```

Tracing Recursion: **allPositive**

Say $a = \{4, 7, 3, 9\}$



```
boolean allPositive(int[] a) {  
    return allPositiveHelper(a, 0, a.length - 1);  
}  
  
boolean allPositiveHelper(int[] a, int from, int to) {  
    if (from > to) { /* base case 1: empty range */  
        return true;  
    }  
    else if (from == to) { /* base case 2: range of one element */  
        return a[from] > 0;  
    }  
    else { /* recursive case */  
        return a[from] > 0 && allPositiveHelper(a, from + 1, to);  
    }  
}
```

Tracing Recursion: allPositive

Say $a = \{5, 3, -2, 9\}$

$\text{allPositive}(a)$

$\text{allPH}(a, 0, 3)$

$a[0] > 0$

$5 > 0$

$\text{allPH}(a, 1, 3)$

$a[1] > 0$


$\text{allPH}(a, 2, 3)$

$a[2] > 0$

$\text{allPH}(a, 3, 3)$

```
boolean allPositive(int[] a) {  
    return allPositiveHelper(a, 0, a.length - 1);  
}  
  
boolean allPositiveHelper(int[] a, int from, int to) {  
    if (from > to) { /* base case 1: empty range */  
        return true;  
    }  
    else if (from == to) { /* base case 2: range of one element */  
        return a[from] > 0;  
    }  
    else { /* recursive case */  
        return a[from] > 0 && allPositiveHelper(a, from + 1, to);  
    }  
}
```

Sorting Orders of Arrays



not, $\neg$, !

non-descending

$\equiv \neg (\text{descending})$



$\equiv \neg (a[i] > a[i+1])$

$\equiv a[i] \leq a[i+1]$



ascending -

Equal to



decreasing/descending





increasing/ascending



non-descending



non-ascending



Problem: Are Numbers Sorted?

Say $a = \{\}$

true (∵ cannot find violation)

Say $a = \{4\}$

✓ Say $a = \{3, 6, 6, 7\}$

①

Say $a = \{3, 6, 5, 7\}$

②
false

$$\begin{aligned} a[0] &\leq a[1] \\ \&\& a[1] &\leq a[2] \\ \&\& a[2] &\leq a[3] \end{aligned}$$

from

isSorted($a, 0, 3$)

$a[0] \leq a[1] \&\& \text{isSorted}(a, \text{from}, \text{to})$

Problem: Are Numbers Sorted?

```
boolean isSorted(int[] a) {  
    return isSortedHelper(a, 0, a.length - 1);  
}  
  
boolean isSortedHelper(int[] a, int from, int to) {  
    if (from > to) { /* base case 1: empty range */  
        return true;  
    }  
    else if (from == to) { /* base case 2: range of one element */  
        return true;  
    }  
    else {  
        return a[from] <= a[from + 1]  
            && isSortedHelper(a, from + 1, to);  
    }  
}
```

Tracing Recursion: **isSorted**

Say $a = \{\}$

isSorted(a)

isSH(a,0,-1)

```
boolean isSorted(int[] a) {  
    return isSortedHelper(a, 0, a.length - 1);  
}  
  
boolean isSortedHelper(int[] a, int from, int to) {  
    if (from > to) { /* base case 1: empty range */  
        return true;  
    }  
    else if (from == to) { /* base case 2: range of one element */  
        return true;  
    }  
    else {  
        return a[from] <= a[from + 1]  
            && isSortedHelper(a, from + 1, to);  
    }  
}
```


Tracing Recursion: **isSorted**

Say $a = \{4\}$

isSorted(a)

isSH(a,0,0)


return **true**

```
boolean isSorted(int[] a) {  
    return isSortedHelper(a, 0, a.length - 1);  
}  
  
boolean isSortedHelper(int[] a, int from, int to) {  
    if (from > to) { /* base case 1: empty range */  
        return true;  
    }  
    else if (from == to) { /* base case 2: range of one element */  
        return true;  
    }  
    else {  
        return a[from] <= a[from + 1]  
            && isSortedHelper(a, from + 1, to);  
    }  
}
```

Tracing Recursion: **isSorted**

Say $a = \{3, 6, 6, 7\}$


```
boolean isSorted(int[] a) {  
    return isSortedHelper(a, 0, a.length - 1);  
}  
  
boolean isSortedHelper(int[] a, int from, int to) {  
    if (from > to) { /* base case 1: empty range */  
        return true;  
    }  
    else if (from == to) { /* base case 2: range of one element */  
        return true;  
    }  
    else {  
        return a[from] <= a[from + 1]  
            && isSortedHelper(a, from + 1, to);  
    }  
}
```





Tracing Recursion: **isSorted**

Say $a = \{3, 6, 5, 7\}$

```
boolean isSorted(int[] a) {  
    return isSortedHelper(a, 0, a.length - 1);  
}  
  
boolean isSortedHelper(int[] a, int from, int to) {  
    if (from > to) { /* base case 1: empty range */  
        return true;  
    }  
    else if (from == to) { /* base case 2: range of one element */  
        return true;  
    }  
    else {  
        return a[from] <= a[from + 1]  
            && isSortedHelper(a, from + 1, to);  
    }  
}
```



Exam Info

- When: 9am to 12pm, Tuesday, December 16 (TM Tait)
- Format: Some Multiple Choice & Mostly **Written** 
- Coverage: **Everything** (lecture materials & labs)
 - + slides, iPad notes, code examples
 - + resources on recursion
- Even problems that look **challenging** at first are built on the same **foundational techniques** you've learned and practiced in lectures and labs. A **solid, reflective** grasp of the basics will take you farther than memorizing examples.
- Restrictions: 
 - + No data sheet + No sketch paper (Exam booklet includes it)
- What you should bring:
 - + Valid, Physical Photo ID (strict) + Water/Snack

I hope you enjoyed learning with me 



All the best to you! 