

EECS2030 Summer 2025

Additional Notes

Solving Problems Recursively

Chen-Wei Wang

Given a problem of size n (e.g., an integer of value n , an array of n elements, *etc.*), adopt the following steps to solve the problem *recursively*:

Step 1: Understand the Problem We denote the original problem to be solved as P_n

(i.e., a problem P , where the subscript n denotes its size). For example:

Example 1. Compute the factorial of n .

Example 2. Compute the n^{th} number in the Fibonacci sequence.

Example 3. Compute if a string s of length n is a palindrome.

Example 4. Compute the reverse of a string s of length n .

Example 5. Compute the number of occurrences of a character c in a string s of length n .

Example 6. Compute if elements in index range $[from, to]$ of an array a are all positive.

Example 7. Compute if elements in index range $[from, to]$ of an array a are sorted in a non-descending order.

Step 2: Define the Base Cases We first define the solutions to the same problem whose sizes are small so that they can be solved immediately: P_0, P_1, P_2 , *etc.* For example:

Example 1. Factorial 0 is just 1.

Example 2. The first and second Fibonacci numbers are both 1.

Example 3. An empty string and a string of length one are both palindromes.

Example 4. The reverse of an empty string or of a string of length one is simply the string itself.

Example 5. The number of occurrences of any character in an empty string is 0.

1. If index range $[from, to]$ is such that $from > to$, e.g., $[3, 2]$, then there is an empty collection of elements to be considered.

Example 6. Since you cannot find a counter-example (i.e., a number which is not positive) from an empty collection, the result of determining all numbers being positive is simply *true*.

Example 7. Since you cannot find a counter-example (i.e., a pair of adjacent numbers which are not sorted in a non-descending order) from an empty collection, the result of determining all numbers in an empty collection being sorted in a non-descending order is simply *true*.

2. If index range $[from, to]$ is such that $from == to$, e.g., $[3, 3]$, then there is a collection of exactly one element to be considered. We call such a collection a *singleton* collection. Say e is such an element that a singleton collection contains.

Example 6. The result of determining all numbers being positive is simply $e > 0$.

Example 7. Since you cannot find a counter-example (i.e., a pair of adjacent numbers which are not sorted in a non-descending order) from a collection of just one number, the result of determining all numbers in a singleton collection being sorted in a non-descending order is simply *true*.

Step 3: Assume that Solutions to Smaller Problems Exist We then assume that there exist solutions to **sub-problems** whose sizes are strictly smaller than the original problem: e.g., P_{n-1}, P_{n-2} , *etc.* For example:

Example 1. Assume the factorial of $n - 1$ already exists (where $n > 0$). We denote this solution as P_{n-1} as its input size (i.e., value of number) is exactly one less than the original problem.

Example 2. Assume the $(n-1)^{th}$ and $(n-2)^{th}$ numbers in the Fibonacci sequence already exist (where $n > 2$). We denote these solutions as P_{n-1} and P_{n-2} as their input sizes (i.e., position in the Fibonacci sequence) are exactly, respectively, one and two less than the original problem.

Example 3. Assume we already know if a smaller substring of s (where $s.length() > 1$), with the first and last characters of s taken out, is a palindrome. We denote this solution as P_{n-2} as its input size (i.e., length of string) is two less than the original problem.

Example 4. Assume we already know the reverse of a smaller substring of s (where $s.length() > 1$), with the first character of s taken out. We denote this solution as P_{n-1} as its input size (i.e., length of string) is one less than the original problem.

Example 5. Assume we already know the the number of occurrences of a character c in a smaller substring of s (where $s.length() > 0$), with the first character of s taken out. We denote this solution as P_{n-1} as its input size (i.e., length of string) is one less than the original problem.

We assume we already know the solution for elements in a smaller index range $[from + 1, to]$ of an array a :

Example 6. We denote P_{n-1} as the solution for if the $n-1$ elements are all positive.

Example 7. We denote P_{n-1} as the solution for if the $n-1$ elements are sorted in a non-descending order.

Step 4: Define the Recursive Cases

We finally define the solution to the original problem P_n in terms of the solutions to other strictly smaller sub-problems: $P_n = f(P_{n-1}, P_{n-2}, \dots)$. That is, P_n is defined as a function f that combines solutions to strictly smaller problems P_{n-1} , P_{n-2} , etc. via some simple calculations. Informally speaking, we “massage” solutions to smaller problems into the solution to a bigger problem. For example:

Example 1. We define $P_n = n \times P_{n-1}$.

Example 2. We define $P_n = P_{n-1} + P_{n-2}$.

Example 3. We define $P_n = (c1 == c2 \ \&\& \ P_{n-2})$ (where $c1$ and $c2$ are, respectively, the first and the last characters of s). For example, $abcb$ is a palindrome because $a == c$ and bcb is a palindrome. However, $abccc$ is not a palindrome because bcc is not a palindrome, even though $a == c$.

Example 4. We define $P_n = P_{n-1} + c1$ (where $c1$ is the first character of s , and the operator $+$ means string concatenation). For example, the reverse of $abcd$ is the reverse of abc (which is $dcba$) concatenated with d .

Example 5. We define $P_n = 1 + P_{n-1}$ if the first character of s matches c , and in case they do not match, we define $P_n = 0 + P_{n-1}$. For example, the number of occurrences of character a in string $ababa$ is 1 ($\because a$ matches the first character in the string) plus the number of occurrences of a in $baba$ (which is 2). But, the number of occurrences of character b in string $ababa$ is 0 ($\because b$ does not the first character a in the string) plus the number of occurrences of b in $baba$ (which is 2).

Example 6. We define $P_n = a[from] > 0 \ \&\& \ P_{n-1}$. For example, numbers in $\{1, 2, 3, 4, 5\}$ are all positive because $1 > 0$ and numbers in $\{2, 3, 4, 5\}$ are all positive. But, numbers in $\{-1, 2, 3, 4, 5\}$ are not all positive because $-1 > 0$ is *false*, even though and numbers in $\{2, 3, 4, 5\}$ are all positive. Also, numbers in $\{1, 2, -3, 4, 5\}$ are not all positive because numbers in $\{2, -3, 4, 5\}$ are not all positive, even though $1 > 0$ is *true*.

Example 7. We define $P_n = a[from] \leq a[from + 1] \ \&\& \ P_{n-1}$. For example, say $from$ is 0, then numbers in $\{1, 2, 2, 3, 4\}$ are sorted because $1 \leq 2$ and numbers in $\{2, 2, 3, 4\}$ are sorted. But, numbers in $\{1, -1, 2, 3, 4\}$ are not sorted because $1 \leq -1$ is *false*, even though numbers in $\{-1, 2, 3, 4\}$ are sorted. Also, numbers in $\{1, 2, 2, -1, 4\}$ are not sorted because numbers in $\{2, 2, -1, 4\}$ are not sorted, even though $2 \leq 2$ is *true*.

| Problem (P_n) | Base Case(s) (P_0, P_1, P_2) | Recursive Solution(s) to Sub-Problem(s) (P_{n-1}, P_{n-2}) | Solution |
|--------------------------|--|---|--|
| $factorial(n)$ | $P_0 = factorial(0) = 1$ | $P_{n-1} = factorial(n-1)$ | $n \times P_{n-1}$ |
| $fib(n)$ | $P_1 = fib(1) = 1$ $P_2 = fib(2) = 1$ | $P_{n-1} = fib(n-1)$ $P_{n-2} = fib(n-2)$ | $P_{n-1} + P_{n-2}$ |
| $isP(s)$ | $P_0 = isP("") = true$ $P_1 = isP("a") = true$ | $P_{n-2} = isP(s.substring(1, s.length() - 1))$ | $s.charAt(0) == charAt(s.length() - 1)$ && P_{n-2} |
| $rev(s)$ | $P_0 = rev("") = ""$ $P_1 = rev("a") = "a"$ | $P_{n-1} = rev(s.substring(1, s.length()))$ | $P_{n-1} + s.substring(0)$ |
| $occ(s, c)$ | $P_0 = occ("", c) = 0$ | $P_{n-1} = occ(s.substring(1, s.length()), c)$ | $1 + P_{n-1}$ if $s.charAt(0) == c$ $0 + P_{n-1}$ if $s.charAt(0) != c$ |
| $allPosH(a, from, to)$ | $P_0 = allPosH(a, from, to)$ = true if $from > to$ $P_1 = allPosH(a, from, to)$ = $a[from] > 0$ if $from == to$ | $P_{n-1} = allPosH(a, from + 1, to)$ | $a[0] > 0$ && P_{n-1} |
| $isSortedH(a, from, to)$ | $P_0 = isSortedH(a, from, to)$ = true if $from > to$ $P_1 = isSortedH(a, from, to)$ = true if $from == to$ | $P_{n-1} = isSortedH(a, from + 1, to)$ | $a[from] \leq a[from + 1]$ && P_{n-1} |