

First Design Attempt

```
public class Student {  
    private Course[] courses;  
    private int noc;  
  
    private int kind;  
    private double premiumRate;  
    private double discountRate;  
  
    public Student (int kind){  
        this.kind = kind;  
    }  
    ...  
}
```

```
public double getTuition(){  
    double tuition = 0;  
    for(int i = 0; i < this.noc; i++){  
        tuition += this.courses[i].fee;  
    }  
    if (this.kind == 1) {  
        return tuition * this.premiumRate;  
    }  
    else if (this.kind == 2) {  
        return tuition * this.discountRate;  
    }  
}
```

```
public void register(Course c){  
    int MAX = -1;  
    if (this.kind == 1) { MAX = 6; }  
    else if (this.kind == 2) { MAX = 4; }  
    if (this.noc == MAX) { /* Error */ }  
    else {  
        this.courses[this.noc] = c;  
        this.noc ++;  
    }  
}
```

dupl

dup2.

Good design?

Judge by Single Choice Principle


- **Repeated** if-conditions
- A new kind is **introduced**?
- An existing kind is **obsolete**?

Testing Student Classes (without inheritance)

```
public class ResidentStudent {
    private String name;
    private Course[] courses; private int noc;
    private double premiumRate; /* assume a m
    public ResidentStudent (String name) {
        this.name = name;
        this.courses = new Course[10];
    }
    public void register(Course c) {
        this.courses[this.noc] = c;
        this.noc ++;
    }
    public double getTuition() {
        double tuition = 0;
        for(int i = 0; i < this.noc; i ++) {
            tuition += this.courses[i].fee;
        }
        return tuition * this.premiumRate;
    }
}
```

```
public class NonResidentStudent {
    private String name;
    private Course[] courses; private int noc;
    private double discountRate; /* assume a
    public NonResidentStudent (String name) {
        this.name = name;
        this.courses = new Course[10];
    }
    public void register(Course c) {
        this.courses[this.noc] = c;
        this.noc ++;
    }
    public double getTuition() {
        double tuition = 0;
        for(int i = 0; i < this.noc; i ++) {
            tuition += this.courses[i].fee;
        }
        return tuition * this.discountRate;
    }
}
```

```
public class StudentTester {
    public static void main(String[] args) {
        Course c1 = new Course("EECS2030", 500.00); /* title and fee */
        Course c2 = new Course("EECS3311", 500.00); /* title and fee */
        ResidentStudent jim = new ResidentStudent("J. Davis");
        jim.setPremiumRate(1.25);
        jim.register(c1); jim.register(c2);
        NonResidentStudent jeremy = new NonResidentStudent("J. Gibbons");
        jeremy.setDiscountRate(0.75);
        jeremy.register(c1); jeremy.register(c2);
        System.out.println("Jim pays " + jim.getTuition());
        System.out.println("Jeremy pays " + jeremy.getTuition());
    }
}
```



Student Classes (without inheritance): Maintenance (1)

```
public class ResidentStudent {
    private String name;
    private Course[] courses; private int noc;
    private double premiumRate; /* assume a m
    public ResidentStudent (String name) {
        this.name = name;
        this.courses = new Course[10];
    }
    public void register(Course c) {
        this.courses[this.noc] = c;
        this.noc ++;
    }
    public double getTuition() {
        double tuition = 0;
        for(int i = 0; i < this.noc; i ++) {
            tuition += this.courses[i].fee;
        }
        return tuition * this.premiumRate;
    }
}
```

```
public class NonResidentStudent {
    private String name;
    private Course[] courses; private int noc;
    private double discountRate; /* assume a
    public NonResidentStudent (String name) {
        this.name = name;
        this.courses = new Course[10];
    }
    public void register(Course c) {
        this.courses[this.noc] = c;
        this.noc ++;
    }
    public double getTuition() {
        double tuition = 0;
        for(int i = 0; i < this.noc; i ++) {
            tuition += this.courses[i].fee;
        }
        return tuition * this.discountRate;
    }
}
```

Maintenance e.g., a new registration constraint:

```
if(numberOfCourses >= MAX_ALLOWANCE) {
    throw new TooManyCoursesException("Too Many Courses");
}
else { ... }
```

Student Classes (without inheritance): Maintenance (2)

```
public class ResidentStudent {
    private String name;
    private Course[] courses; private int noc;
    private double premiumRate; /* assume a m
    public ResidentStudent (String name) {
        this.name = name;
        this.courses = new Course[10];
    }
    public void register(Course c) {
        this.courses[this.noc] = c;
        this.noc ++;
    }
    public double getTuition() {
        double tuition = 0;
        for(int i = 0; i < this.noc; i ++) {
            tuition += this.courses[i].fee;
        }
        return tuition * this.premiumRate;
    }
}
```



```
public class NonResidentStudent {
    private String name;
    private Course[] courses; private int noc;
    private double discountRate; /* assume a
    public NonResidentStudent (String name) {
        this.name = name;
        this.courses = new Course[10];
    }
    public void register(Course c) {
        this.courses[this.noc] = c;
        this.noc ++;
    }
    public double getTuition() {
        double tuition = 0;
        for(int i = 0; i < this.noc; i ++) {
            tuition += this.courses[i].fee;
        }
        return tuition * this.discountRate;
    }
}
```

Maintenance e.g., a new **tuition** formula:

```
/* ... can be premiumRate or discountRate */
...
return tuition * inflationRate * ...;
```

A Collection of Students (**without** inheritance)

```
public class StudentManagementSystem {  
    private ResidentStudent[] rss;  
    private NonResidentStudent[] nrss;  
    private int nors; /* number of resident students */  
    private int nonrs; /* number of non-resident students */  
    public void addRS(ResidentStudent rs){ rss[nors]=rs; nors++; }  
    public void addNRS(NonResidentStudent nrs){ nrss[nonrs]=nrs;nonrs++; }  
    public void registerAll(Course c) {  
        for(int i = 0; i < nors; i ++){ rss[i].register(c); }  
        for(int i = 0; i < nonrs; i ++){ nrss[i].register(c); }  
    }  
}
```




Recall: Student Classes (with inheritance)

```
class Student {
    String name;
    Course[] registeredCourses;
    int numberOfCourses;
    Student (String name) {
        this.name = name;
        registeredCourses = new Course[10];
    }
    void register(Course c) {
        registeredCourses[numberOfCourses] = c;
        numberOfCourses ++;
    }
    double getTuition() {
        double tuition = 0;
        for(int i = 0; i < numberOfCourses; i ++) {
            tuition += registeredCourses[i].fee;
        }
        return tuition; /* base amount only */
    }
}
```

```
class ResidentStudent extends Student {
    double premiumRate; /* there's a mutator method */
    ResidentStudent (String name) { super(name); }
    /* register method is inherited */
    double getTuition() {
        double base = super.getTuition();
        return base * premiumRate;
    }
}
```

```
class NonResidentStudent extends Student {
    double discountRate; /* there's a mutator method */
    NonResidentStudent (String name) { super(name); }
    /* register method is inherited */
    double getTuition() {
        double base = super.getTuition();
        return base * discountRate;
    }
}
```


Student Classes (with inheritance): Expectations



```
Student s = new Student("Stella");
ResidentStudent rs = new ResidentStudent("Rachael");
NonResidentStudent nrs = new NonResidentStudent("Nancy");
```

[illegible]

Intuition: Polymorphism



```
1 Student s = new Student("Stella");
2 ResidentStudent rs = new ResidentStudent("Rachael");
3 rs.setPremiumRate(1.25);
4 s = rs; /* Is this valid? */
5 rs = s; /* Is this valid? */
```